Daikin One+ Smart Thermostat Installation & Commissioning (S21)



Technical Training Module TRC-4



This material provides technical information that is to only be used by appropriately trained and certified HVAC-R installers and technicians who have agreed to the terms and conditions available here at https://www.daikincity.com/DaikinCityB2BTermsOfUse.html. If you have not agreed to these terms and conditions, you may not use or view this material, and you assume responsibility for any injury or property, system or equipment damage which may result. If you have agreed to these terms, you also agree, by viewing or using this material, that this material, by its nature, cannot include a discussion of everything necessary to effect a proper installation or repair of HVAC-R equipment, nor can it address every possible scenario or environment a technician or installer may encounter. Accordingly, this material should not be considered as recommendations for best practices and will not be considered installation or repair instructions to the extent of any conflict with Daikin- or Goodman-issued manuals and specifications, or industry standards and regulations. Each installer or technician remains fully responsible for ensuring proper installation or repair of the HVAC-R equipment being worked on, and you remain fully responsible for any injury or property, system or equipment damage which may result from your installation. ©2021 Daikin, all rights reserved; recording, copying, or distribution of this material is prohibited without express written permission from Daikin.



Agenda

Daikin One+

System Configurations

Installing Daikin One+

Commissioning Daikin One+

Full Set-up

Dealer Navigation

Homeowner Navigation

Mobile Apps



- Premium control that provides optimal comfort.
- Easy to use, energy efficient, reliable, and ensures that the system is set up properly.
- Designed to regulate and communicate with HVAC equipment.
- The user will be able to control the indoor unit remotely through the Daikin One Home app.







Daikin One+ Smart Thermostat

- Offers communication when combined with Single and Multi-Zone indoor unit models (S21 only).
- Is a cloud-connected hub and controller for communicating HVAC systems.





Daikin One+ Interface

- The thermostat has a physical dial on the right used for manual setpoints adjustments.
- Pressing the center of the dial at any time during normal mode acts as a home button, displaying the primary screen.
- The high-resolution touch screen on the left supports tactile-based interactions.
- Navigating to each screen is done by tapping an icon.





Daikin One+ Smart Thermostat

Messaging

- Daikin One's messaging updates, confirms, and informs about selections you make during set-up and operation.
- There are four types of messages:
 - Status
 - Alerts
 - Reminders and Prompts
 - Learn more/tips

Note: Alerts have priority over all other messages in the system.





Messaging

 The homeowner can temporarily dismiss the message or restart the system; however, some alerts may remain until the issue is resolved by a dealer.





Daikin One+ Smart Thermostat

Packaging

- Welcome documentation.
 - Includes quick reference cards.
- Daikin One+ smart thermostat.
- Translation adapter with cover, mounting plate and power cable.
- Double-sided adhesive tape.
- Mounting screws.
 - One set for thermostat.
 - One set for translation adapter.
- Thermostat terminal plate.
- S21 cable.
- Optional trim plate.





Quick Reference Card

 Quick reference cards are packaged with the thermostat to help answer questions during the installation and commissioning. Scanning the bar code on the bottom left corner will link you to a website related to the title of the card.



https://daikinone.com/smart_thermostats/oneplus/pros/



Agenda

Daikin One+

System Configurations

Installing Daikin One+

Commissioning Daikin One+

Full Set-up

Dealer Navigation

Homeowner Navigation

Mobile Apps



Daikin One+ Smart Thermostat for S21 Indoor Units









Notes: the Daikin *One*+ is not compatible with: handheld IR remote controller – BRC944 – KRP928

Indoor units that do not have S21 Interface





Indoor Unit Models (require interface adaptor)	Required Interface Adaptor
FTXM09VVJU, FTXM12VVJU, FTXM18VVJU, FTXM24VVJU	KER087A41
FTX09NMVJU, FTX12NMVJU	KRP067A41E
FTX15NMVJU	KRP980B2E



Agenda

Daikin One+

System Configurations

Installing Daikin One+

Commissioning Daikin One+

Full Set-up

Dealer Navigation

Homeowner Navigation

Mobile Apps



Installing Daikin One+ Smart Thermostat

- Mount the thermostat to be
 - Leveled.

AIR INTELLIGENCE

- Approximately 5' from the floor.
- On an interior wall using the included screws.





- Maximum wire distance between the Daikin One+ and the translation adaptor should not exceed
 125 feet using four conductor 18-gauge field supplied wire.
- Check for proper voltage before and after wiring is installed.
 - 0.6VDC between Data 1 and 2.
 - 24VDC between R and C.
 - Refer to system I/O manual for proper voltage.

Note: If wired incorrectly, you will receive an error.

• If power wires are reversed the PWR LED will flash green.



Data Line 1
 Data Line 2
 Data Line 2
 24 volt common
 24 volt power



Aux1 to Aux 1C and Aux 2 to Aux 2C connections are 24V AC Dry contacts.



DO NOT Install The Thermostat Where It Can Be Affected By:

- Drafts or dead spots behind doors and in corners.
- Hot or cold air from ducts or ceiling fans.
- Radiant heat from the sun or appliances.
- Concealed pipes and chimneys.
- Unheated (uncooled) areas such as an outside wall.





Wiring thermostat to a translation adaptor





Installing Translation Adaptor

Mounting the translation adaptor.

- Mount using screws or adhesive tape.
 - Never use screws to mount to an indoor unit.
 - If using adhesive tape, you can mount to the surface of the indoor unit.
 - Clean the surface prior to mounting.
 - Apply pressure for a minimum of 20 seconds to the adaptor for adhesion to take place.





Wall mounted indoor unit

 Translation adaptor can be mounted inside piping chase to conceal it, or on the outside of the indoor unit.



Ducted indoor unit

 Translation adaptor can be mounted on the side and top of the indoor unit, or above the ceiling using supplied double-sided adhesive tape.





Agenda

Daikin One+ System Configurations Installing Daikin One+ Commissioning Daikin One+ Full Set-up

Dealer Navigation Homeowner Navigation Mobile Apps



- Begin set-up: walks installers through the entire commissioning process to ensure the system is configured properly and ready for the homeowner to use.
 - Enables random access to any setting.
 - Remembers settings as they are entered.
 - Individual may stop and restart as needed.
- The screens are populated based on the model numbers of the equipment, matched to a database of device configuration settings.





- Start-up screen is displayed upon powering the thermostat.
- The welcome screen displays preferences to choose from.
- Select Single/Multi-split (S21) before moving to the setup screen.
- Version of the thermostat is displayed on the learn more screen.

V DAIKIN		< VDAIKIN
welcome		setup
Choose the language you would like to use to set up your Daikin thermostat.		The Daikin smart thermostat saves each step as you proceed. You can always go back and change your settings
english 🔘		baox and change your octange.
español 🔿		
français 🔿	equipment type	
	This setting will affect the equipment	begin setup >
use large font	detected by your thermostat.	setup options >
continue >	unitary O	learn more >
	single/multi-split (S21)	
	VRV,SkyAir,single/multi-split (P1/P2)	
	continue >	



Agenda

Daikin *One*+ System Configurations Installing Daikin *One*+ Commissioning Daikin *One*+

Full Set-up

Dealer Navigation Homeowner Navigation Mobile Apps



Full Set-up

Start-up

- Tapping begin set-up starts the five step set-up process:
 - Communication.
 - Personalization.
 - Equipment Set-up.
 - System Optimization.
 - Preferences.
- Note: All steps must be completed and reviewed before completing set-up to ensure the system is configured properly and ready for the homeowner to use.

For detailed menu settings https://daikinone.com/smart_thermostats/oneplus/pros/

< VDAIKIN	
smart thermostat setup	
1 communication	\rightarrow
2 personalization	\rightarrow
3 equipment setup	\rightarrow
4 system optimization	\rightarrow
5 preferences	\rightarrow
complete setup	\rightarrow



Step 1 - Communication

- Configures Communication Networks.
- Select home Wi-Fi to search for networks.
- With Wi-Fi configured, the system can check the software version and update software to the latest version automatically.

Note:

- Wireless router must be password protected.
 - Compatible with 5Ghz routers which supports 2.4Ghz
- Equipment type displays the equipment selected on start up.

DAIKIN		< communica	ation
smart thermostat setup		equipment type	S21 >
1 communication	\rightarrow	home wifi	disconnected >
2 personalization	\rightarrow		
3 equipment setup	\rightarrow		
4 system optimization	\rightarrow		
5 preferences	\rightarrow		
complete setup	\rightarrow		
		previous step	o next step



Step 2 - Personalization

- Tapping the personalization tab allows you to edit default information.
- Personalization displays:
 - Language.
 - Large font selection.
 - Date & Time.
 - If Wi-Fi is connected, date & time sets automatically.
 - Thermostat Name.
 - Degree Units.

Note: A green check mark appears next to items reviewed from the set-up menu.

DAIKIN		< personalization
smart thermostat setup		language english >
1 communication	\rightarrow	use large font
		date & time 7/14/2020, 7:48 AM >
2 personalization	\rightarrow	device name main room >
3 equipment setup	\rightarrow	degree units fahrenheit >
4 system optimization	\rightarrow	
5 preferences	\rightarrow	
complete setup	\rightarrow	
		previous step next step



Step 3 - Equipment Set-up

- Provides a list of equipment and accessories to add or remove from.
 - You must manually enter the equipment serial number to the indoor and outdoor unit after the model number is selected.

DAIKIN		<	equipment setu	ıp
smart thermostat setup		×	indoor unit	>
		\star	outdoor unit	>
1 communication	\rightarrow		standard filter	>
2 personalization	\rightarrow		add equipment	÷
3 equipment setup	\rightarrow			
4 system optimization	\rightarrow			
5 preferences	\rightarrow			
complete setup	\rightarrow			
			previous step	next step



Step 3 - Equipment Set-up

For the indoor unit, you must select unit type if you manually enter a model number.

< equipment setu	р	< indoor unit				CTXS >
🔆 indoor unit	>	→ model #				FUXS > FTK > FTX >
× outdoor unit	>	serial #	>	< serial	#	TXG > TXR >
standard filter	>	→ unit type	>			× ^
add equipment	\oplus					< unit type
				1 2 3 - / : #+=	4 5 6 7 8 9 ; () \$ 8 0	wall-mount unit
				abc	ď	one-way blow cassette
						concealed ducted unit
previous step	next step					



< model #

Step 4 – System Optimization

- System optimization displays:
 - Error history.
 - Logs alerts with an error code.
 - White = not critical
 - Yellow = critical
- Calibration. Thermostat must be in OFF mode.
 - Wait 30 minutes before calibration for the thermostat to equalize.
- Status.
 - The status menu displays data pertaining to the selected equipment.

DAIKIN		< system optimiz	ation
smart thermostat setup		error history	>
1 communication	\rightarrow		/
2 personalization	\rightarrow	status 	>
3 equipment setup	\rightarrow		
4 system optimization	\rightarrow		
5 preferences	\rightarrow		
complete setup	\rightarrow		
		previous step	next step



Step 5 - Preferences

- There are four preference settings to choose from in order to optimize your systems performance.
 - Cool/Heat
 - House settings
 - Dealer information
 - Reminders

Note:

- Dealer contact information and reminders should be inputted.
 - The homeowner cannot edit service reminders.

DAIKIN		< preferences
smart thermostat		cool/heat >
		house settings
1 communication	\rightarrow	dealer information
2 personalization	\rightarrow	reminders >
3 equipment setup	\rightarrow	
4 system optimization	\rightarrow	
5 preferences	\rightarrow	
complete setup	\rightarrow	
		previous step next step

Step 5 - Preferences

Cool/heat:

- Min/max set points in 1°F increments:
 - heating: 57 to 86
 - cooling: 64 to 90
- Deadband
 - Differential between cooling and heating set point in auto mode.
 - Default: 4°
 - 2°F to 9°F in 1°F increments
- Overcool
 - Default: 0°
 - 0°F to 3°F in 1°F increments

<	preferences		
	cool/heat	>	
	house settings	>	
	dealer information	>	
	reminders	>	
	previous step	next step	

< deadband / overcool

Temperature setpoint deadband:

3	
vercooling allowed to dehumidify:	
0 °F	
1	

The overcool value is overlayed on the deadband, increasing the range to maintain minimum cool/heat differential of at least 2°.



Overcool Example

- The Thermo-ON/OFF deadband is a fixed value (± 1°F) for mini and multi split indoor unit.
- Thermo-ON/OFF when Overcool =0
 - CSP is the cooling setpoint that assigned by the user and displayed on the Daikin One+



- Thermo-ON/OFF when Overcool =2
 - Over CSP is internally calculated and is not displayed on the Daikin One+





Full Set-up

Step 5 - Preferences

- Auto changeover methods:
 - At 1°F above cool or 1°F below heat setpoint (default)(Configurable between 1°F 4°F.)
 - Engages changeover timer (guard timer).
 - Another 1°F above cooling or 1°F below heating changeover points(C-COP/H-COP)(default), immediate changeover ignores changeover timer (Configurable between 1°F 4°F.)
 - Changeover timer to prevent frequent mode change.
 - 0 (default),15, 30, 45 or 60 minutes.
- Recommend leaving the default settings.



Dealer information

- Selecting allows you to enter and review the dealer's information.
- All the information imputed can be viewed by the homeowner.

< preferences		< dealer		information	
cool/heat	>		name	some dealer	>
house settings	>		phone	(123) 456-7890	>
dealer information	>		email	hello@example.com	>
reminders	>		website	http://www.example.com	>
			message	Thanks for choosing so	>
previous step	next step				



Final step - Complete set-up

 Selecting complete set-up will conclude the full set-up of the thermostat and display normal mode for you to navigate and verify settings.

Reminder: All steps must be reviewed before completing full set-up.





(¥)

Agenda

Daikin *One*+ System Configurations Installing Daikin *One*+ Commissioning Daikin *One*+ Full Set-up

Dealer Navigation

Homeowner Navigation

Mobile Apps



Dealer Navigation

Dealer edit

- Navigating to dealer edit will allow you to access or revisit the installer set-up screen.
- Advanced adjustments to the Daikin *One*+ will be made here.



<	settings		<
		/	
	air quality	>	
	humidity	>	
	energy	>	
	thermostat	>	
	equipment	>	
	support	>	
	dealer edit	>	
	~ ^		

configuration	
dealer	
date & time	
messages	
Warning This feature accesses features of your syste the configuration can operation.	s advanced em. Any changes to prevent proper
	C



Dealer Navigation

- Acknowledging the prompt enables you to tap the learn more icon.
- The icon displays the installer code, giving you access to the installer set-up screens.



Enter your 4-digit PIN to unlock the thermostat:



unlock thermostat

(7	V	V	e	Ģ	ľ		1	t	}	/	ι	l	i		C)	k)
	6	à	S	6	C	ł	1	f	ç	J	ł	١	j	j	ŀ	<			
	Û		Z	Z	>	<	C	2	١	/	k)	r	۱	n	n	×]
	123														d	on	е		



А

dealer edit

Dealer edit accesses the advanced settings for the thermostat created during the initial setup process.

Each thermostat has an unique installer code used to unlock the thermostat's advanced settings — last four characters of the thermostat's MAC address.

This thermostat's installer code is:





Agenda

Daikin One+ System Configurations Installing Daikin One+ Commissioning Daikin One+ Full Set-up **Dealer Navigation** Homeowner Navigation Mobile Apps



Normal Mode

- Normal mode allows you to view messaging, temperature, and access settings to adjust parameters placed by the installer.
- Navigating is accomplished by tapping icons or turning the analog dial.
- Note: Analog turn dial is used to adjust temperature only. Pressing the dial returns to the home screen.





Homeowner Navigation

Adjust control

- Tapping the system mode icon allows you to select:
 - Auto. (cool & heat)
 - Cool.
 - Heat.
 - Off.
 - Emergency heat. (heat pump only)
- Tapping the arrow icons or rotating the dial will adjust setpoints that are displayed. You can also slide the setpoints to the desired temperature.





Homeowner Navigation

Schedule

- The schedule is presented as 7 days, displaying one day at a time, with 24 hours fitting on the screen.
- You can use the drop-down menu or swipe to enable schedule editing.
- Copy and paste is a feature that makes scheduling seamless.

Note: Unlike other screens, scheduling requires saving edits before exiting the mode.



tuesday ~	×
awake 6:00 am	
sleep 10:00 pm	
copy day	
to:	
s m t w	t f s
cancel	paste



Away

- The away screen displays the current state (on/off) and the away cooling/heating setpoints used when away is on.
 - on/off is selected from drop down menu.
- User can change the values of the setpoints by dragging the numbers or the comfort range up and down.
- With the mobile application, enabling geo-fencing will automatically switch to away mode when **outside** the radius.
 - Settings must be configured in the mobile application.

away on	< away
82°	Use away mode whenever you want to save energy or automatically based on the location of your phone.
indoor	on O
72° —	away temperatures 61°/82° >
61°	The system can automatically toggle away mode using the geofencing feature of the Daikin One Home mobile app.
	receive geofencing events
$\widehat{\Box} \boxplus \bigotimes \bigotimes $	



Air quality

- The air quality screen displays indoor air quality levels, outdoor air quality, and weather (when connected to the internet and paired with the app.)
- If air quality sensors are not installed, indoor air quality is based on filter life cycle and humidity values.
- Selecting indoor air quality from the air quality screen allows you to access one clean and air quality history.
 - One clean runs the fan, at high speed for three hours, to circulate and filter the indoor air.



< indoor air quality	(i)
moderate	
particles	
প্য chemicals	
run one clean	>
air quality history	>



Homeowner Navigation

Settings

- Settings gives you access to additional supporting features:
 - Display.
 - Adjust and enable visual features.
 - Comfort.
 - Set target humidity.
 - Configuration.
 - App. account setup
 - Dealer information
 - Date & Time
 - Enable messages/view alerts
 - System components
 - Home Wi-Fi

AIR INTELLIGENCE



settings		
system mode		>
schedule		>
away		>
display		>
sound		>
reminders		>
date & time		>
:e	~	

Agenda

Daikin One+ System Configurations Installing Daikin One+ Commissioning Daikin One+ Full Set-up **Dealer Navigation** Homeowner Navigation

Mobile Apps



Mobile Apps

Account set-up

- Setting up an account is a four-step process.
 - 1. Downloading the application from your IOS or Android application store.
 - Creating the account.
 - 2. Confirming your account.
 - 3. Adding the thermostats' location.
 - 4. Connecting the app to the thermostat.

Note: A mobile device, the Daikin One+ connected to Wi-Fi that is wired to an S21 system and a valid email address is needed to create a mobile account.







Step 1 - Create the account

- Tapping create one at the bottom right corner of the login screen will start the process.
- Before agreeing, read the terms and service, privacy statement, and other notices.
- Fill in your name, valid email address, and password.





Step 2 - Confirming the account

- You will be prompted to access the email address you provided when creating the account.
- A welcome email will appear in your inbox providing a six-digit code.
- Entering the six-digit code on your phone app. will allow you to continue.





Mobile Apps

Step 3 - Adding the thermostats location

- Enter the email and password associated to your mobile account and tap the login button.
 - If you have forgotten your password, tap the forgot password link to recover information via email.
- Type the address of where the thermostat is located to gather accurate information.





Step 4 - Connecting the App to the thermostat

- With wifi enabled on your thermostat, access your account to retrieve the six-digit code.
- Type the six-digit code displayed on your thermostat into the space provided on the mobile app.
- Tap connect to continue and operate the Daikin One+ from your mobile device.

account

Get the Daikin Smart Thermostat app from the App Store or Google Play, create an account, then link your thermostat with the code provided here.







Mobile Apps

 West Park Home \equiv downstairs Δ 0 ណ៍ X



Visit <u>Daikinone.com</u> for additional information



