



# DAIKIN ONE LITE CONNECTED THERMOSTAT

## Description

The Daikin *One* lite connected thermostat is a perfect solution for Daikin single and multi-zone products when a wall-mounted smart thermostat is needed. The *One* lite connected thermostat is compatible with most Daikin single and multi-zone systems<sup>+</sup> and can be linked via Wi-Fi to the Daikin *One* home app for control.

## Standard Features

- Compact, non-intrusive design suitable for most interior environments
- Multifunction push buttons labeled for mode, fan, set-point up, set-point down
- Wi-Fi-enabled connected thermostat that works with Daikin *One* home app (iOS and Android)
- Voice control by Amazon Alexa and Google Assistant
- Programmable schedule
- Built-in temperature and humidity sensors
- Indoor unit Control: Mode (Auto/Heat/Cool/Emergency Heat), Setpoint (Dual/Single), Fan Speed, Louver, Fan On/Auto (with minimum run time)
- LED Mode indicator for heating and cooling
- Dehumidification function (setup with Daikin *One* home app)
- Error and maintenance notifications
- Control and comfort functions: Away mode and geo-fencing
- Over-the-air software update capable (requires Wi-Fi connection)
- Compatible with Daikin *One* cloud services
- Setup is possible within the Daikin *One* cloud services app, via the commissioning tool. Setup using buttons is possible, but not recommended.

## Technical Specifications

- Backlit, 3.5 inch MVA TFT LCD display
- Bi-directional communications protocol for controlling HVAC system
- Multi-language support: English, Spanish, French (Daikin *One* home app only)
- 1 Auxiliary Heat output (dry contact), configurable as a primary or secondary heat source.
- Includes Translation adaptor for S21 systems. (Note this control is not for use with P1P2 systems).
- FCC Certified/UL Listed
- An optional trim plate (PSPAC-WPM-L) is available.

## Product Dimensions

- 3.3"W x 3.3"H x 1.04"D

## Product Number

- DTST-LTE-LA-A



### EQUIPMENT COMPATIBILITY<sup>†</sup>

The Daikin *One* lite connected thermostat is compatible with single-zone and multi-zone indoor unit models: FTK\*, FTXB\*, FTX\*, FTXM, FTXR, FTXS, FVXS, CTXS\*, CDXS (discontinued), FDXS (discontinued).

\*Not compatible with FTK\_AXVJU, FTX\_AXVJU, FTKB\_AXVJU, FTXB\_AXVJU, and CTX\_AXVJU

The following indoor units do not have the S21 connection and require an additional interface adaptor that must be ordered separately to provide the S21 connection for the Daikin *One* lite connected thermostat communication:

INDOOR UNIT MODELS	REQUIRED INTERFACE ADAPTOR
FTX09NMVJU(A), FTX12NMVJU(A), FTX09WMVJU9, FTX12WMVJU9	KRP067A41E
FTX15NMVJU(A), FTX15WMVJU9	KRP980B2E

**NOTE:** The Daikin *One* lite connected thermostat is compatible only with S21 systems. An additional, future model is planned for compatibility with P1P2, SkyAir and VRV systems.



\* Complete warranty details available from your local dealer/contractor or at [www.daikincomfort.com](http://www.daikincomfort.com). To receive the 12-Year<sup>1</sup> Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. The duration of warranty coverages in Texas differs in some cases.

<sup>1</sup> 12-Year Limited Warranty is available for owner-occupied residences only.

For multi-family and/or commercial applications, the warranty period is 5-years.

