



DAIKIN ONE TOUCH SMART THERMOSTAT

Description

The Daikin *ONE* touch smart thermostat is the newest addition to the Daikin *ONE* ecosystem line of products, joining the Daikin *ONE+* smart thermostat as a control solution for Daikin's communicating unitary equipment, including Daikin *FIT*.

Standard Features

- Simple, elegant industrial design
- Capacitive touchscreen user interface
- Wi-Fi-enabled smart thermostat with iOS and Android app control
- Voice control by Amazon Alexa and Google Assistant
- Control and comfort functions: Away mode, geo-fencing
- Outdoor environment monitoring: outdoor temperature, outdoor humidity, and weather forecast when connected to Wi-Fi
- Compatible with Daikin *ONE* home air monitor for IAQ visualization
- Error and service notifications
- Multi-language support: English, Spanish, French
- Programmable 4-event schedule with adjustable hold function
- Compatible with *SkyportCare* and *SkyportHome* app
- Open API compatible for home control systems such as Control4 and Crestron
- Compliant to California Title 24 (OCST listed), FCC Certified, and UL Listed

Technical Specifications


- Capacitive touch screen
- Backlit, 3.5 inch MVA TFT LCD display
- Bi-directional communications protocol for controlling HVAC system
- Bubble level (to aid installation)
- 640 × 480 pixels × 24 bit RGB (full color screen)
- Wi-Fi
- Operation Temperature: 32°F to 120°F

Product Dimensions

- Length: 3.4 inches
- Height: 4.74 inches
- Depth: 0.86 inches
- Weight: 6.5 ounces

Product Number

- DTST-TOU-A



R-32 Unitary Split Systems	Type	Compatible Family (Models starting with)
	Outdoor Unit	DC_VS, DC7TC, DH_VS, DH_TC
	Air Handling Unit	D_VE, A_VE
	Coil	CAPE, CHPE
	Modular Blower	MBVK
	Gas Furnace	DR_MC, DR_SC, DD_SC, DD_MC, DR_TC, DD_TC

Indoor Air Quality	Daikin <i>ONE</i> Home Air Monitor (Only compatible with ducted units)
--------------------	---

Ductless Mini & Multi-Split Systems	Type	Compatible Family (Models starting with)
	R-32 12RC Indoor Units	CMXV
	R-410A S21 Indoor Units ¹	CDXS, CTXS ² , FDXS, FTK ³ , FTXB ² , FTXF ² , FTXG ² , FTX09_12N ² , FTX15_18_24N ³ , FTXR, FTXS, FVXS ³
	R-410A P1/P2 Indoor Units ¹	CDMQ, FDMQ, FFQ,

¹ Must purchase and install communication adaptor DAPT-ONE-VMS

² Must purchase S21 adaptor KRP067A41E

³ Must purchase S21 adaptor KRP980B2E

⁴ The Sarara drying function of the *QUATERNITY* units is not supported with Daikin *ONE* touch smart thermostat, but the dehumidification function of the Daikin *ONE* touch can be used with the *QUATERNITY* indoor units

SkyAir and VRV Systems ⁴	Type	Compatible Family (Models starting with)
	R-410A VRV Indoor Units	FXAQ, FXDQ, FXFQ, FXLQ, FXMQ, FXNQ, FXSQ, FXZQ
	R-410A SkyAir Indoor Units	FAQ, FBQ, FCQ, FHQ, FTQ

⁴ Must purchase and install communication adaptor DAPT-ONE-VMS

ACCESSORIES

Flush Mount Kit (DKIT-FLSH-ONE)

J-box Adaptor Plate Kit (DKIT-CONV-ONE)



* Complete warranty available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California, Florida, or Québec. The duration of warranty coverages in Texas and Florida differs in some cases. Other limitations and exclusions apply, refer to complete warranty details for full list of limitations and exclusions.

¹ 12-Year Limited Warranty is available for owner-occupied residences only.

For multi-family and/or commercial applications, the warranty period is 5-years.

Google, Google Assistant, and all related logos are trademarks of Google, or its affiliates. Amazon, Alexa, and all related logos are trademarks of Amazon.com, Inc. or its affiliates.