



Submittal Data Sheet

0.75-Ton Flood Standing

FXLQ09MVJU9

FEATURES

- One of our slimmest indoor units (less than 8") fits any interior design
- Wide air discharge outlet distributes a comfortable airflow throughout the entire space
- Silent stream fan technology keeps sound pressure levels low
- Ideal for installation beneath a window
- Unit requires minimal installation space
- Standard Limited Warranty: 10-year warranty on compressor and all parts



VRV





Submittal Data Sheet

0.75-Ton Flood Standing

FXLQ09MVJU9

PERFORMANCE

| | | | |
|----------------------------------|----------------|-------------------------------|---|
| Indoor Unit Model No. | FXLQ09MVJU9 | Indoor Unit Name: | 0.75-Ton Flood Standing |
| Type: | Floor Standing | Rated Cooling Conditions: | Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75 |
| Rated Cooling Capacity (Btu/hr): | 9,500 | Rated Heating Conditions: | Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43 |
| Sensible Capacity (Btu/hr): | 7,100 | Rated Piping Length(ft): | |
| Cooling Input Power (kW): | 0.050 | Rated Height Separation (ft): | |
| Rated Heating Capacity (Btu/hr): | 10,500 | | |
| Heating Input Power (kW): | 0.05 | | |

INDOOR UNIT DETAILS

| | | | |
|--|-------------------------|--------------------------------|---------|
| Power Supply (V/Hz/Ph): | 208-230 / 60 / 1 | Airflow Rate (H/L) (CFM): | 245/210 |
| Power Supply Connections: | L1, L2, Ground | Moisture Removal (Gal/hr): | |
| Min. Circuit Amps MCA (A): | 0.3 | Gas Pipe Connection (inch): | 1/2 |
| Max Overcurrent Protection (MOP) (A): | 15 | Liquid Pipe Connection (inch): | 1/4 |
| Dimensions (HxWxD) (in): | 23-5/8 x 39-3/8 x 8-3/4 | Condensate Connection (inch): | 25/32 |
| Net Weight (lb): | 58 | Sound Pressure (H/L) (dBA): | 35/32 |
| Ext. Static Pressure (Rated/Max) (inWg): | / | Sound Power Level (dBA): | |

Submittal Data Sheet

0.75-Ton Flood Standing

FXLQ09MVJU9

DIMENSIONAL DRAWING

(Unit : in.(mm))

