



VRV COMMERCIAL PRODUCTS

CATALOG



Table of Contents

Overview

- Why choose Daikin?
- What is Daikin VRV?
- Why choose Daikin VRV?
- Which VRV System Offers the Best Solution?
- Setting the Standards
- Daikin VRV**
 - Setting the Standards, Again
 - What does a VRV installation mean to you?
 - Vertical Market Applications

Product Portfolio

- Outdoor Units
- Indoor Units
- Accessories and Controls

Indoor units

- Indoor Units Overview

Indoor Units (R-410A)

- FXMQ_TBVJU - HSP DC Concealed Ducted Unit
- FXSQ_TBVJU - MSP Concealed Ducted Unit
- FXDQ_MVJU - LSP Slim Concealed Ducted Unit
- FXTQ_TAVJUA(D) Multi-Position Air Handling Unit
- FXMO_MVJU - HSP High Capacity Concealed Ducted Unit
- FXNQ_MVJU9 - Concealed Floor-Standing Unit
- FXFQ_AAVJU - Round Flow Sensing Cassette
- FXUQ_PAVJU - 4-Way Ceiling-Suspended Cassette
- FXZQ_TBVJU - VISTA 2x2 Cassette
- FXEQ_PVJU - Ceiling-Mounted Cassette
- FXHQ_MVJU - Ceiling-Suspended Unit
- FXAQ_PVJU - Wall-Mounted Unit
- FXLQ_MVJU9 - Floor-Standing Unit

Indoor Units (R-32)

- FXFA_AAVJU - Round Flow Sensing Cassette
- FXMA_AAVJU - HSP DC Concealed Ducted Unit
- FXSA_AAJU - MSP Concealed Ducted Unit
- FXTA_AAJU - Multi-Position Air Handling Unit
- DZK Zoning Kit for VRV Indoor Units

Outdoor units

- VRV EMERION - Air-Cooled Heat Recovery
- VRV EMERION - Air-Cooled Heat Pump
- VRV IV X - Air-Cooled Heat Recovery
- High-Efficiency All-Electric Heat Pump Hot and Chilled Water Solutions
- VRV IV X, VRV EMERION Indoor Units 80-97% AFUE
- Gas Furnace and VRV IV X, VRV A-Coil CXTQ_TASBLU
- Daikin VRV AURORA Heat Recovery
- Daikin VRV AURORA Heat Pump
- VRV T-Series Water-Cooled Systems
- VRV S-Series Heat Pump
- Installation Space -
- VRV EMERION, VRV IV X, VRV IV & VRV AURORA, VRV T-Series Water-Cooled, & VRV IV-S
- Piping Length -
- VRV EMERION, VRV IV X, VRV IV & VRV AURORA, VRV T-Series Water-Cooled, & VRV IV-S Piping Length

4	VRV Accessories	128
5	Branch Selector Boxes	128
6	REFNET Pipe Joints	132
7	Hail Guard Kit	133
8	AHU (Air Handling Unit) Integration Kit	134
10	Control Box EKE_CBAV3-US	136
12	Ventilation	139
12	FXMQ_MFVJU - 100% Outside Air Processing Unit	142
24	VAM-GVJU - Energy Recovery Ventilator	144
26	Daikin Mega-Q Hot Water Solutions	147
29	All-Electric Hot Water Generation Systems	148
30	Efficiency and Flexibility	149
34	How it Works	150
36		
45	Controls	153
45	VRV Controls Solution	154
48	VRV Controls Systems Overview	156
	Individual Controllers	158
50	BRC1E73 (R-410A), BRC1NRV71 (R-32)	
52	Navigation Remote Controller	158
54	BRC1H71W - Madoka Remote Controller	160
56	DTST-ONE-ADA-A - Daikin One+ Smart Thermostat	162
58	DTST-TOU-A One Touch Controller	162
60	AZAI6WSCDKA - DKN Cloud Wi-Fi Adaptor	162
62	BRC4C82/BRC7E818/BRC7E83/BRC7E830 - Wireless Remote Controller	163
66	Advanced Multi-Zone Controllers – HERO Pro Edge – Central Controller	
68	DGE601A71 - Daikin HERO Pro Edge	164
70	Advanced Multi-Zone Controllers	
72	DCM601B71 - intelligent Touch Manager (iT™)	170
74	External Equipment Control	171
76	DCM009A51 - iT™ BACnet™ Client Option	171
78	Interface Solutions	172
82	AZAI6WSPDKC - DKN Plus Interface	174
84	DCM014A51 - iT™ BACnet™ Server Gateway Option	176
86	DCM007A51 - Web IF (HTTP) Software Option	176
88	DMS502B71 - Interface for use BACnet™	176
91	DMS504C71 - Interface for LonWorks®	176
92	DTA116A51 - DIII-Net/Modbus® Adaptor	176
96	DTA118A72 - DIII-Net/BACnet™ MS/TP Communication Adaptor	176
100	HERO Cloud Service and HERO Simple Edge	177
104	HERO Cloud Service and HERO Pro Edge	179
106	HERO Cloud Services	181
108	Controls Product List	184
112	Support and Tools	187
112	Support and tools overview	189
116	Selection software	190
122	Energy screening and simulation tools	190
	Design and verification	191
124	Online and tablet reference material	191
	Smartphone and mobile reference	192
126	After sales and service	193




A history of industry-leading product innovation

Becoming a global leader in any industry takes more than just time. For over 95 years Daikin has shown that it takes industry-leading product innovation and a commitment to excellence in order to climb to the top. This commitment led Daikin to develop the first Variable Refrigerant Volume (VRV) system in 1982 and to become a pioneer with our Variable Refrigerant Volume systems.


Daikin's 3 core technologies

Daikin is an industry-leading HVAC technology company. We develop state-of-the-art technology that provides indoor comfort solutions for our customers. We do this by focusing on 3 core technologies. Our refrigerant control technology provides an efficient and effective way to transport heat. Daikin inverter technology allows us to maximize energy efficiency and heat pump technology provides an effective method for moving refrigerant.



The total solution

Daikin's products and controls are designed to provide a flexible, scalable, total indoor comfort solution. We are committed to supporting our customers at every phase of the project to ensure that the highest quality and most cost effective solution is the one that is provided. From project conception throughout the life of an HVAC system, Daikin provides world class products and support. A single source and total solution for your HVAC requirements.



What is Daikin VRV?

One flexible package

Daikin VRV is a modular, commercially applied air-conditioning and heating system that distributes refrigerant from the outdoor unit to multiple indoor units, providing efficiency, comfortable individual user control and reliability in one flexible package.

Daikin VRV systems provide advanced solutions for almost any large residential to commercial application. Available in air-cooled or water-cooled solutions and heat recovery or heat pump systems, VRV provides advanced heating and cooling options with individual zone control for both open plan and tightly grouped applications.

VRV is built upon 5 basic "Building Blocks" — Outdoor Unit, Indoor Unit, Piping, Controls, and Ventilation — providing the attributes of a central chilled water system but with the simplicity of a split system. This makes it very

flexible and ideal for energy-efficient and comfortable cooling and heating of many types of buildings such as banks, health care, skilled care, libraries, storage facilities, conference centers, etc.



Applications

- » Multi-family residences
- » Retail
- » Hotels
- » Office buildings
- » Schools, etc.



Inventor and leader in VRV systems since 1982

Unique products that make the difference

» In efficiency

- Variable Refrigerant Temperature (VRT) technology leading to excellent energy efficiency
- Indoor units with advanced sensing technology and optional self-cleaning air filter panel

» In comfort

- Variable Refrigerant Temperature technology preventing cold droughts
- 16 different indoor unit types and 91 models
- Low sound indoor and outdoor units

» In aesthetics

- Stylish cassettes integrated in the ceiling
- Ceiling suspended cassettes
- Elegant wall mounted units

» In installation

- Self-addressing control system after installation
- VRV Configurator for simplified and time saving commissioning
- Flexible connection possibilities for indoor and outdoor units
- Service Window allows for easy commissioning and troubleshooting

» In control

- *intelligent Touch Manager (iTManager)*— a mini-BMS/Centralized Controller that integrates all units in a cost-efficient system
- Easy integrating with third party BMS
- Dedicated control solutions for applications such as offices, shops, hotels, schools, etc.

» In system design

- User friendly sizing and selection software
- CAD drawings and Revit* families
- Comprehensive engineering manuals

» In after market support

- Nationwide field support organization
- 50+ product training facilities in North America
- Dedicated tech support team

» In reliability

- Refrigerant-cooled electronics in outdoor unit
- Extensive testing before new units leave the factory
- Spare parts available in the US
- ISO 9001 compliant manufacturing
- One of the best warranties** in the industry

* Visit bim.daikincity.com for Revit families

** Complete warranty details available from your local Daikin manufacturer's representative or distributor or online at www.daikincomfort.com.



Which VRV System Offers the Best Solution?

Air-cooled or water-cooled?

Air-cooled

- » Fast and easy to install — no need for additional components
- » Low maintenance costs
- » Can be installed both outdoors and indoors
- » Up to 40 tons capacity for one system


Components:




Outdoor unit



Indoor unit




Refrigerant piping




Water-cooled

- » Suitable for multi-story and large buildings because of the almost unlimited possibilities of water piping
- » Not affected by outdoor temperature/climate conditions
- » Reduce CO₂ emissions thanks to the possibility of geothermal energy as a renewable energy source

Components:



Condensing unit



Indoor unit



Refrigerant piping




(Geothermal) water loop




Heat Recovery or Heat Pump?

VRV Heat Recovery



- » Simultaneous heating AND cooling from one system
- » Efficient heating by transferring heat rejected by cooling zones to those requiring heating.
- » Maximum individual comfort in all areas



Components:



Outdoor unit

Indoor unit


3-pipe refrigerant piping

Single and multi Branch Selector boxes: allows the individual switching of indoor units between heating and cooling

VRV Heat Pump

- » For either heating OR cooling operation from one system


Components:



Outdoor unit

Indoor unit

2-pipe refrigerant piping



Setting the Standards

Over 40 years of VRV history

Daikin invented the first VRV system in 1982 and has continued to set standards in the industry and heighten market expectations. Many of the current market expectations are:

- » Energy efficient inverter compressor
- » Modular system concept
- » Heat recovery function
- » Allow long piping lengths
- » Heating operation down to -13°F ambient air temperature as standard
- » Continuous heat during defrost
- » Auto charge at start up



VRV was invented in 1982 as a result of the oil crisis around the world in the 70's. Energy efficiency laws were passed by the Japanese government. The Japanese government and Daikin worked closely together — they looked at a chiller system; pumps, and air handlers as well and how the pump circulates water and how it uses a lot of power. So, they came up with a concept to use refrigerant instead of water to circulate as a heat transfer medium. The first VRV heat recovery system was launched in 1991 implementing the landmark concept of a heat pump chiller that circulates refrigerant instead of water.


Our quality control is based on the idea that the added value we give to products is quality, and that this quality is what customers are buying. And each Daikin employee constantly puts quality ahead of everything else.





Optimized life cycle cost

The features of a Daikin VRV system, energy efficient and easy to design, install, and maintain, means that it is designed to reduce the total life cycle cost.



Optimized for the North American market needs

Engineered to be simple, sustainable and connected, VRV EMERION delivers an un-matched, all-electric heat recovery solution for new and existing commercial applications that are unique to the needs of North America HVAC Market. In addition, a long list of new and enhanced features and benefits make the new VRV EMERION system an ideal choice to address a wide range of commercial applications for owners, architects, engineers, and contractors.

VRV EMERION Heat Pump & Heat Recovery - Single and Dual modules

VRV EMERION Heat Pump & Heat Recovery	CAPACITY - TONS (SINGLE MODULE)							
	6	8	10	12	14	16	18	20
CAPACITY - TONS (DUAL MODULE)								
	22	24	26	28	30	40		

Daikin VRV sets the standard with the latest technology and time saving commissioning & servicing

Adapting VRV to North American market needs

Dual Fuel with Gas Furnace Connectivity

Expanding VRV into applications that were limited to gas-based heating, VRV EMERION and VRV IV X are a 3-phase dual-fuel VRF system that integrates with communicating gas furnaces.

VRV EMERION and VRV IV X offer outstanding design flexibility when connected to Daikin communicating 80%, 96%, and 97% AFUE gas furnaces and CXTQ coils. VRV EMERION and VRV IV X enable the use of VRV technology to provide utility cost based heating solutions. With the flexibility to switch between electric heat pump heating and gas heating, operational costs can be optimized to building owner's choice for a heating source.


- » Space-saving with ability to connect multiple gas furnaces to one outdoor unit with 14 selectable settings.
- » Customizable changeover temperatures to switch from heat pump to gas heat.
- » Ability to provide system-wide heating independent of outdoor ambient temperature.




Phased Installation

VRV EMERION and VRV IV X deliver enhanced design flexibility thanks to its ability to expand with the building's phased construction.

- » Expand the system from a single to a dual module or from dual to triple module without changes to main pipe sizes that are already installed.
- » Help reduce initial capital and design complexity compared to systems that do not offer phased installation.
- » Optimize piping design, branch selector boxes, and indoor units per phase of installation.
- » Synergize well with *Flex Branch Selector* box to allow additional branch selectors to be added in series without having to branch off from main refrigerant pipe



Enhance phased installation with *Flex Branch Selector Box* series connections.



Adaptive and learning VRT

The new VRV EMERION system features a newly enhanced learning VRT technology. The new learning VRT technology, in addition to helping with annual energy efficiency and maintaining comfort, provides features that enable time-based learning to adjust cooling and heating capacities to provide a stable capacity to the indoor units. The feature must be activated through field setting changes.

How is energy reduced?


A standard variable refrigerant flow system and previous Daikin VRV systems utilize a capacity based control logic where the system will adjust to meet the capacity requirements of the space. With VRT, Daikin has optimized focus not only on capacity but also on efficiency and comfort.

According to changes in the room's heat load and the ambient air temperature, the evaporating temperature (in cooling) and

condensing temperature (in heating) are automatically adjusted to minimize the difference with the condensing temperature and the evaporation temperature, respectively.

This makes the compressors work less and also enables the system to always maintain the ideal compressor speed so that the Daikin VRV system can deliver the optimum efficiency.

Refrigerant cycle during cooling



Fine control to match user preference available through mode selection

Basic mode is selected to maintain optimal comfort. VRT is selected to save energy and prevent excessive cooling.

Capacity priority

Fixed Refrigerant Temperature

BASIC MODE

Fixed T_e - Standard control

Energy saving priority

Variable Refrigerant Temperature

AUTO MODE

Floating target T_e depending on heat load

HIGH SENSIBLE MODE

Fixed target T_e

Selecting VRT enables operation to be optimised for either energy efficiency or rapid cooling.

Floating T_e

POWERFUL MODE

Reaction speed Very Fast

QUICK MODE

Reaction speed Fast

MILD MODE

Reaction speed Medium

Fixed T_e

ECO MODE

Unable to change T_e

- » Can boost capacity above 100% if needed.
- The refrigerant temperature can go lower in cooling than the set minimum.
- » Gives priority to very fast reaction speed.
- The refrigerant temperature goes down fast to keep the room setpoint stable.

- » Gives priority to fast reaction speed.
- The refrigerant temperature goes down fast to keep the room setpoint stable.

- » Gives priority to efficiency.
- The refrigerant temperature goes down gradually giving priority to the efficiency of the system instead of the reaction speed.


Continuous heating during defrost*

- » Each outdoor unit heat exchanger goes into defrost mode at different times so continuous heating is maintained — avoiding discomfort indoors.
- » Reduces cold drafts.
- » No extra energy for reheating indoors, piping & zone (compared to variable refrigerant flow systems without continuous heating during defrost).

*Refer to engineering and installation manuals for application rules.



**SINGLE MODULE (16 - 20 T)
CONTINUOUS HEATING DURING DEFROST**



**DUAL MODULE (22 - 40 T)
CONTINUOUS HEATING DURING DEFROST**

Hot Gas Defrost Technology

The Hot Gas Defrost circuit at the bottom of the heat exchanger eliminates the need for a base pan heater. This unique technology helps improve defrost, condensate disposal, and reduce ice accumulation at the bottom of the coil. This allows for reliable and efficient system operation year-round.



Inverter Board Cooled by Refrigerant Circuit.
Minimum influence on electronics from ambient temperature. Section of the coil in the unit is permanently set as condenser for cooling of the inverter board.



Extended Operation Range —


Heating operation down to -22°F*
outdoor temperature and cooling
operation down to -4°F*

Daikin VRV systems can provide heating inside the building even when the outside air temperature is as low as -22°F* as standard. This enables enhanced application flexibility and use of the system in colder regions.


*varies based on outdoor unit type

Temperature Limits

VRV Air-Cooled



VRV T-Series Water-Cooled



*Limited to 27°F (for the PC series)

Piping flexibility —


More options for installation location

Daikin VRV provides very flexible piping possibilities. These generous allowances outlined in the figure facilitate an extensive variety of system designs.

- » 100 ft. maximum vertical difference between indoor units provides greater flexibility for riser type piping layouts.
- » Allows for up to 30* floors to be served from a single VRV System
- » Ideal for mid- to high-rise chiller or WSHP replacement projects

*varies based on outdoor unit type

Refrigerant Piping Limitations



PIPING LIMITATIONS Liquid Line Max (ft)	AIR-COOLED					WATER-COOLED	
	VRV EMERION Heat Pump & Heat Recovery	VRV IV / X Heat Pump	VRV IV / X Heat Recovery	VRV AURORA Low Ambient	VRV S (2 & 3 Ton)	VRV S (4 & 5 Ton)	VRV T-Series
(A) Vertical Drop	164 (361) ¹	164 (295) ¹	164 (295) ¹	164 (295) ¹	98	98	164
(B) Between IDU	100	100	100 (49) ³	100 (49) ³	33	49	98
(C) Vertical Rise	130 (361) ¹	130 (295) ¹	130 (195) ¹	130 (295) ¹	98	98	130
(D) From 1st Joint	130 (295) ²	130 (295) ²	130 (295) ²	130 (295) ²	130	130	130 (295) ²
(E) Linear Length	540	540	540	540	164	2-4 230	5 394
Total Network	3280	3280	3280	1640	820	984	980

¹ Setting adjustment on condensing unit required.

² Application rules apply. Refer to Installation Manual for further details.

³ Possible refrigerant noise can be mitigated (via setting adjustments on ODU) when linear length exceeds 390 ft.

Improved connection ratio flexibility

To properly match outdoor units with indoor units, VRV system designers calculate the connection ratio.

If a system has more combined indoor unit capacity index than combined outdoor unit capacity index, the result is a combination ratio that is greater than 100%. If the outdoor unit combined capacity index is higher than the index for indoor units, the combination ratio is less than 100%.

Most Variable refrigerant flow system systems do not allow the combination ratio to be more than 130%. However, due to the advanced design of the Daikin VRV EMERION system, the connection ratio is in most cases allowed to be up to 200%.

This generous connection ratio range enables increased flexibility when a VRV system is designed.

Connection ratio 50%–200%*

Connection ratio =

Total capacity index
of the **indoor units**

Total capacity index
of the **outdoor units**

VRV EMERION Connection Ratio

APPLICABLE VRV INDOOR UNITS	FXDQ, FXSQ05-54T, FXMQ_T, FXAQ	   	200%	OTHER VRV/INDOOR UNIT MODELS	FXFQ07A, FXFQ09A FXSQ05T, FXZQ05T
6-14 Ton				200%	180%
16-20 Ton				180%	180%
22-40 Ton				160%	160%

* Connection ratio limitations vary based on outdoor unit and indoor unit models



Advantages of 3-pipe technology

Daikin 3 pipe technology used in heat recovery systems has dedicated refrigerant pipes for suction gas, liquid and discharge gas. The dedicated refrigerant pipes provide smooth and efficient refrigerant flow during all main modes of operation and aid with the heating performance of the system.

In a 2 pipe heat recovery system, where the gas and liquid travel as a mixture in the refrigerant pipes, the condensing temperature needs to be higher in order to separate the mixed gas and refrigerant. The higher condensing temperature that is needed means that the compressor has to work harder. In addition, the disturbed refrigerant flow in large pipes on 2 pipe system results in extra pressure drop which can negatively impact the system capacity and efficiency.

New *Flex Branch Selector* for Ultimate Flexibility

Daikin's new *Flex Branch Selector* boxes are engineered to be compact and provide flexibility in design, installation, maintenance, and service. Packed with Daikin's state of the art technology, the new *Flex Branch Selector* boxes fit in tight mechanical spaces (common in ceilings) combined with flexibility in piping configuration and movable E-box makes the new design an ideal choice for commercial buildings.

Main Features and Benefits

Flexible

- » Design flexibility with versatile piping configurations of Left or Right or Pass through layouts.
- » Engineered for tight ceiling spaces with a compact height of 9½" and 0"1 service clearance between the slab and the top of the *Flex Branch Selector* box.
- » Flexibility to expand design with up to 121 ports and 230Mbh¹ down stream capacity by connecting multiple boxes in series.
- » Ability to optimize installed system cost by reducing *REFNETs* and braze joints in pass thru configuration vs non-pass through configuration.
- » Simple electrical configurations with flexibility to re-position E-box.²
- » Ability to mix and match Daikin *Flex Branch Selector* boxes and standard branch selector box for ultimate design flexibility.



Installation Flexibility

- » Ease of maintenance with access to electronic expansion valve (EEV) heads and motor via side access panel.
- » Eliminate cross piping with refrigerant pipe identification labels.
- » Simple electrical and communication wiring with connection from the front side of E-box.²



Innovative

- » Daikin's high specification EEV enables precise refrigerant control for high comfort in user spaces and reliable system operation.
- » Hermetically sealed to prevent condensate build up within the unit, eliminating the need for a condensate drain pan and plumbing connections for a simple installation.
- » Low ambient cooling down to -4°F¹ for simple and integrated system design.

¹ Refer to engineering manuals for design rules

² Feature available for BSF4Q54TAVJU (4-port) model only


Engineered to create a truly unique experience for contractors, VRV EMERION offers a new and improved design to provide ease of service and maintenance making way for simplicity in installation.



Outdoor unit sequencing technology

Automatic sequencing operation

During start-up, Daikin VRV unit sequencing operation will be automatically enabled to ensure balanced operation of each outdoor unit to improve longevity of equipment and stable operation.



Double backup operation functions responding resiliently to various unexpected situations

Double backup operation functions

Daikin VRV system boasts double backup operation functions, which can secure the use of air conditioners in this area to the greatest extent by emergently enabling double backup operation functions even if failure occurs in a set of air conditioning equipment. In the event of a failure, emergency operation can be conveniently enabled to allow the remaining system to operate in a limited fashion.

Unit backup operation function

If malfunction occurs in an outdoor unit...

Emergency operation can be conveniently set and enabled by the remote controller for indoor unit (for systems composed of two or more outdoor units).




Compressor backup operation function*

If malfunction occurs in a compressor...

Emergency operation can be easily set and enabled by the outdoor unit.

* Only for modules with 2 compressors



With the *VRV* heat pump and heat recovery systems, the Daikin brand is one of the most extensive lines of heating and cooling systems in North America.



VRV outdoor units assembled in the U.S.A.

The VRV IV is the first variable refrigerant flow system to be Designed, engineered, and assembled in North America. With a state of the art production line, local/in house preparation, tooling, processing and construction of heat exchangers, refrigerant

cycle assemblies, sheet metal parts, electrical box, etc., we can react quickly to changes in the market-place and truly optimize the product for the North American market.

- » Extensive local inventory and short lead times.
- » Typically, 98% of replacement parts can be shipped in approximately 48 hours.



VRV system configuration and commissioning

- » The VRV configurator is an advanced software solution that allows for easy system configuration and commissioning.
- » Less time is required on the roof configuring the outdoor unit.
- » Multiple systems at different sites can be managed in exactly the same way, thus offering simplified commissioning for key accounts.
- » Initial settings on the outdoor unit can be easily retrieved.



Simplified commissioning



Retrieve initial system settings

Outstanding 10-Year Parts and Compressor Warranties*



R32

Outstanding commercial warranty* with 10-Year Replacement Compressor Warranty and 10-Year Parts Warranty as standard ensures our confidence in our new VRV IVX.

* Complete warranty details available from your local Daikin manufacturer's representative or distributor or online at www.daikincomfort.com.

Consulting engineers

Daikin's VRV technology maximizes flexibility and leads the way in customization to match individual building requirements in comfort and energy — all designed to reduce the total life cycle costs.

- » Maximum flexibility to meet customer requirements
- » Advanced software tools assist with system design

Building owners

VRV is the ultimate in customized comfort and intelligent control tailored to your individual needs and used to maximize energy efficiency.

- » Optimized life cycle cost
- » No more cold droughts with variable refrigerant temperature
- » Single point of contact for the design of your climate system
- » Integrated system, combining air conditioning, heating, ventilation, etc., enables optimized system function
- » Multiple systems can be managed in exactly the same way for key accounts
- » Dedicated after-sales service to ensure fast on-site support

See how you can profit from
Daikin's flexible and efficient
product range.




Installers

Daikin VRV sets the standard with state-of-the-art technology and time-saving commissioning and servicing.

- » Simplified and time-saving commissioning with VRV configurator
- » Unique range of single and multi Branch Selector boxes reduce installation time compared to previous generation
- » Wide range of outdoor with single module up to 20 Ton and dual module up to 40 Tons
- » One supplier equals one point of contact
- » Maximum flexibility to meet customer requirements
- » Customized training to maximize expertise
- » Service Window allows for easy commissioning and troubleshooting

Architects

- » Indoor units with a sleek and sophisticated design
- » Space efficient outdoor units
- » Low sound levels for both indoor and outdoor units
- » Wide range of indoor units to allow installation in most environments






VRV for offices and banks

Our office solution offers:

- » Increased occupant productivity with individual zone control, low sound levels & tight temperature control
- » Optimized energy efficiency
- » Simple maintenance — low operational cost
- » Modular system allowing cost effective out-of-hours operation
- » Integrated ventilation solutions allowing high indoor air quality
- » Complete Daikin Building Management System for office building management with *Intelligent Touch Manager (iTM)*
- » Remote monitoring with email alerts
- » Self-cleaning filters yielding operational and maintenance cost savings
- » Intelligent sensors on *Round Flow* cassette, suspended cassette (optional), and *VISTA 2x2* cassette (optional) maximize efficiency using innovative occupancy sensing features.



VRV for hotels

Our hotel solution offers:


- » Energy efficient systems capable of simultaneous heating and cooling.
- » Ultra-quiet guest room solutions discrete and simple to control.
- » Flexible installation options lowering installation complexity, costs and space requirements than most traditional HVAC systems
- » Inverter technology creating the perfect guest room environment by regulating temperature swings and humidity
- » Centralized control with the *iTouch Manager* improving owner / management operational capabilities
- » Seamless integration & compatibility with industry acclaimed INNCOM™ systems delivering combined benefits in guest operations and experience for both guests and management team



VRV for retail and restaurants

Our retail solutions offer:

- » Scalable project opportunities with modular design
- » Individual zone control for advanced zoning capabilities
- » Enhanced efficiency in retail chain operations and energy usage from Daikin's complete Building Management System with *Intelligent Touch Manager (iTM)*
- » Centralized building control & autonomy from VRV remote commissioning and management capability
- » 10-Years Parts and Compressor Warranty*



VRV for schools

Our school solution offers:

- » Flexible, scalable total HVAC solution for school classrooms, common areas and administrative offices
- » Over 12,000 Daikin VRV systems in schools in North America
- » Quiet operating sound levels as low as 28 dB(A)
- » Minimal occupant air temperature variations
- » Advanced zoning capabilities with user-friendly and intuitive controls
- » Modular in design accommodating unique school and classroom spaces
- » Self-cleaning filter option for *Round Flow* cassette simplifies maintenance process and increases operational efficiency
- » Combined benefits of energy and operations efficiency for both school administrators and maintenance staff
- » 10-Year Parts and Compressor Warranty*

* Complete warranty details available from your local Daikin manufacturer's representative or distributor or online at www.daikincomfort.com.



Product Portfolio



Product Portfolio

Outdoor Units



VRV EMERION

VRV EMERION Heat Pump / Heat Recovery

Simple. Sustainable. Connected.

- » Simple and Stylish design with expanded line up with single-module units from 6 – 20 T and dual-modules up to 40 T
- » High energy efficiency with IEERs up to 30.0 delivers up to 30% efficiency increase compared to previous VRV systems
- » Sealed e-box design with an ingress protection rating of IP55 provides for high dust and moisture protection
- » Simplified diagnosis with built-in data recorder which stores up to 45 minutes of operational data
- » Engineered for ease of installation and service with three-segment panel design. Design flexibility to enlarge



system from single to a dual-module without hangers to installed main pipe sizes for phased installation or tenant fit-out buildings

- » Heating down to -13°F as standard and high heating capacities at 17°F make it an ideal choice for all-electric heat pump solutions
- » Continuous heating during defrost capability with single module (16 T – 20 T) and all dual module systems. Only available on heat recovery.
- » Hot gas defrost circuit allows for installation without base pan heater.

VRV IV X

VRV IV X Heat Pump / Heat Recovery

Industry's first 3-phase variable refrigerant flow system to integrate with communicating gas furnaces



- » Equipped with Daikin's patented inverter based vapor-injection compressor to provide high heating capacities down to -13°F WB
- » Enhanced design flexibility by allowing for phased installations with predefined pipe sizes and design rules
- » New service window provides ease of access to the multi-functional display without removing the main electrical panel. The built-in multi-functional display is

utilized for commissioning and maintenance and quickly converts to digital gauges to provide refrigerant pressure and temperatures

- » Choice of gas furnace or heat pump heating for optimizing operational costs based on utility cost
- » Field performable intermittent outdoor fan operation to help minimize snow accumulation on fan blades when the system is in thermal off
- » Total comfort solution for heating, cooling, ventilation, and controls
- » Outstanding warranty* with 10-Year Compressor and Parts Limited Warranty as standard
- » Fully integrated solution with high efficiency (IEER up to 27.80 on Heat Recovery models and IEER up to 27.30 for Heat Pump)

VRV

VRV AURORA Heat Pump / Heat Recovery



- » Variable refrigerant flow system
- » Industry's first air-cooled system that delivers heating down to -22°F (-30°C) as standard
- » Hot gas base pan circuit allows installation without an additional drain pan heater
- » Designed to provide continuous heating during defrost and oil return¹
- » Engineered with Daikin vapor injection compressor for optimized part load efficiencies





AHRI CERTIFIED®
www.ahridirectory.org

VRV S SERIES

Air-Cooled

The Daikin VRV-S elevates the renowned VRV air-cooled technology with its sleek, compact design tailored for small-scale installations without compromising performance. The Daikin VRV-S comes integrated with Variable Refrigerant Temperature (VRT) technology that supports optimal comfort throughout the year while maintaining overall energy efficiency.

- » Addition of a 2-ton model for a complete 2- to 5-ton offering
- » Long pipe lengths with vertical separation up to 164 ft. and total pipe length up to 984 ft.
- » Compact, space-saving single fan chassis design across all sizes
- » Dependable operation in extreme ambient conditions of up to 122°F¹
- » Compact height of only 34-1/4" to support a range of applications
- » Efficient operation and year-round energy savings through
- » Smart Variable Refrigerant Temperature (VRT) technology improved efficiencies in heating and cooling operation compared to the previous R-410A lineup
- » Quiet operation with sound levels as low as 56 dB(A)
- » Ease of retrofit of existing R-410A installation with the ability to re-use larger diameter refrigerant pipes via field setting
- » Optional base pan heater to defrost base pan in cooler climate applications
- » Increased nominal capacity compared to previous
- » R-32 lineup up to 60,000 Btu/hr for the 5T mode



R32

VRV
T-Series Water-Cooled System

VRV T-Series Water-Cooled Condensing Unit Heat Pump / Heat Recovery

- » Flexible System design with increased diversity up to 150%[†]
- » Can be applied to both geothermal and boiler/tower applications as standard with condenser water inlet temperature as low as 14°F[†] in heating and 23°F[†] in cooling is possible
- » Triple-stack capable to deliver up to 36 tons in just under 11.5 feet ceiling height thanks to the compact design
- » Engineered with heat rejection cancellation technology[†] to eliminate mechanical room conditioning requirements
- » 2-9V variable water flow control logic[†] as standard to increase waterside system operational efficiencies
- » Drop-down switch box for easy service to key components
- » Field selectable top or front refrigerant connections for flexible and easy installation



¹ Multi module heat recovery systems only for continuous heating during defrost
[†] Conditions/rules apply. Refer to Installation and Engineering Manual for further details.

* Complete warranty details available from your local Daikin manufacturer's representative or distributor or online at www.daikincomfort.com.

** Varies based on condensing unit model selected



Product Portfolio

Outdoor Units (cont.)



TYPE	MODEL	FEATURES	PRODUCT NAME	CAPACITY (TONS)																			
				3	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38
Air-Cooled	VRV EMER/ON Heat Pump & Heat Recovery	<ul style="list-style-type: none"> » New Simple and Stylish design with expanded line up with single-module units from 6 – 20 T and dual-modules up to 40 T. » High energy efficiency with IEERs up to 30.0 delivers up to 30% efficiency increase compared to previous VRV systems » Sealed e-box design with an ingress protection rating of IP55 provides for high dust and moisture protection. » Simplified diagnosis with built-in data recorder which stores up to 45 minutes of operational data. » Engineered for ease of installation and service with three-segment panel design. » Heating down to -13°F as standard and high heating capacities at 17°F make it an ideal choice for all-electric heat pump solutions » Continuous heating during defrost capability with single module (16 T – 20 T) and all dual module systems. Only available on Heat Recovery » Hot gas defrost circuit allows for installation without base pan heater. 	     	3				■															
								■	■	■	■	■											
													■	■	■	■							
														■	■	■	■	■					
																■	■	■	■				
																			■				
																				■	■	■	■
VRV/IVX	VRV/IVX Heat Pump & Heat Recovery	<ul style="list-style-type: none"> » Industry's first 3-phase variable refrigerant flow system to integrate with communicating gas furnaces » Enhanced design flexibility by allowing for phased installations with predefined pipe sizes and design rules » VRV/IVX service window provides ease of access to the multi-functional display without removing the main electrical panel. The built-in multi-functional display is utilized for commissioning and maintenance and quickly converts to digital gauges to provide refrigerant pressure and temperatures. 	  	3	■	■	■	■	■	■	■												
								■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
																				■	■	■	■

** 6-ton model is a PC-Series model. Some features may not be available for this model. *** Conditions/rules apply. Refer to Installation and Engineering Manual for further details.



** 6-ton model is a PC-Series model. Some features may not be available for this model. *** Conditions/rules apply. Refer to Installation and Engineering Manual for further details.

Product Portfolio

Indoor Units



Type	Model	Features	Product Name	
Ducted	HSP DC Concealed Ducted Unit	<ul style="list-style-type: none"> » Energy efficient due to the DC fan motor » Ideal to use together with the optional Daikin Zoning Kit, DZK » Enhanced indoor air quality and LEED® ready with MERV 13 filter options » Flexible ductwork design with ESP capabilities up to 0.8" In. Wg » Low profile height of only 9-11/16" 	<p>(R-32)</p> <ul style="list-style-type: none"> » Factory-installed integrated refrigerant leak sensor » Dispersion Mode: Higher airflow rate for leak mitigation through circulation » On-board terminal for connection to external alarms and monitoring systems 	FXMO_TBVJU (R-410A) FXMA_AAVJU (R-32)
	MSP Concealed Ducted Unit	<ul style="list-style-type: none"> » Powerful static pressure up to 0.6" In. Wg » Low profile height of only 9-11/16" » Auto fan speed control optimizes energy use, occupant comfort, and sound levels » Factory shipped for rear air inlet – field convertible to bottom air inlet » Integral condensate pump with more than 25" of lift 	<p>(R-32)</p> <ul style="list-style-type: none"> » Factory-installed integrated refrigerant leak sensor » Dispersion Mode: Higher airflow rate for leak mitigation through circulation » On-board terminal for connection to external alarms and monitoring systems 	FXSO_TBVJU (R-410A) FXSA_AAVJU (R-32)
	LSP Slim Concealed Ducted Unit	<ul style="list-style-type: none"> » Slim height, at only 7- 7/8" » Washable filter included » Low sound level » Factory shipped for rear air inlet —field convertible to bottom air inlet » Condensate pump with vertical lift of up to 21-1/8" included as standard 		FXDQ_MVJU
	Multi-Position Air Handling Unit	<ul style="list-style-type: none"> » Ideal replacement for fan coils, geothermal heat pumps or traditional splits systems » Upflow and horizontal right installation is permitted » ECM fan motor provides energy efficiency » Wide line up of electric heat (field installed) options from 3kW to 20kW 	<p>(R-32)</p> <ul style="list-style-type: none"> » Factory-installed integrated refrigerant leak sensor » Dispersion Mode: Higher airflow rate for leak mitigation through circulation » On-board terminal for connection to external alarms and monitoring systems 	FXTQ_TAVJU (R-410A) FXTA_AAVJU (R-32)
	HSP High Capacity Concealed Ducted Unit	<ul style="list-style-type: none"> » Powerful static pressure capability, with up to 1.0 in.w.g. (249Pa) external static pressure. » Ease of installation with remotely adjustable external static pressure using a <i>Navigation</i> Remote Controller (BRC1E73). » Designed for easier servicing and maintenance (compared to previous model) with 2 removable service panels for inspection of the interior or drain pan. » Sound levels as low as 28 dB(A) for quiet operation. » Includes a standard 1" filter rack for faster installation in the field, filter to be field provided 		FXMO_MVJU
Duct-Free	Low Temperature (LT) Hydrobox	<ul style="list-style-type: none"> » High-efficiency all-electric heat pump hot and chilled water solution for VRV » Direct control over the leaving water temperature for a wide leaving water temperature range down to 50°F in cooling and up to 113°F in heating » Ships with factory-installed hydronic accessories 		HXY48TAVJU
	Round Flow Sensing Cassette 	<ul style="list-style-type: none"> » True 360° Airflow and three room sensors enables optimized occupant comfort » Energy efficient with DC fan motor and auto-logic that adjusts fan speed » Optional self-cleaning filter panel to further increase efficiency and reduce maintenance » Increased indoor air quality with high efficiency filter options and ventilation connection kit » Very flexible with 18 different possible airflow patterns 	<p>(R-32)</p> <ul style="list-style-type: none"> » Factory-installed integrated refrigerant leak sensor » Dispersion Mode: Higher airflow rate for leak mitigation through circulation » On-board terminal for connection to external alarms and monitoring systems 	FXFQ_TVJU (R-410A) FXFA_AAVJU (R-32)
	4-Way Ceiling-Suspended Cassette	<ul style="list-style-type: none"> » Very low unit height of under 8" » Optional Sensor Kit enables input from three room sensors » Stylish unit blends easily with any interior » Individual air louver control 		FXUQ
	VISTA 2x2 Cassette for VRV Systems	<ul style="list-style-type: none"> » Fits in a standard 2' x 2' ceiling grid with no overlap of adjacent tiles » Features a low profile decoration panel design measuring only 5/16" deep » Space-saving depth of units requires only 11.75" of ceiling space » Easy-to-clean grille, washable long-life filter » Optional space and presence sensor accessory enhances energy efficiency and occupant comfort 		FXZQ_TBVJU
	Ceiling-Mounted Cassette (Single flow)	<ul style="list-style-type: none"> » Only 7- 7/8" in height and a width of 18-1/2" making it possible to use this style of indoor unit in the tightest of spaces » The unit is equipped with both horizontal and vertical louvers to optimize the airflow and throw to suite your room design » The indoor unit can be set to 5 predetermined fan speeds which allows for optimum and comfortable airflow » Factory installed condensate pump with a lift capacity of up to 33- 1/8" (measured from the bottom of the unit) 		FXEQ_PVJU
	Ceiling-Suspended Unit	<ul style="list-style-type: none"> » One of our slimmest indoor units, less than 8" » Wide air discharge outlet distributes a comfortable airflow throughout the entire space » Innovative stream fan technology keeps sound pressure levels low » Smooth flat louver design makes cleaning simple » Long-life filter is standard 		FXHQ_MVJU
	Wall-Mounted Unit	<ul style="list-style-type: none"> » Auto-swing mechanism ensures efficient air distribution via louvers » Wide air discharge outlet distributes a comfortable airflow throughout the entire space » Horizontal louvers and front panel can be easily removed for cleaning » Drain pipe can be easily hidden from sight » Compact and stylish design 		FXAQ_PVJU
	Floor-Standing Unit	<ul style="list-style-type: none"> » Ideal for installation beneath a window » Unit requires minimal installation space » Fitted with a washable long-life filter » Remote-control options available » Space-saving unit can be freestanding or wall-mounted 		FXLQ_MVJU9, FXNO_MVJU9



Product Portfolio

Accessories



Branch Selector Boxes

Providing flexibility and minimizing mechanical and electrical installation costs, Daikin's branch selector boxes that are used in Heat Recovery systems, are ideal for spaces that require individual heating and cooling control.

SINGLE-PORT BRANCH SELECTOR			MULTI-PORT BRANCH SELECTOR				
MODELS	BSQ36TVJ	BSQ60TVJ	BSQ96TVJ	BS4Q54TVJ	BSF4Q54TVJ	BSF6Q54TVJ	BSF8Q54TVJ
PORTS	1			4		6	
						8	
						10	
							12

REFNET

REFNET joints distribute correct flow of refrigerant in every branch of the piping network. Sourced locally and complies to ASTM E-84 Class A low flame and smoke spread index requirements.

VRV IV X, VRV IV / VRV AURORA Heat Pump

OPTIONAL ACCESSORIES		RXYQ72 - 96T RXYQ72 - 96X RXLQ72 - 96T	RXYQ120-168T RXYQ120-168X RXLQ120T	RXYQ192-336T RXYQ192-336X RXLQ144-240T	RXYQ360-408T RXYQ360-408X RXYQ360-480MBH
Distributed piping	REFNET Header	KHRP26M22H (max. 4 branch) KHRP26M33H (max. 8 branch)	KHRP26M22H (max. 4 branch) KHRP26M33H (max. 8 branch) KHRP26M72H (max. 8 branch)	KHRP26M22H (max. 4 branch) KHRP26M33H (max. 8 branch) KHRP26M72H (max. 8 branch)	KHRP26M22H (max. 4 branch) KHRP26M33H (max. 8 branch) KHRP26M72H (max. 8 branch) KHRP26M73HU (max. 8 branch)
	REFNET Joint	KHRP26A22T, KHRP26A33T	KHRP26A22T, KHRP26A33T, KHRP26M72TU	KHRP26A22T, KHRP26A33T, KHRP26M72TU, KHRP26M73TU	
Outdoor unit multi connection piping kit		—	—	BHFP22P100U	BHFP22P151U

VRV EMERION / VRV IV X / VRV IV / VRV AURORA Heat Recovery

OPTIONAL ACCESSORIES		RXYQ72-96A REYQ72 - 96A REYQ72 - 96X RELQ72 - 96T	RXYQ120-168A REYQ120-168A REYQ120-168X REYQ120-168T	RXYQ192-480A REYQ192-480A REYQ192-336X REYQ192-336T	REYQ360-456X REYQ360-456T
Distributed piping	REFNET header	KHRP25M33H (max. 8 branch)	KHRP25M33H (max. 8 branch) KHRP25M72H (max. 8 branch)	KHRP25M33H (max. 8 branch) KHRP25M72H (max. 8 branch)	KHRP25M33H (max. 8 branch) KHRP25M72H (max. 8 branch) KHRP25M73HU (max. 8 branch)
	REFNET joint	KHRP25A22T KHRP25A33T	KHRP25A22T KHRP25A33T KHRP25M72TU	KHRP25A22T KHRP25A33T KHRP25M72TU KHRP25M73TU	
Outdoor unit multi connection piping kit		—	—	BHFP26P100U	BHFP26P151U

¹Reducer pipe kit KHP26P100U is required for REYQ264-480A models

VRV T-Series Water-Cooled Heat Pump / Heat Recovery and VRV IV-S

UNIT MODEL NUMBER		VRV T-SERIES WATER-COOLED					VRV IV-S
		RWEQ96T	RWEQ120T	RWEQ144T	RWEQ192 - 288T	RWEQ312 - 432T	RXTQ36TBVJUA RXTQ48TBVJUA RXTQ60TBVJUA
REFNET Header	Heat Pump	KHRP26M22H (Max 4 branch) KHRP26M33H (Max 8 branch)	KHRP26M22H (Max 4 branch), KHRP26M33H (Max 8 branch) KHRP26M72H (Max 8 branch)	KHRP26M22H (Max 4 branch), KHRP26M33H (Max 8 branch) KHRP26M72H (Max 8 branch)	KHRP26M22H (Max 4 branch), KHRP26M33H (Max 8 branch) KHRP26M72H (Max 8 branch), KHRP26M73HU (Max 8 branch)	KHRP26M22H (Max. 4 branch) KHRP26M33H (Max. 8 branch)	
	Heat Recovery	KHRP25M33H (Max 8 branch)	KHRP25M33H (Max 8 branch) KHRP25M72H (Max 8 branch)	KHRP25M33H (Max 8 branch) KHRP25M72H (Max 8 branch)	KHRP25M33H (Max 8 branch), KHRP25M72H (Max 8 branch) KHRP25M73HU (Max 8 branch)	—	
REFNET Joint	Heat Pump	KHRP26A22T, KHRP26A33T	KHRP26A22T, KHRP26A33T, KHRP26M72TU	KHRP26A22T, KHRP26A33T, KHRP26M72TU, KHRP26M73TU	KHRP26A22T, KHRP26A33T, KHRP26M72TU, KHRP26M73TU	KHRP26A22T	
	Heat Recovery	KHRP25A22T, KHRP25A33T	KHRP25A22T, KHRP25A33T, KHRP25M72TU	KHRP25A22T, KHRP25A33T, KHRP25M72TU, KHRP25M73TU	KHRP25A22T, KHRP25A33T, KHRP25M72TU, KHRP25M73TU	—	
Outdoor Unit Multi Piping Connection Kit	Heat Pump	—	—	—	BHFP22T84U	BHFP22T126U	—
	Heat Recovery	—	—	—	BHFP26T84U	BHFP26T126U	—



Hail Guard Kits, Snow/Wind Hood Kit

The optional hail guard kit for VRV 3-phase enables optimal airflow for efficient heat transfer while providing condenser coil protection from hail damage in severe climates. Each hail guard kit, that is field installed, consists of 4 panels (Right, Left, Front and Back).

Hail Guard Kit for VRV IV X, VRV IV, and VRV AURORA

QUANTITY OF KITS PER ODU MODELS					PANEL DIMENSIONS (H X W X D)				
VRV IV	R_YQ72T	R_YQ96-168T	R_YQ192T	R_YQ216-336T	R_YQ360-456T	Right Panel	Left Panel	Front Panel	Front Panel
VRV AURORA		R_LQ72-120T		R_LQ144-240T					
VRV IV X HP	RXYQ72X	RXYQ96-168X	RXYQ192X	RXYQ216-336X	RXYQ360-456X				
VRV IV X HR		REYQ72-168X		REYQ192-336X	REYQ360-408X				
VRV4HGS-K1	1		1			45 ⁷ / ₈ " x 26" x 4"		45 ⁷ / ₈ " x 13 ¹ / ₄ " x 4"	45 ⁷ / ₈ " x 32 ⁵ / ₈ " x 4"
VRV4HGL-K1		1	1	2	3			45 ⁷ / ₈ " x 24" x 4"	45 ⁷ / ₈ " x 44 ³ / ₄ " x 4"

*Refer engineering and installation manual for more detail.

Hail Guard Kit for VRV EMERION

QUANTITY OF KITS PER ODU MODELS			
VRV EMERION	RXYQ72A / REYQ72A	RXYQ96-168A / REYQ96-168A	RXYQ192-240A / REYQ192-240A-240A
VRV6HGM-K1	1		
VRV6HGL-K1		1	
VRV6HGX-L-K1			1



Snow/Wind Hood Kits

The optional Snow/Wind Hood Kits mount over the heat exchanger coil to protect from snow build-up and wind in cold climates. The Hoods install easily to condensing units using existing screw taps with no modification required. Different kits can be ordered for different job requirements.

VRV IV / X AURORA	KIT PART NUMBER	CHASSIS SIZE	KIT INCLUSION
	VRV-SHS-FR	Small Chassis	Front Hood
	VRV-SHL-FR	Large Chassis	Front Hood
	VRV-SH-RL	Both Chassis	Right Hood
	VRV-SHS-T	Small Chassis	Top Hood
	VRV-SHL-T	Large Chassis	Top Hood

VRV EMERION	KIT PART NUMBER	CHASSIS SIZE	KIT INCLUSION
	VRV6-SHM-FR	Medium Chassis	Front Hood
	VRV6-SHL-FR	Large Chassis	Front Hood
	VRV6-SHLX-FR	X-Large Chassis	Front Hood
	VRV6-SH-RL	All Chassis	Right Hood
	VRV6-SHM-T	Medium Chassis	Top Hood
	VRV6-SHL-T	Large Chassis	Top Hood
	VRV6-SHLX-T	X-Large Chassis	Top Hood

NUMBER OF KITS REQUIRED FOR EACH OUTDOOR SYSTEM			
MODEL TYPE			NUMBER OF MODULES
			VRV6-SHM-FR
VRV EMERION	208-230V / 460V	RXYQ72A, REYQ72A	Single
		RXYQ96-168A, REYQ96-168A	Single
		RXYQ196-240A, REYQ196-240A	Single
		RXYQ264-336A, REYQ264-336A	Dual
		RXYQ360A, REYQ360A	Dual
		RXYQ384-480A, REYQ384-480A	Dual
VRV AURORA	208-230V / 460V / 575V	R_LQ72-120T	Single
		R_LQ144-240T	Dual
VRV IV / Heat Recovery Heat Pump	208-230V / 460V	R_YQ72T	Single
		R_YQ96-168T	Single
		R_YQ192T	Dual
		R_YQ216-336T	Dual
		R_YQ360-456T*	Triple
VRV IV X Heat Recovery	208-230V / 460V	REYQ72-168X	Single
		REYQ192-336X	Dual
		REYQ360-456X	Triple
VRV IV X Heat Pump	208-230V / 460V	RXYQ72X	Single
		RXYQ96-168X	Single
		RXYQ192X	Dual
		RXYQ216-336X	Dual
		RXYQ360-408X	Triple

*Up to 408 on Heat Pump

Product Portfolio

Accessories (cont.)



DZK (Daikin Zoning Kit)



The optional DZK increases the flexibility of the Daikin VRV and SkyAir systems in both residential and commercial applications by adding a Zoning Box to an indoor unit fan coil, allowing several separate ducts to supply air to different individually controlled zones. The DZK BACnet™ HUB module will work with any BACnet/IP & BACnet/MSTP compatible Building Management System. The DZK BACnet Hub is now Wi-Fi capable and provides remote access via the Airzone Cloud app or device web browser. (DZK-BACnet-HUB4)

DZK Zoning Box for FXMQ and FXSQ indoor units



Daikin BACnet HUB4 Module



DZK Wired, Wireless, and Wireless Lite thermostat options



Air treatment systems

Daikin's Outside Air Processing Unit can combine fresh air treatment and air conditioning, supplied from a single system.

The compact Energy Recovery Ventilator is designed to improve indoor air quality while reducing the overall HVAC system power

consumption. This is achieved by providing fresh outside air and recovering waste heat from exhaust air leaving the conditioned space.

		OUTSIDE AIR PROCESSING UNIT, FXMQ_MVJU	ENERGY RECOVERY VENTILATOR, VAM-GVJU
VRV Refrigerant Piping		Connectable	Not connectable
VRV Control Wiring			Connectable
High Efficiency Filter (MERV 8 and MERV 13)		Option	Not available
Ventilation System		Air supply	Air supply and Air exhaust
Power Supply	V/ph/Hz		208-230/1/60
Airflow Rate	CFM	635 988 1236	305/300/170 470/470/390 600/600/500 1200/1200/930





The configurable display and operation buttons on the *Navigation* Remote Controller will provide as much or as little control as the installed VRV system requires.



Product Portfolio

Controls



Optimized for VRV technology, Daikin controls provide highly scalable solutions for all applications and budgets. VRV controls offer solutions to meet your project controls needs from individual zone control with local controllers to centrally controlling the building with Centralized Controllers and/or interfacing with Building Management Systems (BMS) for comfort control in an easily managed and operated system.

PROJECT REQUIREMENTS	DAIKIN VRV CONTROLS					
R32 IDU Compatible					■	
After Hours Override				■		
Individual zone control	■	■	■	■	■	■
Independent cool and heat set-points	■	■	■	■	■	■
Individual zone control with weekly programmable scheduling		■	■	■	■	■
Basic On/Off control for indoor units	■	■	■	■	■	■
Advanced multi-zone control of small to medium size projects						
Advanced multi-zone control of large commercial projects						
Advanced multi-zone control with scheduling logic and calendar						
Automatic cooling/heating changeover for heat pump systems	■	■	■	■	■	■
Single input batch shutdown of all connected air handlers						
Web browser control and monitoring						
E-mail notification of system alarms and equipment malfunctions						
Multiple tenant power billing for shared condenser applications						
Temperature set-point range restrictions	■		■	■	■	■
Graphical user interface with floor plan layout						
Start/stop control of ancillary building systems*						
Daikin VRV integration with BACnet based automation systems						
Daikin VRV integration with LonWorks based automation systems						
Daikin VRV integration with Modbus based automation systems		■				
Wi-Fi option remote access through smartphone app		■			■	■
View service data on a graphical view						
Trend and Plot (Current and Past Data)						
Adjust outdoor unit field settings remotely						
Multisite Monitoring					■	■
Automated Reports						

* Requires WAGO® IO module (for use with iTM and HERO Pro Edge).

■ Native application or feature for this device. ■ Dependent upon capabilities of the third party energy management system



DAIKIN VRVCONTROLS

Product Portfolio

Controls (cont.)




Network solutions


TYPE		iTM	LonWorks®	BACnet™	ModBus®	BACnet™ MSTP Adaptor	DKN Plus Interface
Screen	Layout screen	■					
	Touch screen	■					
Integration	Mini BMS for heating, air conditioning applied systems and refrigeration units (BACnet and WAGO®)	■					
	3rd party equipment integration	■					Tstat & Aux Heater
Control	Basic control functions: on/off, set point setting, air flow settings, operation mode	■	■	■	■	■	■
	Temperature limitation	■					
	Setback	■					
	Automatic changeover	■					■
	Weekly schedule and special day pattern	■					■
	Timer extension	■					
	Forced off	■	■	■			■
	Interlock	■					
Monitoring	Basic control functions: ON/OFF status, operation mode, set point temp.	■	■	■	■	■	■
	Filter status	■	■	■	■	■	■
	Malfunction code	■	■	■	■	■	■
	History (Control, malfunction, settings, status)	■					
	Data storage (indoor and outdoor unit operation data)	■					
	Visualization	■					
Options	PPD (Power Proportional Distribution)	■					
	Web access and control		Web Browser				Wi-Fi App Access
	BACnet Client	■					
	BACnet Server	■		■		■	■
	D-Net Service	■					
	Operation Data	■				■	
Other	Maximum number of indoor unit groups	8 x 64	64	4 x 64	16	32	1



Powerful Service Tool with Indoor and Outdoor Unit Operation Data Points



Optional





Indoor Units



Designed for absolute comfort and versatility, Daikin's wide selection of ducted and duct-free indoor units with a sleek and sophisticated design provides zoning flexibility and comfort control for almost any application.



As many as 64 separate indoor units can be connected to a refrigerant circuit with a single outdoor unit of up to 38 tons capacity. The Daikin VRV indoor unit range is one of the widest on the market, offering no less than 16 stylish and elegant indoor units types in 91 different models — all designed to maximize comfort, minimize operating sound and simplify installation and servicing.

Indoor unit models include *Round Flow* ceiling mounted cassette, ceiling concealed ducted, ceiling suspended, wall mounted and floor standing models.

The *Round Flow* sensing cassette now includes an optional variable refrigerant flow system industry first self-cleaning filter, which automatically cleans itself daily

(user adjustable), leading to yearly energy savings of up to 50%. Dust from the filter is collected in the unit for easy and quick removal (when indicated) with a standard vacuum cleaner.

Designed to fit rooms of any size and shape, Daikin indoor units are also user friendly, ultra reliable, easy to control and quiet in operation.



INDOOR UNIT TYPE		CAPACITY														
		MBH	5.8	0.7	09	12	15	18	24	30	36	42	48	54	60	72
TONS	0.5	0.6	0.75	1	1.25	1.5	2	2.5	3	3.5	4	4.5	5	6	8	
DUCTED	FXMQ_TBVJU (R-410A) FXMA_AAVJU (R-32) HSP DC Concealed Ducted Unit 															
	FXSQ_TBVJU (R-410A) FXSA_AAVJU (R-32) MSP Concealed Ducted Unit 															
	FXTO_TBVJUA (D) FXTA_AAVJUA (D) (R-32) Multi-Position Air Handling Unit (Upflow, Downflow, Horizontal Left and Horizontal Right) 															
	FXDO_MVJU LSP Slim Concealed Ducted Unit															
	FXMQ_MVJU HSP High Capacity Concealed Ducted Unit														 	
DUCT-FREE	FXFQ_TVJU (R-410A) FXFQ_AAVJU (R-32) Round Flow Sensing Cassette, Ceiling Mounted 															
	HYX48TAVJU Low Temperature (LT) Hydobox															
	FXUO_PAVJU 4-Way Blow Ceiling-Suspended Cassette															
	FXZQ_TBVJU VISTA 2x2 Cassette for VRV															
	FXEQ_PVJU Ceiling-Mounted Cassette (Single Flow)															
	FXHQ_MVJU Ceiling-Suspended Unit															
	FXAQ_PVJU Wall-Mounted Unit						 									
	FXNO_MVJU9 Concealed Floor-Standing Unit,						 									
	FXLO_MVJU9 Floor-Standing Unit						 									



Comfort cooling/heating



Condensate pump standard



Outside air connection possible

Indoor Units Overview

	Condensate Pump as Standard		All Aluminum Coil		Optional Auto Cleaning Filter
	Outside Air Integration Possible		Variable-Speed ECM Motor		
	All Aluminum Coil		Filter Included		

What are your choices?

FXMQ_TBVJU (R-410A) FXMA_AAVJU (R-32)
HSP DC Concealed Ducted Unit

Ceiling mounted DC-Ducted unit — ideal for small to large spaces in need of a concealed air-conditioning system.



R32

FXFQ_TVJU (R-410A) FXFQ_AAVJU (R-32)
Round Flow Sensing Cassette, Ceiling Mounted

Ideal for open plan applications such as classrooms and offices where adaptive comfort control is preferred. Provides excellent comfort level, energy efficiency, and flexibility due to advanced control functions.



R32

FXSQ_TBVJU (R-410A) FXSA_AAVJU (R-32)
MSP Concealed Ducted

Ducted unit with compact design and powerful static pressure capabilities.



R32

FXTQ_TBVJUA(D) (R410A) FXTA_AAVJUA(D)(R-32)
Multi-Position Air Handling Unit

Vertical air handling unit ideal for both residential and light commercial applications. It has upflow, downflow, horizontal left and horizontal right possibilities.



R32

FXDQ_MVJU
LSP Slim Concealed Ducted Unit

Slim duct built-in concealed unit with low profile and low sound level.



FXNQ_MVJU9
Concealed Floor-Standing Unit

Floor-standing unit that can easily be installed along a perimeter wall — or concealed

FXLO_MVJU9
Floor-Standing Unit

Great way to save space. The floor-standing units can easily be installed along a perimeter wall.



FXMQ_MVJU**HSP High Capacity Concealed Ducted**

Ideal unit for larger open space floor plans usually found in offices, retail, hotels or education facilities.

**FXUQ_PAVJU****4-Way Blow Ceiling-Suspended Cassette**

Perfect solution for rooms without a false ceiling, or minimal space above a false ceiling, where adaptive comfort control is preferred.

**FXAQ_PVJU****Wall-Mounted Unit**

Unit ideal for cooling or heating smaller zones such as stores, offices and restaurants. Compact and stylish design.

**FXZQ_TBVJU****VISTA 2x2 Cassette for VRV**

2'x2' 4-way Cassette best for open plan applications such as classrooms, offices and retail.

**FXEQ_PVJU****Ceiling-Mounted Cassette (Single Flow)**

Slim and compact design for installation flexibility. For hotel rooms, offices and residential.

**FXHQ_MVJU****Ceiling-Suspended Unit**

Ceiling-suspended with slim and elegant design solution for VRV

**HXY48TAVJU****Low Temperature Hydrobox**

High-efficiency all-electric heat pump hot and chilled water solution for VRV





Condensate Pump as Standard

Outside Air Integration Possible

Powerful, Concealed, Flexible

The ceiling mounted HSP DC concealed ducted unit is ideal for small to large spaces in need of a concealed air-conditioning system. It is extremely powerful and the compact design allows it to be completely concealed. This makes it perfect for retail, classrooms, offices, banks, restaurants, shops and hotels common areas.

Features and Benefits

- » Capacity range up to 54 MBH.
- » Energy efficient due to the DC fan motor
- » Ideal to use together with the optional Daikin Zoning Kit, DZK
- » Provides a high degree of control for auxiliary heating devices, with independently configurable on/off temperature values
- » Advanced economizer control logic
- » Enhanced indoor air quality and LEED® ready with MERV 13 filter options
- » Ease of installation with auto adjusting airflow at commissioning based on external static pressure
- » Flexible ductwork design with ESP capabilities up to 0.8" W.G.
- » Installation flexibility with a low profile, compact design at less than 12" in height
- » Easy maintenance with complete service access from below
- * Refer to installation manual for all installation clearance requirements.
- ** Auto fan speed requires the use of the BRC1E73 controller



BRC1E73 (option)



AZAI6WSCDKA (option)




BRC4C82 (option)



BRC1H71W (option)



AZAI6WSPDKC (option)



DTST-ONE-ADA-A (option)




DTST-TOU-ADA-A (option)


Auto Adjust External Static Pressure

- » After installation, it is possible that the actual duct resistance is lower than expected at the time of designing. As a consequence, the air-flow will be too high.
- » With the automatic air-flow adjustment function the unit can adapt its fan speed to a lower curve, so the air-flow decreases.
- » The air-flow will always be within 10% of the rated air-flow because of the amount of possible fan curves (more than 8 fan curves available per model).
- » Alternatively the installer can manually select a fan curve with the wired remote control.

Auto Adjust External Static Pressure



- Fan characteristic curve
- Actual duct resistance curve
- - Duct resistance curve at the time of designing
- Rated airflow
- Airflow without airflow automatic adjustment
- Actual airflow



Applications

- » Offices
- » Hotels
- » Schools
- » Retail

FXMQ-TBVJU SPECIFICATIONS		1.25 TON	1.5 TON	2.0 TON	2.5 TON	3.0 TON	4.0 TON	4.5 TON						
Model Name		FXMQ15TBVJU	FXMQ18TBVJU	FXMQ24TBVJU	FXMQ30TBVJU	FXMQ36TBVJU	FXMQ48TBVJU	FXMQ54TBVJU						
Power Supply	V/ph/Hz	Single-phase 208/230V 60Hz												
Rated Cooling Capacity	BTU/h	14,200 (4.2)	18,000 (5.3)	24,000 (7.0)	30,000 (8.8)	36,000 (10.6)	48,000 (14.1)	54,000 (16.7)						
Rated Heating Capacity	BTU/h	17,000 (5.0)	20,000 (5.9)	27,000 (7.9)	34,000 (10.0)	40,000 (11.7)	54,000 (15.8)	63,000 (18.5)						
Airflow Rate (H/M/L)	SCFM (M3/MIN)	560/447/406 (15.8/12.7/11.5)	635/565/512 (18.0/16.0/14.5)	742/635/565 (21.0/18.0/16.0)	1094/847/795 (31.0/24/22.5)	1130/953/795 (32.0/27.0/22.5)	1377/1130/918 (39.0/32.0/26.0)	1518/1235/989 (43.0/35.0/28.0)						
Height	in.	9-11/16												
Width	in.	39-3/8			55-1/8			61						
Depth	in.	31-1/2												
Condensate Pump Lift	in.	25-5/16												
Sound Level (Reference) *	Power dB(A)	65	64	67	71	72	76	80						
	Pressure dB(A)	37/34/31	36/34/32	39/35/33	43/38/36	44/40/36	48/44/39	52/47/42						
Weight	lbs (kg)	77 (35)		82 (37)	101 (46)		104 (47)	115 (52)						
Condensate Pipe Connection	in. O.D.	VP25												
Pipe Connections	Gas	in. (mm)	ø1/4 (ø6.4) (Flare)		ø3/8 (ø9.5) (Flare)									
	Liquid	in. (mm)	ø1/2 (ø12.7) (Flare)		ø5/8 (ø15.9) Flare									
Refrigerant		R-410A												
Refrigerant Control		Electronic Expansion Valve												
Maximum Overcurrent Protective Device	A	15												
Minimum Circuit Amps	A	1.8	1.9	3	3.1	3.6								
Protection Devices		Fuse and Fan Driver Overload Protector												
External Finish		Galvanized Steel Plate												
External Static Pressure (H/L)	in. W.G.	0.80/0.20					0.56/0.20							


* The sound power levels are based on ISO9614 and the sound pressure levels are based on JIS B 8616.

FXDQ_MVJU ACCESSORIES

Model Name	FXMQ15TBVJU	FXMQ18TBVJU	FXMQ24TBVJU	FXMQ30TBVJU	FXMQ36TBVJU	FXMQ48TBVJU	FXMQ54TBVJU
Navigation Remote Controller*				BRC1E73			
DKN Cloud Wi-Fi Adaptor				AZA16WSCDKA			
Madoka Remote Controller				BRC1H71W			
Button Sensor Kit				KRCSH2018-01			
Daikin One+ Smart Thermostat				DTST-ONE-ADA-A			
DKN Plus Interface				AZA16WSPDKC			
Daikin One Touch				DTST-TOU-A			
Wireless Remote Controller				BRC4C82			
Remote Sensor Kit				Kit KRCS01-6B			
Wiring Adaptor PCB (interface with aux/primary heater, humidifier, OA damper/fan)				KRP1C75			
Group Control Adaptor PCB (connects to external BMS)				KRP4A74			

* Optional face plates available to provide a more intuitive user interface and disable specific functions

FXMQ-TBVJU INSTALLATION SPACE



FXSQ_TBVJU

MSP Concealed Ducted Unit



Condensate Pump
as Standard

Outside Air
Integration Possible

Do more with less

The MSP concealed ducted unit is engineered with impressive static pressure capability in a compact, flexible chassis design to give designers a tool to approach even the most cramped air conditioning applications.

Features and Benefits

- » Powerful static pressure capability, with up to 0.6 in. Wg (150Pa) external static pressure.
- » Ease of installation with auto adjusting airflow at commissioning based on external static pressure.
- » Designed for installation flexibility, with a factory rear-return configuration and field convertible to bottom return.
- » Sound levels as low as 28 dB(A) for quiet operation.
- » Provides a high degree of control for auxiliary heating devices, with independently configurable on/off temperature values.
- » Integral condensate pump with up to 25-5/16" (643mm) of lift from the drain outlet




Flexible Installation

The FXSQ_TB can easily be converted to a bottom-return configuration to optimize the use of space above the ceiling or bulkhead space.



Applications

- » Offices
- » Hotel Rooms
- » Multi-family residences
- » Single-family residences
- » Schools




SPECIFICATIONS		0.5 TON	0.6 TON	0.75 TON	1.0 TON	1.25 TON	1.5 TON
Model Name		FXSQ05TBVJU	FXSQ07TBVJU	FXSQ09TBVJU	FXSQ12TBVJU	FXSQ15TBVJU	FXSQ18TBVJU
Capacity Index		5.8	7.5	9.5	12	15	18
Power Supply		V/ph/Hz	208/230VAC, 60Hz, 1 phase				
Nominal Cooling Capacity* ¹		Btu/h (kW)	5,800 (1.7)	7,200 (2.1)	9,500 (2.8)	12,000 (3.5)	15,000 (4.4)
Nominal Heating Capacity* ²		Btu/h (kW)	6,500 (1.9)	8,500 (2.5)	10,500 (3.1)	13,500 (4.0)	17,000 (5.0)
Fan	Type		Sirocco fan				
	Motor Output	W	78			130	230
	Air Flow Rate (H/M/L)	CFM	281 / 265 / 230		318 / 265 / 230	335 / 283 / 247	530 / 441 / 371
	Drive Type		DC Direct Drive				
	External Static Pressure (Std./Max)		0.2 / 0.6			0.4 / 0.6	
Height		in. (mm)	9-11/16				
Width		in. (mm)	21-11/16			27-9/16	39-3/8
Depth		in. (mm)	31-1/2				
Weight (net)		lb. (kg)	55 (25)			60 (27)	77 (35)
Condensate Pump Lift		in. (mm)	25-5/16 (643)				
Sound Pressure Level (H/M/L speed)		dB(A)	33 / 30 / 28		34 / 32 / 30	36 / 33 / 30	34 / 32 / 29
Pipe Connections	Liquid	in.	1/4 (Flare)				
	Gas	in.	1/2 (Flare)				
	Condensate Drain	in.	VP25				
Refrigerant Control			Electronic Expansion Valve				
Maximum Overcurrent Protection Device		A	15			1.4	1.6
Minimum Circuit Ampacity		A	0.8				

SPECIFICATIONS		2.0 TON	2.5 TON	3.0 TON	4.0 TON	4.5 TON	
Model Name		FXSQ24TBVJU	FXSQ30TBVJU	FXSQ36TBVJU	FXSQ48TBVJU	FXSQ54TBVJU	
Capacity Index		24	30	36	48	54	
Power Supply	V/ph/Hz	208/230VAC, 60Hz, 1 phase					
Nominal Cooling Capacity* ¹	Btu/h (kW)	24,000 (7.0)	30,000 (8.8)	36,000 (10.6)	48,000 (14.1)	54,000 (15.8)	
Nominal Heating Capacity* ²	Btu/h (kW)	27,000 (7.9)	34,000 (10.0)	40,000 (11.7)	54,000 (15.8)	60,000 (17.6)	
Fan	Type	Sirocco fan					
	Motor Output	W	230			300	
	Air Flow Rate (H/M/L)	CFM	742 / 618 / 512	812 / 689 / 565	1130 / 953 / 795	1307 / 1112 / 918	
	Drive Type		DC Direct Drive				
	External Static Pressure (Std./Max)		0.2 / 0.6			0.2 / 0.56	
Height	in. (mm)	9-11/16					
Width	in. (mm)	39-3/8			55-1/8	61	
Depth	in. (mm)	31-1/2					
Weight (net)	lb. (kg)	77 (35)	82 (37)	101 (46)	104 (47)	115 (52)	
Condensate Pump Lift	in. (mm)	25-5/16 (643 mm)					
Sound Pressure Level (H/M/L speed)	dB(A)	36 / 32 / 29	37.5 / 34 / 30	39 / 35 / 32	42 / 38.5 / 35	43 / 40 / 36	
Pipe Connections	Liquid	in.	3/8 (Flare)				
	Gas	in.	5/8 (Flare)				
	Condensate Drain	in.	VP25				
Refrigerant Control			Electronic Expansion Valve				
Maximum Overcurrent Protection Device		A	15			2.8	3.3
Minimum Circuit Ampacity		A	1.8				

Note: ¹ Nominal cooling capacities are based on the following conditions: 80°F DB / 67°F WB (26.7°C DB / 19.4°C WB) return air temperature; 95°F DB (35°C DB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.

² Nominal heating capacities are based on the following conditions: 70°F DB (21.1°C DB) return air temperature; 47°F DB / 43°F WB (8.3°C DB / 6.1°C WB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.

FXSQ





Condensate Pump
as StandardOutside Air
Integration PossibleFilter
Included**Concealed, Slim, Quiet, Comfortable**

The LSP slim concealed unit is available for use with the VRV systems to complement the existing concealed ceiling unit options. With its low profile and low sound level this unit can be installed into limited ceiling void, bulkhead or soffit space.

Features and Benefits

- » Slim height, at only 7 $\frac{7}{8}$ ", makes it suitable for most of the applications where attic / bulkhead space is limited
- » With a sound level down to 29 dB(A) these units are among the quietest on the market
- » Factory shipped for rear air inlet — field convertible to bottom air inlet
- » Washable filter included
- » Condensate pump with vertical lift of up to 21 $\frac{5}{8}$ " included as standard
- » Blends unobtrusively with any interior decor; only the suction and discharge grills are visible

BRC1E73
(option)AZA16WSCDKA
(option)BRC4C82
(option)BRC1H71W
(option)AZA16WSPDKC
(option)DTST-ONE-ADA-A
(option)DTST-TOU-ADA-A
(option)**Applications**

- » Hotel rooms
- » Multi-family residences
- » Single family residences
- » School dormitories



FXDQ_MVJU SPECIFICATIONS		0.6 TON	0.75 TON	1 TON	1.5 TONS	2 TONS
Model Name		FXDQ07MVJU	FXDQ09MVJU	FXDQ12MVJU	FXDQ18MVJU	FXDQ24MVJU
Power Supply	V/ph/Hz			208-230/1/60		
Rated Cooling Capacity	BTU/h	7,500	9,500	12,000	18,000	24,000
Rated Heating Capacity	BTU/h	8,500	10,500	13,500	20,000	27,000
Airflow Rate (H/L)	CFM		280/226		440/350	580/460
Weight	lbs.		51		63	71
Height	in.			7-7/8		
Width	in.		27-9/16		35-7/16	43-5/16
Depth	in.			24-7/16		
Sound Pressure (H/L)	dB(A)		33/29		35/31	36/32
Condensate Pump Lift	in.			21-5/8		
Condensate Pipe Connection	in. O.D.			1-1/32		
Pipe Connections	Gas	in.		1/2 (Flare)		5/8 (Flare)
	Liquid	in.		1/4 (Flare)		3/8 (Flare)
Refrigerant				R-410A		
Refrigerant Control				Electronic Expansion Valve		
Maximum Overcurrent Protective Device	A			15		
Minimum Circuit Amps	A		0.9		1.3	1.4
Protection Devices				Fuse and Fan Motor Thermal Protector		
External Finish				Galvanized Steel Plate		
Standard Filter Type				Removable, Washable, Mildew Proof		
External Static Pressure (H/L)	in. Wg		0.12/0.04		0.17/0.06	0.17/0.06

Nominal Conditions: **Cooling Mode**
Indoor: 80°F DB / 67°F WB
Outdoor: 95°F DB
Pipe Length: 25 ft.
Level Difference: 0 ft.

Heating Mode
Indoor: 70°F DB
Outdoor: 47°F DB / 43°F WB
Pipe Length: 25 ft.
Level Difference: 0 ft.

Note: Specifications are subject to change without notice.

FXDQ_MVJU ACCESSORIES



Model Name	FXDQ07MVJU	FXDQ09MVJU	FXDQ12MVJU	FXDQ18MVJU	FXDQ24MVJU
Navigation Remote Controller*			BRC1E73		
DKN Cloud Wi-Fi Adaptor			AZA16WSCDKA		
Madoka Remote Controller			BRC1H71W		
Button Sensor Kit			KRCSH2018-01		
Daikin One+ Smart Thermostat			DTST-ONE-ADA-A		
DKN Plus Interface			AZA16WSPDKC		
Daikin One Touch			DTST-TOU-A		
Wireless Remote Controller			BRC4C82		
Remote Sensor Kit			KRCS01-1B		
Wiring Adaptor PCB (interface with aux/primary heater, humidifier, OA damper/fan)			KRP1C75		
Group Control Adaptor PCB (connects to external BMS)			KRP4A74		
Access Panel (single door)		APFXDQ070912		APFXDQ18	APFXDQ24
Access Panel with return air filter (single door)		APRFFXDQ070912		APRFFXDQ18	APRFFXDQ24
Filter Media Replacement		APRFFXDQ070912F		APRFFXDQ18F	APRFFXDQ24F

* Optional face plates available to provide a more intuitive user interface and disable specific functions

FXDQ_MVJU INSTALLATION SPACE

Choose an installation site that ensures both optimum air distribution and sufficient clearance for maintenance.

The return air inlet can be easily changed from rear to bottom using the same chamber lid.



FXTQ_TBVJUA(D)

Multi-Position Air Handling Unit



Outside Air
Integration
Possible



All
Aluminum
Coil



Variable
Speed
ECM Motor

Outstanding flexibility and performance

The FXTQ_TAVJUA(D) air handler features full multi-position* flexibility to meet the most demanding installation conditions. A multitude of features ensure reliable, efficient performance year round.

Features and Benefits

- » Expanded capacity lineup, featuring ten models ranging from 3/4 ton to 5 tons, with a redesigned** unit frame for maximum durability.
- » Full multi-position air handler capable of upflow, downflow*, horizontal right, and horizontal left installation.
- » A high efficiency, ECM motor powers the fan to deliver nominal CFM at up to 0.9" in. Wg static. An auto fan speed setting automatically adjusts the fan speed through 5 steps based on the load in the space.
- » Wide line up of electric heat (field installed) options from 3kW to 25kW.
- » An auxiliary heat logic features a reduced heater operation deadband and the ability to run both heat pump and auxiliary heat for maximum comfort and performance in colder climates. The auxiliary heat can be interlocked with the ambient temperature sensed by the outdoor unit.
- » Designed with less than 2% air leakage when tested in accordance with ASHRAE standard 193.
- » New integrated control board reduces** the number of electrical connections required. Quick disconnect control wiring terminals simplify installation.
- » Easily integrate with third party accessories such as a humidifier or economizer with on-board contacts.



- » Up to 200% connection ratio is possible on applicable VRV IV systems.

- » Available with optional factory installed disconnect (Built to order — model FXTQ_TAVJUD.)

*Downflow requires field installed optional downflow accessory.
(Part number DFK-B/C/D)

**Compared to previous model FXTQ_P

Designed for Compact Spaces

With its compact and space saving design, the new FXTQ_TAVJUA(D) air handler units are engineered to suit most light commercial and residential applications.

- » At under 46" tall and only 17-1/2" wide up to 3 tons, the FXTQ_TAVJUA(D) can be installed in tight closet spaces.
- » Designed for zero clearance on three sides and only 24" clearance on the front for service.
- » Sound levels as low as 36 dBA to suit applications in sound sensitive environments.

Electric Heater Options

ELECTRICAL HEATER CAPACITY

Model Name	3kW	5kW	6kW	8kW	10kW	15kW	19kW	20kW	25kW
FXTQ09TBVJUA(D)	■	■							
FXTQ12TBVJUA(D)	■	■	■						
FXTQ18TBVJUA(D)	■	■	■	■	■				
FXTQ24TBVJUA(D)	■	■	■	■	■				
FXTQ30TBVJUA(D)	■	■	■	■	■				
FXTQ36TBVJUA(D)	■	■	■	■	■				
FXTQ42TBVJUA(D)		■	■	■	■	■	■	■	
FXTQ48TBVJUA(D)		■	■	■	■	■	■	■	
FXTQ54TBVJUA(D)		■	■	■	■	■	■	■	
FXTQ60TBVJUA(D)		■	■	■	■	■	■	■	



Applications

- » Multi-family
- » Single-family
- » Hotels
- » Offices

SPECIFICATIONS		0.75 TON	1 TON	1.5 TON	2 TON	2.5 TON	
Model Name		FXTQ09TBVJUA	FXTQ12TBVJUA	FXTQ18TBVJUA	FXTQ24TBVJUA	FXTQ30TBVJUA	
Model Name (With factory disconnect)		FXTQ09TBVJUD	FXTQ12TBVJUD	FXTQ18TBVJUD	FXTQ24TBVJUD	FXTQ30TBVJUD	
Power Supply		V/ph/Hz	208/230VAC, 60Hz, 1 phase				
Nominal Cooling Capacity*1		Btu/h	9,500	12,000	18,000	24,000	30,000
Nominal Heating Capacity*2		Btu/h	10,500	13,500	20,000	27,000	34,000
Fan	Type		Sirocco FC Centrifugal				
	Motor Output	HP	1/2				
	Air Flow Rate (H/M/L)	CFM	300 / 275 / 250	400 / 340 / 280	600 / 510 / 420	800 / 680 / 560	1000 / 850 / 700
	Static Pressure*3	in. Wg	0.18" / 0.9"				
	Drive Type		Variable speed ECM				
Height		in.	45				
Width		in.	17.5				
Depth		in.	21				
Weight (net) (TAVJUA/TAVJUD)		lbs.	105/108	112/115	111/118	112/115	113/116
Sound Pressure Level (H speed)		dB(A)	36				
Pipe Connections	Liquid	in.	1/4 (Braze)				
	Gas	in.	1/2 (Braze)				
	Condensate Drain	in.	3/4 (fpt)				
Refrigerant Control			Electronic Expansion Valve				
Maximum Overcurrent Protective Device		A	15				
Minimum Circuit Amps		A	4.9				

SPECIFICATIONS		3 TON	3.5 TON	4 TON	4.5 TON	5 TON				
Model Name		FXTQ36TBVJUA	FXTQ42TBVJUA	FXTQ48TBVJUA	FXTQ54TBVJUA	FXTQ60TBVJUA				
Model Name (With factory disconnect)		FXTQ36TBVJUD	FXTQ42TBVJUD	FXTQ48TBVJUD	FXTQ54TBVJUD	FXTQ60TBVJUD				
Power Supply		V/ph/Hz	208/230VAC, 60Hz, 1 phase							
Nominal Cooling Capacity*1		Btu/h	36,000	42,000	48,000	54,000	60,000			
Nominal Heating Capacity*2		Btu/h	40,000	46,000	54,000	60,000	66,000			
Fan	Type		Sirocco FC Centrifugal							
	Motor Output	HP	1/2	3/4	1.0					
	Air Flow Rate (H/M/L)	CFM	1050 / 900 / 750	1400 / 1190 / 980	1520 / 1290 / 1060	1800 / 1530 / 1260	1800 / 1530 / 120			
	Static Pressure*3	in. Wg	0.23" / 0.9"							
	Drive Type		Variable speed ECM							
Height		in.	45	53.43	58					
Width		in.	17.5	21	24.5					
Depth		in.	21							
Weight (net) (TAVJUA/TAVJUD)		lbs.	113/116	144/147	165/168					
Sound Pressure Level (H speed)		dB(A)	52	54	50					
Pipe Connections	Liquid	in.	3/8 (Braze)							
	Gas	in.	5/8 (Braze)							
	Condensate Drain	in.	3/4 (fpt)							
Refrigerant Control			Electronic Expansion Valve							
Maximum Overcurrent Protective Device		A	15							
Minimum Circuit Amps		A	4.9	6.5	8.6					

*1 Nominal cooling capacities are based on the following conditions: 80°F DB / 67°F WB (26.7°C DB / 19.4°C WB) return air temperature; 95°F DB (35°C DB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.

*2 Nominal heating capacities are based on the following conditions: 70°F DB (21.1°C DB) return air temperature; 47°F DB / 43°F WB (8.3°C DB / 6.1°C WB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.

*3 External static pressures are indicated as rated / maximum allowable range.

FXTQ_TBVJUA(D) ACCESSORIES						
Model Name	FXTQ36TBVJUA(D)	FXTQ42TBVJUA(D)	FXTQ48TBVJUA(D)	FXTQ54TBVJUA(D)	FXTQ60TBVJUA(D)	
Navigation Remote Controller*			BRC1E73			
DKN Cloud Wi-Fi Adaptor			AZAI6WSCDKA			
Madoka Remote Controller			BRC1H71W			
Button Sensor Kit			KRC5H2018-01			
Daikin One+ Smart Thermostat			DTST-ONE-ADA-A			
DKN Plus Interface			AZAI6WSPDKC			
Daikin One Touch			DTST-TOU-A			
Wireless Remote Controller			BRC4C82			
Remote Sensor Kit			KRC501-1B			
Wiring Adaptor PCB (interface with aux/primary heater, humidifier, OA damper/fan)			KRP1C75			
Group Control Adaptor PCB (connects to external BMS)			KRP4A74			

* Optional face plates available to provide a more intuitive user interface and disable specific functions


Do More with Less

Daikin's large capacity FXMQ_MVJU Concealed Ducted unit offers designers a option to provide a large impact in a small space. The large capacity FXMQ features a high efficiency DC fan motor delivering CFM up to 1.0" external static pressure. With the ability to remotely adjust the static pressure, the installation of Daikin VRV equipment is now even easier than before!



Features and Benefits

- » Powerful static pressure capability, with up to 1.0 in.w.g. (249Pa) external static pressure.
- » Ease of installation with remotely adjustable external static pressure using a Navigation Remote Controller (BRC1E73).
- » Designed for easier servicing and maintenance (compared to previous model) with 2 removable service panels for inspection of the interior or drain pan.
- » Sound levels as low as 28 dB(A) for quiet operation.
- » Includes a standard 1" filter rack for faster installation in the field, filter to be field provided
- » High levels of flexibility with 3 separate fan speeds along with a variety of fan curves.

BRC1E73
(option)AZAI6WSCDKA
(option)BRC4C82
(option)BRC1H71W
(option)AZAI6WSPDKC
(option)DTST-ONE-ADA-A
(option)DTST-TOU-ADA-A
(option)

Applications

- » Hotel/conference centers
- » Schools
- » Retail/shopping centers
- » Large open-plan offices
- » Churches




FXMQ_MVJU ACCESSORIES

Model Name	FXMQ96MVJU
Navigation Remote Controller*	BRCE73
DKN Cloud Wi-Fi Adaptor	AZAI6WSCDKA
Madoka Remote Controller	BRCH71W
Button Sensor Kit	KRCSH2018-01
Daikin One+ Smart Thermostat	DTST-ONE-ADA-A
Daikin One Touch	DTST-TOU-A
DKN Plus Interface	AZAI6WSPDKC
Adaptive Touch Controller	BACRC-T-P01/ BACRC-TH-P01/ BACRC-THO-P01/ BACRC-THOC-P01
Wireless Remote Controller	BRCC82
Remote Sensor Kit	KRCS01-1B
Wiring Adaptor PCB (interface with aux/primary heater, humidifier, OA damper/fan)	KRP1C74
Group Control Adaptor PCB (connects to external BMS)	KRP4A71
High Efficiency Filter Kit (MERV 13)	DACA-MQ96M-13-1K
High Efficiency Filter Kit (MERV 8)	DACA-MQ96M-8-1K

* Optional face plates available to provide a more intuitive user interface and disable specific functions

FXMQ_MVJU INSTALLATION SPACE



FXNQ_MVJU9

Concealed Floor-Standing Unit



Outside Air
Integration Possible

Filter
Included

Versatile, Logical, Durable, Quiet

The ideal way to save space, our floor-standing units can easily be installed along a perimeter wall — or concealed. The air distribution from these models will allow you to find the right balance for classrooms, churches, office hallways or similar spaces. The concealed floor units cover a wide range of capacities and can be built into counter in order to maintain the aesthetics of the room.

Features and Benefits

- » Ideal for installation beneath a window
- » Unit requires minimal installation space
- » Fitted with a washable long-life filter
- » Remote-control options available
- » Space-saving unit can be freestanding or wall-mounted, concealed or exposed
- » Models range from 7.5 MBH to 24 MBH



BRC1E73
(option)



AZA16WSCDKA
(option)




BRC4C82
(option)



BRC1H71W
(option)



AZA16WSPDKC
(option)



DTST-ONE-ADA-A
(option)



DTST-TOU-ADA-A
(option)

Applications

- » Multi-family residences
- » Single-family residences
- » Churches
- » Historic buildings
- » Schools
- » Offices



FXNQ_MVJU9 SPECIFICATIONS		0.6 TON	0.75 TON	1 TON	1.5 TON	2 TON
Model Name		FXNQ07MVJU9	FXNQ09MVJU9	FXNQ12MVJU9	FXNQ18MVJU9	FXNQ24MVJU9
Power Supply		V/ph/Hz		208-230/1/60		
Rated Cooling Capacity		BTU/h	7,500	9,500	12,000	18,000
Rated Heating Capacity		BTU/h	8,500	10,500	13,500	20,000
Airflow Rate (H/L)		CFM	245/210		280/210	490/380
Weight		lbs.	47		56	60
Height		in.	36-5/8		42-1/8	53-1/8
Width		in.	8-5/8		15	
Depth		in.	35/32		36/33	40/35
Sound Pressure (H/L)		dB(A)	35/32		40/35	41/36
Condensate Pipe Connection		in. O.D.	27/32		27/32	
Pipe Connections	Gas	in.	1/2		5/8	
	Liquid	in.	1/4		3/8	
Refrigerant			R-410A			
Refrigerant Control			Electronic Expansion Valve			
Maximum Overcurrent Protective Device		A	15			
Minimum Circuit Amps		A	0.3	0.5	0.6	
Protection Devices			Fuse and Fan Motor Thermal Protector			
External Finish			Galvanized Steel Plate			
Standard Filter Type			Resin Net (with Mold Resistant)			


Nominal Conditions:	Cooling Mode Indoor: 80°F DB / 67°F WB Outdoor: 95°F DB Pipe Length: 25 ft. Level Difference: 0 ft.	Heating Mode Indoor: 70°F DB Outdoor: 47°F DB / 43°F WB Pipe Length: 25 ft. Level Difference: 0 ft.	Note: Specifications are subject to change without notice.
---------------------	---	---	--

FXNQ_MVJU9 ACCESSORIES

Model Name	FXNQ07MVJU9	FXNQ09MVJU9	FXNQ12MVJU9	FXNQ18MVJU9	FXNQ24MVJU9
Navigation Remote Controller			BRC1E73		
DKN Cloud Wi-Fi Adaptor			AZAI6WSCDKA		
Madoka Remote Controller			BRC1H71W		
Button Sensor Kit			KRCSH2018-01		
Daikin One+ Smart Thermostat			DTST-ONE-ADA-A		
DKN Plus Interface			AZAI6WSPDKC		
Daikin One Touch			DTST-TOU-A		
Wireless Remote Controller			BRC4C82		
Remote Sensor Kit			KRCS01-1B		
Wiring Adaptor PCB (interface with aux/primary heater, humidifier, OA damper/fan)			KRP1C74		
Group Control Adaptor PCB (connects to external BMS)			KRP4A71		
Condensate Pump			DACA-CP3-1		

* Optional face plates available to provide a more intuitive user interface and disable specific functions

FXNQ_MVJU9 INSTALLATION SPACE





Condensate Pump as Standard



Outside Air Integration Possible



Filter Included



Optional Auto Cleaning Filter



Surface & Occupancy Sensor Kit as Standard

Round Flow Sensing Cassette FXFQ-AAVJU

The *Round Flow* Sensing Cassette is ideal for open plan applications such as classrooms and offices where adaptive comfort control is preferred. The unit provides an excellent comfort level, energy efficiency, and flexibility due to advanced control functions based on input from three room sensors (occupancy, air temperature, and surface temperature). With 18 configurable airflow distribution patterns, it can be efficient and provide a comfortable environment in smaller, more intricate spaces as well.

Features and Benefits

- » Capacity range from 0.6 TO 4.5 Tons
- » True 360° Airflow and three room sensors enables optimized occupant comfort and efficiency
- » Energy efficient with DC fan motor and auto-logic that adjusts fan speed based on space load
- » Optional self-cleaning filter panel to further increase efficiency and reduce maintenance costs, when used in VRV/IV systems
- » Increased indoor air quality with high efficiency filter options and ventilation connection kit
- » Very flexible with 18 different possible airflow patterns, ensuring ideal air distribution to maximize comfort and efficiency
- » Compact design to allow for installation in small ceiling voids
- » Sound pressure levels as low as 27 db(A)

The built-in occupancy sensor has two main functions: save energy and optimize occupancy comfort. In order to save energy, the function of the occupancy sensor can be used to automatically set back the air temperature and also lower the fan speed if no people are present in the room.

Together with the occupancy sensor, the air-temperature sensor and the built-in surface temperature sensor are



BRC1E73 (option)




AZAI6WSCDKA (option)



BRC1H71W (option)



AZAI6WSPDKC (option)



DTST-ONE-ADA-A (option)



DTST-TOU-ADA-A (option)


used to maintain an even and comfortable temperature distribution from floor to ceiling in the room. This is done by automatically adjusting the supplied airflow rate and the individual position of each of the four supply air louvers in the unit, thus maintaining the required comfortable space environment.

In order to further increase efficiency and reduce maintenance costs, the *Round Flow* Sensing Cassette can be equipped with an optional self-cleaning filter panel that performs automatic air-filter cleaning up to once a day. Dust is deposited into a collection box during the self-cleaning process. When indicated with light on the unit and on the controller display, the dust collection box in the unit can easily and quickly be emptied with a standard vacuum cleaner.

4-way flow vs. Round Flow


Round Flow Ceiling Mounted Cassette type offers 360° airflow with improved temperature distribution.

4-way flow



Areas of uneven temperature

Round Flow



Much fewer areas of uneven temperature

Applications

- » Retail
- » Schools
- » Offices
- » Restaurants



Advanced design for comfort and efficiency

Heat Exchanger Design

Optimized for part load operation
— great enhancement to seasonal energy efficiency

Occupancy and Surface Temperature Sensors

Enables additional energy savings and increased comfort

Optional Self-Cleaning Filter Panel

Provides optimum efficiency, airflow and reduced maintenance



DC Fan Motor

Very efficient — enables fan auto logic based on ΔT set point


DC Drain Pump

Low power consumption

Decoration Panel

- » Efficient due to large air discharge outlets
- » Unique 360° airflow distribution
- » 4 individually controlled louvers enables optimized comfort in the space
- » Possibility to close 1, 2 or 3 louvers adds flexibility

Automatic air-direction control




Air flow from the indoor unit is automatically adjusted to always maintain a comfortable environment — even when occupancy changes.

Dual infrared sensors

Sensors detect the presence of people and surface temperature to provide comfortable air-conditioning and energy savings.

Infrared presence sensor

The sensor detects human presence, and energy saving control can be performed when no people are detected.



Infrared surface sensor

The sensor detects the surface temperature and automatically adjusts operation of the indoor unit to reduce the temperature difference between the ceiling and the floor.

FXFQ_AAVJU° (cont.)

Round Flow Sensing Cassette



Condensate Pump
as Standard



Outside Air
Integration Possible



Filter
Included




Optional
Auto Cleaning Filter




Surface & Occupancy
Sensor Kit as Standard


Automatic air filter cleaning (optional)



At the programmed time, the air filter rotates while the air filter brush turns back and forth to brush the filter.



Dust from the air filter brush is deposited into the dust collection container during the fully automatic self-cleaning process.



When indicated, the dust container in the unit is easily emptied with a standard vacuum cleaner.



FXFQ-AAVJU SPECIFICATIONS		0.60 TON	0.75 TON	1 TON	1.25 TON	1.5 TON	2 TON	2.5 TON	3 TON	4 TON	4.5 TON											
Model Name		FXFQ07AAVJU	FXFQ09AAVJU	FXFQ12AAVJU	FXFQ15AAVJU	FXFQ18AAVJU	FXFQ24AAVJU	FXFQ30AAVJU	FXFQ36AAVJU	FXFQ48AAVJU	FXFQ54AAVJU											
Power Supply	(V/ph/Hz)	208-230/1/60																				
Rated Cooling Capacity	BTU/h	7,200	9,500	12,000	14,400	18,000	23,000	30,000	36,000	48,000	54,000											
Rated Heating Capacity	BTU/h	8,500	10,500	13,500	17,000	20,000	27,000	34,000	40,000	48,000	60,000											
Refrigerant	R-410A																					
Refrigerant Control	Electronic Expansion Valve																					
Airflow Rate H/M/L	CFM	420/406/353	441/406/353	441/406/353	512/459/388	742/618/477	777/618/477	1,112/918/671	1,165/918/671	1,218/971/742	1,53/1006/741											
Unit Weight	lbs	42		48		63		11-5/16														
Unit Height	in.	9-11/16		33-1/16		33-1/16		11-5/16														
Unit Width	in.	33-1/16		33-1/16		33-1/16		11-5/16														
Unit Depth	in.	33-1/16		33-1/16		33-1/16		11-5/16														
Sound Pressure H/M/L	dB(A)	30/28.5/27		31/29/27		35.5/32/28		36/32/28		43.5/38/32												
Unit Condensate Connection	in. O.D.	1-1/4		1-1/4		1-1/4		1-1/4		1-1/4												
Condensate Pump Lift	in.	33-1/2																				
Pipe Connections	Gas	in.	1/2 (Flare)		5/8 (Flare)		5/8 (Flare)		5/8 (Flare)		5/8 (Flare)											
External Finish	Galvanized Steel Plate																					
Protection Devices			Fuse/Breaker		Fan Motor Thermal Protector																	
Recommended Fuse/Breaker	A	15																				
Standard Filter Type		Mold-Resistant Resin Net																				

Nominal Conditions:

Cooling Mode
 Indoor: 80 °F DB / 67 °F WB
 Outdoor: 95 °F DB
 Pipe Length: 25 ft.
 Level Difference: 0 ft.

Heating Mode
 Indoor: 70 °F DB
 Outdoor: 47 °F DB / 43 °F WB
 Pipe Length: 25 ft.
 Level Difference: 0 ft.

Note: Specifications are subject to change without notice.

FXFQ-AAVJU ACCESSORIES WITH:


Accessory	Item #	Self-Cleaning Filter Panel (BYCQ54EEGFU)	Standard Sensing Decoration Panel (BYCQ54EEFU)
Navigation Remote Controller	BRC1E73	Yes ¹	Yes ¹
Navigation Remote Controller	BRC1E52A7	Yes ²	Yes ²
Remote Sensor Kit	KRCS01-4B	Yes	Yes
Outside Air Intake Kit	KAF555D160	Available	Yes
Long-Life Replacement Air Filter	KDBP55H160FA	Yes	Yes
Panel Spacer	KDBP55H160FA	Yes	Yes

OUTDOOR / CONDENSING UNIT COMPATIBILITY

Outdoor Condensing Unit	FXFQ-AAVJU with:	
	Self-Cleaning Filter Panel (BYCQ54EEGFU)	Standard Sensing Decoration Panel (BYCQ54EEFU)
VRV IV X, VRV EMERION	Yes	Yes
VRV LIFE, VRV IV S	Yes	Yes
SkyAir	Yes	Yes

¹ No sensing functions available

² Optional face plates available to provide a more intuitive user interface and disable specific functions

FXFQ INSTALLATION SPACE

MODEL	HEIGHT
FXFQ07-24AAVJU	11"
FXFQ30-54AAVJU	12" or more

* Leave 7 1/8" or more space on sides where the air outlet is closed.



Condensate Pump as Standard

Filter Included

Optional Surface & Occupancy Sensor Kit

Slim, Stylish, Flexible

The unique 4-way ceiling-suspended cassette is an ideal solution for rooms without a false ceiling, or minimal space above a false ceiling, where adaptive comfort control is preferred.

The optional Sensor Kit (occupancy and surface temperature) together with air temperature sensor and advanced control functions enables the unit to provide an exceptional comfort level, energy efficiency, and flexibility.

Features and Benefits

- » Very low unit height of under 8" makes it an ideal solution for school, shops, restaurants and offices with no or low false ceilings
- » Optional Sensor Kit enables input from three room sensors to provide optimized occupant comfort and efficiency
- » Stylish unit blends easily with any interior, as the air louvers close entirely when not in operation
- » Energy efficient fan motor
- » Individual air louver control — one or more louvers can be easily closed via the remote controller when required
- » Ideal for both new and existing buildings
- » Can also be mounted partially recessed in a false ceiling
- » Same appearance and size for all capacity models
- » Standard drain pump with 19.5" lift



BRC1E73 (option)



AZAI6WSCDKA (option)



BRC1H71W (option)



AZAI6WSPDKC (option)



DTST-ONE-ADA-A (option)




DTST-TOU-ADA-A (option)

Flexible Airflow Pattern


The four individually controlled air louvers in the unit enables comfortable space environment in a variety of different room layouts.

Air from each louver can be set to exhaust in 5 different angles between 0 and 60 degrees, or set to auto-swing.





Airflow Angles

Auto Swing: Wide discharge angle: 0° to 60°



Fixed angles: 5 levels



Applications

- » Retail
- » Schools
- » Offices
- » Restaurants

FXUQ_PAVJU SPECIFICATIONS		1.5 TON	2 TON	2.5 TON	3 TON
Model Name		FXUQ18PAVJU	FXUQ24PAVJU	FXUQ30PAVJU	FXUQ36PAVJU
Power Supply	(V/ph/Hz)		208-230/1/60		
Rated Cooling Capacity	BTU/h	18,000	24,000	30,000	36,000
Rated Heating Capacity	BTU/h	20,000	27,000	34,000	40,000
Airflow Rate (H/M/L)	CFM	795/689/565		1095/918/742	
Weight	lbs.	58		60	
Height	in.		7-13/16		
Width	in.		37 3/8		
Depth	in.		37 3/8		
Sound Pressure (H/M/L)	dB(A)	40/38/36		47/44/40	
Condensate Pump Lift	in.		19.5		
Condensate Pipe Connection	in. O.D.		VP20		
Pipe Connections	Gas	in.	1/2 (Flare)	5/8 (Flare)	5/8 (Flare)
	Liquid	in.	1/4 (Flare)	3/8 (Flare)	3/8 (Flare)
Refrigerant			R-410A		
Refrigerant Control			Electronic Expansion Valve		
Maximum Overcurrent Protective Device	A		15		
Minimum Circuit Amps	A	0.6		1.4	
Protection Devices			Fuse and Fan Motor Thermal Protector		
External Finish			White Casing		
Standard Filter Type			Resin Net (with Mold Resister)		

Nominal Conditions: Cooling Mode Indoor: 80°F DB / 67°F WB
Outdoor: 95°F DB
Pipe Length: 25 ft.
Level Difference: 0 ft.

Heating Mode Indoor: 70°F DB
Outdoor: 47°F DB / 43°F WB
Pipe Length: 25 ft.
Level Difference: 0 ft.


Note: Specifications are subject to change without notice.

FXUQ_PAVJU ACCESSORIES


Model Name	FXUQ18PAVJU	FXUQ24PAVJU	FXUQ30PAVJU	FXUQ36PAVJU
Sealing Member of Air Discharge Outlet		KDBHP49B140		
Decoration Panel for Air Discharge		KDBTP49B140		
Replacement Long-Life Filter		KAF5511D160		
Remote Control (wired type)		BRC1E73		
Sensor Kit 2		BRE49B2F		
Madoka Remote Controller		BRC1H71W		
Button Sensor Kit		KRCSH2018-01		
Daikin One+ Smart Thermostat		DTST-ONE-ADA-A		
DKN Plus Interface		AZAI6WSPDKC		
Daikin One Touch		DTST-TOU-A		
Group Control Adaptor Printed Circuit Board1		KRP4A74		
Installation Box for Adaptor PCB		KRP1BA97		
Remote Sensor 2		KRCS01-6B		

¹ Installation box for Adaptor PCB (KRP1BA97) is necessary. ² Remote Sensor can only be installed when Sensor Kit is not installed.

FXUQ_PAVJU INSTALLATION SPACE



Automatic air-direction control



Air-flow from the indoor unit is automatically adjusted to always maintain a comfortable environment — even when occupancy changes.



Condensate Pump as Standard

Outside Air Integration Possible

Filter Included

Designer Comfort

VISTA is a remarkable blend of iconic design and engineering excellence with an elegant white or a silver and white finish. Fitting within the ceiling grid, *VISTA* is stylish, low profile, and compact. Energy efficiency and comfort can be enhanced through the combined use of optional floor and presence sensors. It is also possible to close individual louvers via the wired remote control for personalized comfort.


Features and Benefits

- » New 0.5 ton (5,800 Btu/h) size.
- » Seamless integration in standard architectural ceiling tiles, eliminating any overlap of adjacent tiles.
- » Energy efficient operation thanks to specially developed small tube heat exchanger and two optional intelligent sensors.
- » The use of a high efficiency DC fan motor reduces operational power input up to 48% compared to the previous generation.
- » Provides high degree of control for auxiliary heating devices, with independently configurable on/off temperature values.
- » Direct integration of fresh air through a factory knock out.




Flexible Airflow Patterns

The four air louvers in the unit enables comfortable space environment in many different room layouts.




Airflow Angles

Auto Swing: Wide discharge angle: 0° to 60°




Fixed Angles: 5 Levels



Angles can be also set on site to prevent drafts (0°-35°) or soiling of the ceiling (25°-60°), other than standard setting (0°-60°).

Applications

- » Retail
- » Schools
- » Offices



SPECIFICATIONS		0.5 TON	0.6 TON	0.75 TON	1 TON	1.25 TON	1.5 TON
Model Name		FXZQ05TBVJU	FXZQ07TBVJU	FXZQ09TBVJU	FXZQ12TBVJU	FXZQ15TBVJU	FXZQ18TBVJU
Capacity Index		5.8	7.5	9.5	12	15	18
Power Supply	V/ph/Hz			208/230VAC, 60Hz, 1 phase			
Nominal Cooling Capacity*1	Btu/h (kW)	5,800 (1.7)	7,500 (2.2)	9,500 (2.8)	12,000 (3.5)	15,000 (4.5)	18,000 (5.3)
Nominal Heating Capacity*2	Btu/h (kW)	6,500 (1.9)	8,500 (2.5)	10,500 (3.1)	13,500 (4.0)	17,000 (5.0)	20,000 (5.9)
Fan	Type			Turbo Fan			
	Motor Output	W		50			
	Air Flow Rate (H/M/L)	CFM	300 / 247 / 229	307 / 264 / 229	317 / 282 / 229	353 / 300 / 247	405 / 335 / 282
	Drive Type				DC Direct Drive		
Dimensions - Unit Body (H x W x D)	in. (mm)			10-1/4 x 22-5/8 x 22-5/8 (260x575x575)			
Dimensions - Decoration Panel (H x W x D)	in. (mm)			1-13/16 x 24-7/16 x 24-7/16 (46x620x620)			
Weight (net)	lb. (kg)		40.4 (18.3)		42.6 (19.3)		47 (21.3)
Condensate Pump Lift	in. (mm)			24-15/16 (630)			
Sound Pressure Level (H/M/L speed)	dB(A)	32 / 29.5 / 25.5		33 / 30 / 29.5	33.5 / 30 / 26	37 / 32 / 28	43 / 40 / 33
Pipe Connections	Liquid	in.		1/4 (Flare)			
	Gas	in.		1/2 (Flare)			
	Condensate Drain	in.		VP20			
Refrigerant Control				Electronic Expansion Valve			
Maximum Overcurrent Protection Device	A			15			
Minimum Circuit Ampacity	A		0.3		0.4		0.6
Decoration Panel – White				BYFQ60C3W1W			
Decoration Panel – Silver/White				BYFQ60C3W1S			

Note: *1 Nominal cooling capacities are based on the following conditions: 80°F DB / 67°F WB (26.7°C DB / 19.4°C WB) return air temperature; 95°F DB (35°C DB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.

*2 Nominal heating capacities are based on the following conditions: 70°F DB (21.1°C DB) return air temperature; 47°F DB / 43°F WB (8.3°C DB / 6.1°C WB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.


FXZQ_TBVJU ACCESSORIES

Model Name	FXZQ05TBVJU	FXZQ07TBVJU	FXZQ09TBVJU	FXZQ12TBVJU	FXZQ15TBVJU	FXZQ18TBVJU
Navigation Remote Controller*			BRC1E73			
DKN Cloud Wi-Fi Adaptor			AZAI6WSCDKA			
Madoka Remote Controller			BRC1H71W			
Button Sensor Kit			KRCSH2018-01			
Daikin One+ Smart Thermostat			DTST-ONE-ADA-A			
DKN Plus Interface			AZAI6WSPDKC			
Daikin One Touch			DTST-TOU-A			
Infrared Remote Controller - White**			BRC082A42W			
Infrared Remote Controller - Silver**			BRC082A42S			
Space and Presence Sensor Kit - White**			BRYQ60AAW			
VISTA Decoration Panel - White			BYFQ60C3W2W			
Legacy MVJU9-style Decoration Panel			BYFQ60B3W1			
Remote Sensor Kit			KRCS01-6B			
Wiring Adaptor PCB (interface with aux heater, humidifier, OA damper/fan)			KRC1C75			
Long-Life Replacement Filter			KAFQ441BA60			
Sealing Member of Air Discharge Kit			BDBHQ44C60			
Fresh Air Intake Kit			KDDQ44XA60			

*Optional face plates to provide a more intuitive user interface and disable specific functions

**Not compatible with the legacy-style decoration panel

FXZQ_V-MVJU9 INSTALLATION SPACE



MODEL	HEIGHT
FXZQ05-18TBVJU	11.75" or more

*Leave 7-7/8" or more space on sides where the air outlet is closed.

FXEQ_PVJU

Ceiling-Mounted Cassette (Single Flow)



Condensate Pump
as Standard



Outside Air
Integration Possible

Filter
Included


Slim and Compact Design for Installation Flexibility

Features and Benefits

- » The main body of the unit is optimized to be a compact design. Only 7-7/8" in height and a width of 18-1/2" making it possible to use this style of indoor unit in the tightest of spaces.
- » The innovative discharge air louver design forces air in heating mode to ground level to improve the overall space heating effect of the indoor unit.




Overview of the vertical fins
to the right or left up to 45°



Balance of horizontal fins to
frequency between 20° and 70°

- » The unit is equipped with both horizontal and vertical louvers that can be freely adjusted with the remote controller providing a capability to optimize the airflow and throw to suit your room design.
- » The utilization of both a DC-style Fan Motor and integrated Condensate Pump allow for improvements in energy consumption as well as lower operating sound levels than other styles of indoor units.
- » This Indoor unit can be set to 5 predetermined fan speeds using the BRC1E73 wired remote controller, which allows for optimum and comfortable airflow.



Applications

- » Hotel Rooms
- » Offices
- » Residential (Apartments, Condominiums, etc.)



BRC1E73
(option)



AZAI6WSPDKC
(option)



AZAI6WSCDKA
(option)



BRC1H71W
(option)



DTST-ONE-ADA-A
(option)



DTST-TOU-ADA-A
(option)

- » A Ventilation Air knock-out is provided to allow up to 15% of the rated airflow through the unit to be pretreated outside air.





- » The innovative "smooth finish" decoration panel design helps to minimize dust and dirt build-up and facilitates easier cleaning.

- » The Indoor Unit is equipped with a factory installed condensate pump with a lift capacity of up to 33-7/16" (measured from the bottom of the unit).



- » The units are equipped with customizable auxiliary heat control settings to facilitate the On/Off control of an external auxiliary heat solution.



- » For ease of service and maintenance activities, it is possible to access the main components of the unit by only removing the decoration panel.

FXEQ_PVJU SPECIFICATIONS			0.6 TON	0.75 TON	1.0 TON	1.25 TON	1.5 TON	2 TON
Model			FXEQ07PVJU	FXEQ09PVJU	FXEQ12PVJU	FXEQ15PVJU	FXEQ18PVJU	FXEQ24PVJU
Power Supply			1 phase 60Hz 208/230V					
Cooling capacity	*1,*3	Btu/h	7500	9500	12000	15000	18000	24000
Heating capacity	*2,*3	Btu/h	8500	10500	13500	17000	20000	27000
Electrical	Min. circuit amps (MCA)	A	0.3	0.4	0.4	0.5	0.5	0.7
	Max. overcurrent protection (MOP)	A	15	15	15	15	15	15
Casing/color			Galvanized steel plate					
Dimensions: (H x W x D)		in.	7-7/8 x 18-1/2 x 33-1-1/16				7-7/8 x 18-1/2 x 48-13/16	
Fan	Type		Sirocco fan					
	Air flow rate (Dry coil)	Cooling (H/HM/M/ML/L)	CFM	212/191/173/155/141	244/226/205/187/170	283/265/247/223/194	346/311/276/247/219	441/403/367/336/307
Drive			Direct drive					
Sound pressure level	Cooling (H/HM/M/ML/L)	dBA	30/29/28/27/26	32/31/30/29/28	35/34/33/32/30	38/37/35/33/31	38/37/35/33/31	43/41/39/37/35
Weight		lbs.	38				40	
Piping connections	Liquid	in.	$\varnothing \frac{1}{4}$ (flare connection)					$\varnothing \frac{3}{8}$ (flare connection)
	Gas	in.	$\varnothing \frac{1}{2}$ (flare connection)					$\varnothing \frac{5}{8}$ (flare connection)
	Drain	in.	PVC26 (O.D. 1-1/32 x I.D. 13/16)					
Drain pump lift		in.	25					
Refrigerant control			Electronic expansion valve					
Connectable outdoor unit			R-410A VRV series					
Decoration panel (required option)	Model		BYEP40AW1				BYEP63AW1	
	Color		Fresh White					
	Dimensions (H x W x D)		3-3/16 x 21-5/8 x 37-13/32				3-3/16 x 21-5/8 x 53-5/32	
	Air filter		Resin net (with mold resistant)					
Weight	lbs.		17.6				22	

Note: *1. Nominal cooling capacities are based on the following conditions: return air temperature: 80.0°F DB (26.7°C DB), 67.0°F WB (19.4°C WB), outdoor temperature: 95.0°F DB (35.0°C DB) equivalent ref. piping: 25ft. (7.6m) (Horizontal)

*2. Nominal heating capacities are based on the following conditions: return air temperature: 70.0°F DB (21.1°C DB), outdoor temperature: 47.0°F DB (8.3°C DB), 43.0°F DB (6.1°C WB) equivalent ref. piping: 25ft. (7.6m) (Horizontal)



*3. Capacities are net, including a deduction for cooling (an addition for heating) for indoor fan motor heat.

FXEQ_PVJU ACCESSORIES

Model	FXEQ07PVJU	FXEQ09PVJU	FXEQ12PVJU	FXEQ15PVJU	FXEQ18PVJU	FXEQ24PVJU
Decoration panel			BYEP40AW1			BYEP63AW1
Wired remote controller				BRC1E73		
<i>Madoka</i> Remote Controller				BRC1H71W		
Button Sensor Kit				KRCSH2018-01		
Daikin <i>One+</i> Smart Thermostat				DTST-ONE-ADA-A		
DKN Plus Interface				AZAI6WSPDKC		
Daikin <i>One Touch</i>				DTST-TOU-A		
Remote sensor				KRCS01-4B		
Wiring adaptor printed circuit board	2			KRP1C75		
Group control adaptor printed circuit board	2			KRP4A74		
Adaptor mounting box				KRP1B101		

Note: *1. Electrical box (No. 5-1/6-1) is required for controller (No. 5/6) *2. Adaptor mounting box (No.12) is necessary.

FXEQ_PVJU INSTALLATION SPACE



FXHQ MVJU

Ceiling-Suspended Unit



Optional
Condensate Pump



Filter
Included

Slim, Efficient, Quiet, Easy to Maintain

With its slim, elegant design, the FXHQ ceiling-suspended unit is a great fit for any light commercial space. Wide air openings provide a comfortable airflow and an innovative stream fan ensures quiet operation, making it ideal for retail stores, restaurants, classrooms and conference rooms.

Features and Benefits

- » One of our slimmest indoor units (less than 8") fits within any interior design
- » Wide air discharge outlet distributes a comfortable airflow throughout the entire space with throw of up to 25 ft.
- » Innovative stream fan technology keeps sound pressure levels low
- » Smooth flat louver design makes cleaning simple
- » Long-life filter is standard
- » Models range from 12 MBH to 36 MBH



BRC1E73
(option)



AZAI6WSCDKA
(option)




BRC4C82
(option)



BRC1H71W
(option)



AZAI6WSPDKC
(option)




DTST-ONE-ADA-A
(option)



DTST-TOU-ADA-A
(option)


Quiet Stream Fan (side view)

Uses the quiet stream fan and many more advanced technologies.



Applications

- » Retail/shops
- » Offices
- » Restaurants



FXHQ_MVJU SPECIFICATIONS		1 TON	2 TON	3 TON
Model Name		FXHQ12MVJU	FXHQ24MVJU	FXHQ36MVJU
Power Supply	V/ph/Hz		208-230/1/60	
Rated Cooling Capacity	BTU/h	12,000	24,000	36,000
Rated Heating Capacity	BTU/h	13,500	27,000	40,000
Airflow Rate (H/L)	CFM	410/340	710/600	830/670
Weight	lbs.	55	80	90
Height	in.		7-11/16	
Width	in.	37-13/16	55-1/8	62-5/8
Depth	in.		26-3/4	
Sound Pressure (H/L)	dB(A)	42/33	44/36	46/41
Condensate Pipe Connection	in. O.D.		1	
Pipe Connections	Gas	in.	1/2 (Flare)	5/8 (Flare)
	Liquid	in.	1/4 (Flare)	3/8 (Flare)
Refrigerant			R-410A	
Refrigerant Control			Electronic Expansion Valve	
Maximum Overcurrent Protective Device	A		15	
Minimum Circuit Amps	A	0.8	1.0	1.4
Protection Devices			Fuse and Fan Motor Thermal Protector	
External Finish			White Casing	
Standard Filter Type			Resin Net (with Mold Resistant)	

Nominal Conditions:

Cooling Mode
 Indoor: 80°F DB / 67°F WB
 Outdoor: 95°F DB
 Pipe Length: 25 ft.
 Level Difference: 0 ft.

Heating Mode
 Indoor: 70°F DB
 Outdoor: 47°F DB / 43°F WB
 Pipe Length: 25 ft.
 Level Difference: 0 ft.


Note: Specifications are subject to change without notice.

FXHQ_MVJU ACCESSORIES

Model Name	FXHQ12MVJU	FXHQ24MVJU	FXHQ36MVJU
Navigation Remote Controller*		BRC1E73	
DKN Cloud Wi-Fi Adaptor		AZAI6WSCDKA	
Madoka Remote Controller		BRC1H71W	
Button Sensor Kit		KRCSH2018-01	
Daikin One+ Smart Thermostat		DTST-ONE-ADA-A	
DKN Plus Interface		AZAI6WSPDKC	
Daikin One Touch		DTST-TOU-A	
Wireless Remote Controller		BRC7E83	
Remote Sensor Kit		KRCS01-1B	
Wiring Adaptor PCB (interface with aux/primary heater, humidifier, OA damper/fan)		KRP1C74	
Group Control Adaptor PCB (connects to external BMS)		KRP4A72	
Replacement long-life filter	KAFJ501D56	KAFJ501D112	KAFJ501D160
Condensate Pump		DACA-CP3-1	

* Optional face plates available to provide a more intuitive user interface and disable specific functions

FXHQ_MVJU INSTALLATION SPACE



FXAQ_PVJU

Wall-Mounted Unit



Optional
Condensate Pump



Filter
Included

Stylish, Compact, Convenient, Comfortable

Daikin's wall-mounted units are ideal for cooling or heating smaller zones such as stores, offices, and restaurants. The compact, stylish design lets the unit blend discreetly into any interior design, and airflow can be supplied in any of five different directions and easily programmed via remote control.

Features and Benefits

- » Auto-swing mechanism ensures efficient air distribution via louvers that automatically close when the unit is turned off
- » Wide air discharge outlet distributes a comfortable airflow throughout the entire space
- » Horizontal louvers and front panel can be easily removed for cleaning
- » Drain pipe can be easily hidden from sight
- » Models range from 7.5 MBH to 24 MBH



BRC1E73
(option)



AZAI6WSCDKA
(option)




BRC4C82
(option)



BRC1H71W
(option)



AZAI6WSPDKC
(option)



DTST-ONE-ADA-A
(option)



DTST-TOU-ADA-A
(option)

Applications

- » Retail
- » Restaurants
- » Offices
- » Hotels
- » Multi-family residences



FXAQ_PVJU SPECIFICATIONS		0.6 TON	0.75 TON	1 TON	1.5 TON	2 TON
Model Name		FXAQ07PVJU	FXAQ09PVJU	FXAQ12PVJU	FXAQ18PVJU	FXAQ24PVJU
Power Supply	V/ph/Hz			208-230/1/60		
Rated Cooling Capacity	BTU/h	7,500	9,500	12,000	18,000	24,000
Rated Heating Capacity	BTU/h	8,500	10,500	13,500	20,000	27,000
Airflow Rate (H/L)	CFM	260/160	280/175	290/180	500/400	635/470
Weight	lbs.		26			31
Height	in.			11-3/8		
Width	in.		31-1/4			41-3/8
Depth	in.			9		
Sound Pressure (H/L)	dB(A)	36/31	37/31	38/31	43/37	47/41
Condensate Pipe Connection	in. O.D.			11/16		
Pipe Connections	Gas	in.		1/2 (Flare)		5/8 (Flare)
	Liquid	in.		1/4 (Flare)		3/8 (Flare)
Refrigerant				R-410A		
Refrigerant Control				Electronic Expansion Valve		
Maximum Overcurrent Protective Device	A			15		
Minimum Circuit Amps	A		0.4		0.5	0.6
Protection Devices				Fuse and Fan Motor Thermal Protector		
External Finish				White Casing		
Standard Filter Type				Resin Net (washable)		

Nominal Conditions:

Cooling Mode
 Indoor: 80°F DB / 67°F WB
 Outdoor: 95°F DB
 Pipe Length: 25 ft.
 Level Difference: 0 ft.

Heating Mode
 Indoor: 70°F DB
 Outdoor: 47°F DB / 43°F WB
 Pipe Length: 25 ft.
 Level Difference: 0 ft.

Note: Specifications are subject to change without notice.

FXAQ_PVJU ACCESSORIES

Model Name	FXAQ07PVJU	FXAQ09PVJU	FXAQ12PVJU	FXAQ18PVJU	FXAQ24PVJU
<i>Navigation Remote Controller*</i>			BRC1E73		
DKN Cloud Wi-Fi Adaptor			AZA16WSCDKA		
<i>Madoka Remote Controller</i>			BRC1H71W		
Button Sensor Kit			KRCSH2018-01		
<i>Daikin One+ Smart Thermostat</i>			DTST-ONE-ADA-A		
DKN Plus Interface			AZA16WSPDKC		
<i>Daikin One Touch</i>			DTST-TOU-A		
Wireless Remote Controller			BRC7E818		
Remote Sensor Kit			KRCS01-1B		
Group Control Adaptor PCB (Connects to external BMS)			KRP4A71		
Condensate Pump			DACA-CP1-1		

* Optional face plates available to provide a more intuitive user interface and disable specific functions

FXAQ_PVJU INSTALLATION SPACE





Fig.1




Fig.2

Fig.3

Bottom-right pipe

Back-right pipe
 Back-left pipe
 Bottom-left pipe

FXLQ_MVJU9

Floor-Standing Unit



Filter
Included

Versatile, Logical, Durable, Quiet

The ideal way to save space, our floor-standing units can easily be installed along a perimeter wall. The air distribution from these models will allow you to find the right balance for classrooms, churches, office hallways or similar spaces.

Features and Benefits

- » Ideal for installation beneath a window
- » Unit requires minimal installation space
- » Fitted with a washable long-life filter
- » Remote-control options available
- » Space-saving unit can be freestanding or wall-mounted
- » Models range from 7.5 MBH to 24 MBH



BRC1E73
(option)



AZAI6WSCDKA
(option)



BRC4C82
(option)



BRC1H71W
(option)



AZAI6WSPDKC
(option)



DTST-ONE-ADA-A
(option)



DTST-TOU-ADA-A
(option)

Applications

- » Multi-family residences
- » Single-family residences
- » Churches
- » Historic buildings
- » Schools
- » Offices



FXLQ_MVJU9 SPECIFICATIONS		0.6 TON	0.75 TON	1 TON	1.5 TON	2 TON			
Model Name		FXLQ07MVJU9	FXLQ09MVJU9	FXLQ12MVJU9	FXLQ18MVJU9	FXLQ24MVJU9			
Power Supply		V/ph/Hz		208-230/1/60					
Rated Cooling Capacity		BTU/h	7,500	9,500	12,000	18,000			
Rated Heating Capacity		BTU/h	8,500	10,500	13,500	20,000			
Airflow Rate (H/L)		CFM	245/210		280/210	490/380			
Weight		lbs.	58		66	80			
Height		in.	23-5/8		23-5/8				
Width		in.	39-3/8		44-7/8	55-7/8			
Depth		in.	8-3/4		8-3/4				
Sound Pressure (H/L)		dB(A)	35/32		36/33	40/35			
Condensate Pipe Connection		in. O.D.	27/32		27/32				
Pipe Connections	Gas	in.	1/2 (Flare)			5/8 (Flare)			
	Liquid	in.	1/4 (Flare)			3/8 (Flare)			
Refrigerant		R-410A							
Refrigerant Control		Electronic Expansion Valve							
Maximum Overcurrent Protective Device		A	15		15				
Minimum Circuit Amps		A	0.3	0.5	0.6				
Protection Devices		Fuse and Fan Motor Thermal Protector							
External Finish		Ivory White Casing							
Standard Filter Type		Resin Net (with Mold Resistant)							


Nominal Conditions: Cooling Mode Indoor: 80°F DB / 67°F WB Outdoor: 95°F DB Pipe Length: 25 ft. Level Difference: 0 ft. Heating Mode Indoor: 70°F DB Outdoor: 47°F DB / 43°F WB Pipe Length: 25 ft. Level Difference: 0 ft. Note: Specifications are subject to change without notice.

FXLQ_MVJU9 ACCESSORIES

Model Name	FXLQ12MVJU9	FXLQ18MVJU9	FXLQ24MVJU9	FXNQ12MVJU9	FXNQ18MVJU9	FXNQ24MVJU9
Navigation Remote Controller*				BRC1E73		
DKN Cloud Wi-Fi Adaptor				AZA16WSCDKA		
Madoka Remote Controller				BRC1H71W		
Button Sensor Kit				KRCSH2018-01		
Daikin One+ Smart Thermostat				DTST-ONE-ADA-A		
DKN Plus Interface				AZA16WSPDKC		
Daikin One Touch				DTST-TOU-A		
Wireless Remote Controller				BRC4C82		
Remote Sensor Kit				KRCS01-1B		
Wiring Adaptor PCB (interface with aux/primary heater, humidifier, OA damper/fan)				KRP1C74		
Group Control Adaptor PCB (connects to external BMS)				KRP4A71		

* Optional face plates available to provide a more intuitive user interface and disable specific functions

FXLQ_MVJU9 INSTALLATION SPACE



FXFA_AAVJU (R-32)

Round Flow Sensing Cassette



Condensate Pump as Standard



Outside Air Integration Possible



Filter Included



Optional Auto Cleaning Filter



Surface & Occupancy Sensor Kit as Standard

R32

Adaptive Comfort Control

The *Round Flow* Sensing Cassette is ideal for open-plan applications such as classrooms and offices where adaptive comfort control is preferred. The unit provides excellent comfort, energy efficiency, and flexibility due to innovative control functions based on input from three room sensors (occupancy, air temperature, and surface temperature). With 18 configurable airflow distribution patterns, it can be efficient and provide a comfortable environment in smaller, more intricate spaces as well.

Low GWP R-32 Refrigerant

Aligning with Daikin's goals of decarbonization, sustainability, and advancement towards clean energy, FXFA models feature Low GWP R-32 refrigerant. Widely used and proven globally, readily available, efficient, and affordable, R-32 is an ideal choice to replace R-410A. R-32 is a single component refrigerant offering simplicity and flexibility in charging, and reclaiming.

All R-32 VRV indoor units feature:

- » Factory-installed integrated refrigerant leak sensor
- » Dispersion Mode: Higher airflow rate for leak mitigation through circulation
- » On-board terminal for connection to external alarms and monitoring systems



BRC1NRV71

Features and Benefits:


Capacity range from 0.6 TO 4.5 Tons

- » True 360° Airflow with three room sensors enabling optimal occupant comfort and efficiency.
- » Application flexibility with 18 different airflow patterns ensures ideal air distribution to maximize comfort and efficiency.
- » Ease of outside air integration with optional fresh air intake kit
- » Energy efficient with DC fan motor and auto-logic that adjusts fan speed based on space load


4-way flow vs. Round Flow

Round Flow Ceiling Mounted Cassette type offers 360° airflow with improved temperature distribution.

4-way flow



Round Flow



Applications

- » Retail
- » Schools
- » Offices
- » Restaurants

Advanced design for comfort and efficiency

Heat Exchanger Design

Optimized for part load operation
— great enhancement to seasonal energy efficiency

Occupancy and Surface Temperature Sensors

Enables additional energy savings and increased comfort

Optional Self-Cleaning Filter Panel

Provides optimum efficiency, airflow and reduced maintenance



DC Fan Motor

Very efficient — enables fan auto logic based on ΔT set point

DC Drain Pump

Low power consumption

Decoration Panel

- » Efficient due to large air discharge outlets
- » Unique 360° airflow distribution
- » 4 individually controlled louvers enables optimized comfort in the space
- » Possibility to close 1, 2 or 3 louvers adds flexibility

Automatic air-direction control




Dual infrared sensors

Sensors detect the presence of people and surface temperature to provide comfortable air-conditioning and energy savings.

Infrared presence sensor

The sensor detects human presence, and energy saving control can be performed when no people are detected.



Infrared surface sensor

The sensor detects the surface temperature and automatically adjusts operation of the indoor unit to reduce the temperature difference between the ceiling and the floor.

Air flow from the indoor unit is automatically adjusted to always maintain a comfortable environment — even when occupancy changes.

FXFA_AAVJU (R-32) (cont.)

Round Flow Sensing Cassette



Condensate Pump
as Standard



Outside Air
Integration Possible



Filter
Included




Optional
Auto Cleaning Filter




Surface & Occupancy
Sensor Kit as Standard


Automatic air filter cleaning (optional)




At the programmed time, the air filter rotates while the air filter brush turns back and forth to brush the filter.



Dust from the air filter brush is deposited into the dust collection container during the fully automatic self-cleaning process.



When indicated, the dust container in the unit is easily emptied with a standard vacuum cleaner.



FXFQ-AAVJU SPECIFICATIONS		0.60 TON	0.75 TON	1 TON	1.25 TON	1.5 TON	2 TON	2.5 TON	3 TON	4 TON	4.5 TON
Model Name		FXFA07AAVJU FXFA09AAVJU FXFA12AAVJU FXFA15AAVJU FXFA18AAVJU FXFA24AAVJU FXFA30AAVJU FXFA36AAVJU FXFA48AAVJU FXFA54AAVJU									
Power Supply	(V/ph/Hz)	208-230/1/60									
Rated Cooling Capacity	BTU/h	7,200	9,500	12,000	14,400	18,000	23,000	30,000	36,000	48,000	54,000
Rated Heating Capacity	BTU/h	8,500	10,500	13,500	17,000	20,000	27,000	34,000	40,000	48,000	60,000
Refrigerant		R-32									
Refrigerant Control		Electronic Expansion Valve									
Airflow Rate H/M/L	CFM	441/406/353		512/459/388	547/477/388	777/618/477	1059/882/671	1253/918/671	1253/971/741	1253/1006/741	
Unit Weight	lbs		42			51			58		
Unit Height	in.			9-1/16					11-5/16		
Unit Width	in.				33-1/16						
Unit Depth	in.				33-1/16						
Sound Pressure H/M/L	dB(A)	30/28.5/27		31/29/27	35.5/32/28	36/32/28	43.5/38/32	44/38/32	45/40/35	47/41/36	
Unit Condensate Connection	in. O.D.				1-1/4						
Condensate Pump Lift	in.				33-1/2						
Pipe Connections	Gas	in.		1/2 (Flare)					5/8 (Flare)		
	Liquid	in.		1/4 (Flare)					3/8 (Flare)		
External Finish				Galvanized Steel Plate							
Protection Devices				Fuse/Breaker							
Recommended Fuse/Breaker	A			Fan Motor Thermal Protector							
Standard Filter Type				Mold-Resistant Resin Net							

Nominal Conditions:

Cooling Mode
 Indoor: 80°F DB / 67°F WB
 Outdoor: 95°F DB
 Pipe Length: 25 ft.
 Level Difference: 0 ft.

Heating Mode
 Indoor: 70°F DB
 Outdoor: 47°F DB / 43°F WB
 Pipe Length: 25 ft.
 Level Difference: 0 ft.

Note: Specifications are subject to change without notice.

FXFA-AAVJU ACCESSORIES WITH:


Accessory	Item #	Self-Cleaning Filter Panel (BYCQ54EEGFU)	Standard Sensing Decoration Panel (BYCQ54EEFU)
Navigation Remote Controller	BBRC1NRV71	Yes ¹	Yes ¹
Remote Sensor Kit	KRCS01-6B	Yes	Yes
Outside Air Intake Kit	KAF555D160	-	Yes
Long-Life Replacement Air Filter	KAF5511D160	-	Yes
Panel Spacer	KDBP55H160FA	Yes	Yes

¹ No sensing functions available² Optional face plates available to provide a more intuitive user interface and disable specific functions

Features and Benefits (cont.)

- » Optional self-cleaning filter panel to further increase efficiency and reduce maintenance costs, when used in VRV systems
- » Increased indoor air quality with high efficiency filter options and ventilation connection kit
- » Compact design to allow for installation in small ceiling voids Sound pressure levels as low as 27 db(A)

FXFQ INSTALLATION SPACE



MODEL	HEIGHT
FXFA07-24AAVJU	11"
FXFA30-54AAVJU	12" or more

* Leave 7 1/2" or more space on sides where the air outlet is closed.

FXMA_AAVJU (R-32)

Ducted Concealed Unit



Condensate Pump
as Standard



Outside Air
Integration Possible



Drain Pan
Inspection Port



Auto Fan Speed
Control

R32

Powerful. Concealed. Flexible

Daikin's FXMA HSP Concealed Ducted unit offers design flexibility for many applications. Its compact design with a short chassis height of only 9-11/16" (245 mm) allows for installation in confined spaces. The high-efficiency DC fan motor delivers nominal CFM at up to 0.8" external static pressure. A selectable Auto fan** speed control automatically adjusts the fan speed in response to the room temperature to deliver ideal comfort and help reduce fan energy use.

Low GWP R-32 Refrigerant

Aligning with Daikin's goals of decarbonization, sustainability, and advancement towards clean energy, FXMA models feature Low GWP R-32 refrigerant. Widely used and proven globally, readily available, efficient, and affordable, R-32 is an ideal choice to replace R-410A. R-32 is a single component refrigerant offering simplicity and flexibility in charging and reclaiming.

All R-32 VRV indoor units feature:


- » Factory-installed integrated refrigerant leak sensor
- » Dispersion Mode: Higher airflow rate for leak mitigation through circulation
- » On-board terminal for connection to external alarms and monitoring systems



BRC1NRV71

Features and Benefits:

- » DC fan motor efficiently provides nominal CFM at up to 0.8" W.G.
- » Installation flexibility with a low profile, compact design at less than 12" in height.
- » Reduced risk of condensation on air vents with minimal discharge air temperature setting.
- » Efficient operation using Variable Refrigerant Temperature (VRT).
- » Innovative economizer control logic.
- » Enhance indoor air quality (and LEED® ready) with MERV 13 filter options.
- » Ease of installation with auto-adjusting airflow at commissioning based on external static pressure.
- » Provides a high degree of control for auxiliary heating devices, with independently configurable on/off temperature values.
- » Easy maintenance with complete service access from below. Alternatively the installer can manually select a fan curve with the wired remote control.



Dust from the air filter brush is deposited into the dust collection container during the fully automatic self-cleaning process.

When indicated, the dust container in the unit is easily emptied with a standard vacuum cleaner.

FXMQ-TBVJU SPECIFICATIONS		1.25 TON	1.5 TON	2.0 TON	2.5 TON	3.0 TON	4.0 TON	4.5 TON								
Model Name		FXMA15AAVJU	FXMA18AAVJU	FXMA24AAVJU	FXMA30AAVJU	FXMA36AAVJU	FXMA48AAVJU	FXMA54AAVJU								
Power Supply		Single-phase 208/230V 60Hz														
Rated Cooling Capacity		BTU/h	14,200 (4.2)	18,000 (5.3)	24,000 (7.0)	30,000 (8.8)	36,000 (10.6)	48,000 (14.1)								
Rated Heating Capacity		BTU/h	17,000 (5.0)	20,000 (5.9)	27,000 (7.9)	34,000 (10.0)	40,000 (11.7)	54,000 (15.8)								
Airflow Rate (H/M/L)	SCFM (M3/MIN)	560/447/406	635/565/512	742/635/565	1094/847/795	1130/953/795	1377/1130/918	1518/1235/989								
	(m3/min)	(15.8/12.7/11.5)	(18.0/16.0/14.5)	(21.0/18.0/16.0)	(31.0/24/22.5)	(32.0/27.0/22.5)	(39.0/32.0/26.0)	(43.0/35.0/28.0)								
Height		in.	9-11/16													
Width		in.	39-3/8			55-1/8		61								
Depth		in.	31-1/2													
Condensate Pump Lift		in.	25-5/16													
Sound Level (Reference) *	Power dB(A)	65	64	67	71	72	76	80								
	Pressure dB(A)	37/34/31	36/34/32	39/35/33	43/38/36	44/40/36	48/44/39	52/47/42								
Weight		lbs (kg)	77 (35)		82 (37)	101 (46)		104 (47)								
Condensate Pipe Connection		in. O.D.	VP25													
Pipe Connections	Gas	in. (mm)	ø1/4 (ø6.4) (Flare)		ø3/8 (ø9.5) (Flare)											
	Liquid	in. (mm)	ø1/2 (ø12.7) (Flare)		ø5/8 (ø15.9) Flare											
Refrigerant		R-32														
Refrigerant Control		Electronic Expansion Valve														
Maximum Overcurrent Protective Device		A	15													
Minimum Circuit Amps		A	1.8	1.9	3	3.1	3.6									
Protection Devices		Fuse and Fan Driver Overload Protector														
External Finish		Galvanized Steel Plate														
External Static Pressure (H/L)		in. W.G.	0.80/0.20					0.56/0.20								


* The sound power levels are based on ISO9614 and the sound pressure levels are based on JIS B 8616.

FXMA-PBVJU ACCESSORIES

Model Name	FXMA15AAVJU	FXMA18AAVJU	FXMA24AAVJU	FXMA30AAVJU	FXMA36AAVJU	FXMA48AAVJU	FXMA54AAVJU
Navigation Remote Controller*				BRC1NRV71			
Remote Sensor Kit				KRCS01-6B			
Group Control Adapter PCB (connects to external BMS)				KRP4A71			

*Optional face plates available to provide a more intuitive user interface and disable specific functions

FXMQ-PBVJU INSTALLATION SPACE



Applications:



FXSA_AAVJU (R-32) MSP Concealed Ducted Unit



Condensate Pump
as Standard



Outside Air
Integration Possible



Drain Pan
Inspection Port



Auto Fan Speed
Control

R32

Compact. Powerful. Comfortable.

Daikin's FXSA MSP Concealed Ducted unit offers designers a solution for navigating restrictive application setups. It features a high-efficiency DC fan motor that delivers nominal CFM up to a 0.6" external static pressure from within a compact body that requires only 11-1/4" of clearance space. Additionally, it includes a selectable Auto fan* speed control feature that intelligently modifies the fan speed based on room temperature, enhancing comfort while minimizing fan energy consumption.

Low GWP R-32 Refrigerant

Aligning with Daikin's goals of decarbonization, sustainability, and advancement towards clean energy, FXSA models feature Low GWP R-32 refrigerant. Widely used and proven globally, readily available, efficient, and affordable, R-32 is an ideal choice to replace R-410A. R-32 is a single component refrigerant offering simplicity and flexibility in charging, and reclaiming.

All R-32 VRV indoor units feature:

- » Factory-installed integrated refrigerant leak sensor
- » Dispersion Mode: Higher airflow rate for leak mitigation through circulation
- » On-board terminal for connection to external alarms and monitoring systems




BRC1NRV71

Features and Benefits:

- » Design for installation flexibility, with a factory rear-return configuration and field convertible to bottom return configuration.
- » Slender design requires only 11-1/4" clearance in ceiling space, allowing for installation in cramped applications.
- » Ease of installation with auto-adjusting airflow at commissioning based on external static pressure.
- » Powerful static pressure capability, with up to 0.6 in.w.g. (150Pa) external static pressure.
- » Enhanced comfort and humidity control with dehumidification cooling operation.
- » Minimal discharge air temperature settings help lower the risk of condensation on air vents.
- » Efficient operation using Variable Refrigerant Temperature (VRT).
- » Sound levels as low as 28 dB(A) for quiet operation.
- » Includes a high degree of control for auxiliary heating devices, with independently configurable on/off temperature values.
- » Integral condensate pump with up to 25-5/16" (643mm) of lift from the drain outlet.
- » A maintenance-friendly inspection port lets contractors quickly check the drain pan's conditions.
- » Provides a high degree of control for auxiliary heating devices, with independently configurable on/off temperature values.
- » Integral condensate pump with up to 25-5/16" (643mm) of lift from the drain outlet

Applications

- » Offices
- » Hotel Rooms
- » Multi-family residences
- » Single-family residences
- » Schools



SPECIFICATIONS		0.5 TON	0.6 TON	0.75 TON	1.0 TON	1.25 TON	1.5 TON					
Model Name		FXSA05AAVJU	FXSA07AAVJU	FXSA09AAVJU	FXSA12AAVJU	FXSA15AAVJU	FXSA18AAVJU					
Capacity Index		5.8	7.5	9.5	12	15	18					
Power Supply		V/ph/Hz	208/230VAC, 60Hz, 1 phase									
Nominal Cooling Capacity*1		Btu/h (kW)	5,800 (1.7)	7,200 (2.1)	9,500 (2.8)	12,000 (3.5)	15,000 (4.4)					
Nominal Heating Capacity*2		Btu/h (kW)	6,500 (1.9)	8,500 (2.5)	10,500 (3.1)	13,500 (4.0)	17,000 (5.0)					
Fan	Type		Sirocco fan									
	Motor Output	W	78			130	230					
	Air Flow Rate (H/M/L)	CFM	281 / 265 / 230		318 / 265 / 230	335 / 283 / 247	530 / 441 / 371					
	Drive Type		DC Direct Drive									
	External Static Pressure (Std./Max)		0.2 / 0.6			0.4 / 0.6						
Height	in. (mm)	9-11/16										
Width	in. (mm)	21-11/16			27-9/16		39-3/8					
Depth	in. (mm)	31-1/2										
Weight (net)	lb. (kg)	55 (25)			60 (27)		77 (35)					
Condensate Pump Lift	in. (mm)	25-5/16 (643)										
Sound Pressure Level (H/M/L speed)	dB(A)	33 / 30 / 28			34 / 32 / 30	36 / 33 / 30	34 / 32 / 29					
Pipe Connections	Liquid	in.	1/4 (Flare)									
	Gas	in.	1/2 (Flare)									
	Condensate Drain	in.	VP25									
Refrigerant		R32										
Refrigerant Control		Electronic Expansion Valve										
Maximum Overcurrent Protection Device	A	15										
Minimum Circuit Ampacity	A	0.8			1.4		1.6					
SPECIFICATIONS		2.0 TON	2.5 TON	3.0 TON	4.0 TON	4.5 TON						
Model Name		FXSA24AAVJU	FXSA30AAVJU	FXSA36AAVJU	FXSA48AAVJU	FXSA54AAVJU						
Capacity Index		24	30	36	48	54						
Power Supply	V/ph/Hz	208/230VAC, 60Hz, 1 phase										
Nominal Cooling Capacity*1	Btu/h (kW)	24,000 (7.0)	30,000 (8.8)	36,000 (10.6)	48,000 (14.1)	54,000 (15.8)						
Nominal Heating Capacity*2	Btu/h (kW)	27,000 (7.9)	34,000 (10.0)	40,000 (11.7)	54,000 (15.8)	60,000 (17.6)						
Fan	Type		Sirocco fan									
	Motor Output	W	230			300	350					
	Air Flow Rate (H/M/L)	CFM	742 / 618 / 512	812 / 689 / 565	1130 / 953 / 795	1307 / 1112 / 918	1377 / 1183 / 989					
	Drive Type		DC Direct Drive									
	External Static Pressure (Std./Max)		0.2 / 0.6				0.2 / 0.56					
Height	in. (mm)	9-11/16										
Width	in. (mm)	39-3/8			55-1/8		61					
Depth	in. (mm)	31-1/2										
Weight (net)	lb. (kg)	77 (35)	82 (37)	101 (46)	104 (47)	115 (52)						
Condensate Pump Lift	in. (mm)	25-5/16 (643 mm)										
Sound Pressure Level (H/M/L speed)	dB(A)	36 / 32 / 29	37.5 / 34 / 30	39 / 35 / 32	42 / 38.5 / 35	43 / 40 / 36						
Pipe Connections	Liquid	in.	3/8 (Flare)									
	Gas	in.	5/8 (Flare)									
	Condensate Drain	in.	VP25									
Refrigerant		R32										
Refrigerant Control		Electronic Expansion Valve										
Maximum Overcurrent Protection Device	A	15										
Minimum Circuit Ampacity	A	1.8			2.5	2.8	3.3					

Note:

*1. Nominal cooling capacities are based on the following conditions: 80°F DB / 67°F WB (26.7°C DB / 19.4°C WB) return air temperature; 95°F DB (35°C DB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.


*2. Nominal heating capacities are based on the following conditions: 70°F DB (21.1°C DB) return air temperature; 47°F DB / 43°F WB (8.3°C DB / 6.1°C WB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.

Capacity Range: 0.5 to 4.5 tons Applications:



Flexible Installation.

The FXSA can easily be converted to a bottom-return configuration to optimize the use of space above the ceiling or bulkhead space.



FXTA_AAVJU (R-32)

Multi-Position Air Handling Unit



Outside Air
Integration
Possible



All
Aluminum
Coil



Variable
Speed
ECM Motor



R32

Outstanding flexibility and performance

The FXTA air handler features full multi-position* flexibility to meet the most demanding installation conditions. With its compact and space-saving design at under 46" tall and only 17-1/2" wide up to 3 tons, the FXTA is an ideal choice for tight closet spaces. The FXTA is also designed for zero clearance on three sides and only 24" clearance on the front side for service facilitating installation in restricted spaces.

Low GWP R-32 Refrigerant

Aligning with Daikin's goals of decarbonization, sustainability, and advancement towards clean energy, FXTA models feature Low GWP R-32 refrigerant. Widely used and proven globally, readily available, efficient, and affordable, R-32 is an ideal choice to replace R-410A. R-32 is a single component refrigerant offering simplicity and flexibility in charging, and reclaiming.

All R-32 VRV indoor units feature:

- » Factory-installed integrated refrigerant leak sensor
- » Dispersion Mode: Higher airflow rate for leak mitigation through circulation
- » On-board terminal for connection to external alarms and monitoring systems

Features and Benefits:

- » This full multi-position air handler can upflow, downflow*, horizontal right, and horizontal left installation.
- » High efficiency, ECM motor powers the fan to deliver nominal CFM at up to 0.9" w.g. static.
- » The auto fan speed setting automatically adjusts the fan speed through 5 steps based on the load in the space.
- » Broad line up of electric heat (field installed) options from 3kW to 25kW.




BRC1NRV71

- » Auxiliary heat logic features a reduced heater operation deadband and the ability to run heat pump and auxiliary heat for maximum comfort and performance in colder climates. The auxiliary heat can be interlocked with the ambient temperature sensed by the outdoor unit.
- » Designed with less than 2% air leakage when tested in accordance with ASHRAE standard 193.
- » Easy integration with third-party accessories such as a humidifier or economizer with on-board contacts.
- » Sound levels as low as 36 dBA for operation in sound-sensitive environments
- » Optional factory-installed disconnect (Built-to-order — model FXTA_AAVJUA(D)).



Applications

- » Multi-family
- » Single-family
- » Hotels
- » Offices



SPECIFICATIONS		0.75 TON	1 TON	1.5 TON	2 TON	2.5 TON
Model Name		FXTA09AAVJUA	FXTA12AAVJUA	FXTA18AAVJUA	FXTA24AAVJUA	FXTA30AAVJUA
Model Name (With factory disconnect)		FXTA09AAVJUD	FXTA12AAVJUD	FXTA18AAVJUD	FXTA24AAVJUD	FXTA30AAVJUD
Power Supply	V/ph/Hz			208/230VAC, 60Hz, 1 phase		
Nominal Cooling Capacity*1	Btu/h	9,500	12,000	18,000	24,000	30,000
Nominal Heating Capacity*2	Btu/h	10,500	13,500	20,000	27000	34,000
Fan	Type			Sirocco FC Centrifugal		
	Air Flow Rate (H/M/L)	CFM	300 / 275 / 250	400 / 340 / 280	600 / 510 / 420	800 / 680 / 560
	Static Pressure*3	in w.g.		0.18" / 0.9"		0.23" / 0.9"
	Drive Type			Variable speed ECM		
Height	in.			45		
Width	in.			17.5		
Depth	in.			21		
Weight (net) (TAVJUA/TAVJUD)	lbs.	105/108	112/115	111/118	112/115	113/116
Sound Pressure Level (H speed)	dB(A)		36		45	52
Pipe Connections	Liquid	in.		1/4 (Braze)		3/8 (Braze)
	Gas	in.		1/2 (Braze)		5/8 (Braze)
	Condensate Drain	in.		3/4 (fpt)		
Refrigerant				R32		
Refrigerant Control				Electronic Expansion Valve		
Maximum Overcurrent Protective Device	A			15		
Minimum Circuit Amps	A			4.9		
SPECIFICATIONS		3 TON	3.5 TON	4 TON	4.5 TON	5 TON
Model Name		FXTA36AAVJUD	FXTA42AAVJUA	FXTA48AAVJUA	FXTA54AAVJUA	FXTA60AAVJUA
Model Name (With factory disconnect)		FXTA36AAVJUD	FXTA42AAVJUD	FXTA48AAVJUD	FXTA54AAVJUD	FXTA60AAVJUD
Power Supply	V/ph/Hz			208/230VAC, 60Hz, 1 phase		
Nominal Cooling Capacity*1	Btu/h	36,000	42,000	48,000	54,000	60,000
Nominal Heating Capacity*2	Btu/h	40,000	46,000	54,000	60,000	66,000
Fan	Type			Sirocco FC Centrifugal		
	Air Flow Rate (H/M/L)	CFM	1050 / 900 / 750	1400 / 1190 / 980	1520 / 1290 / 1060	1800 / 1530 / 1260
	Static Pressure*3	in w.g.		0.23" / 0.9"		0.28" / 0.9"
	Drive Type			Variable speed ECM		
Height	in.	45		53.43		58
Width	in.	17.5		21		24.5
Depth	in.			21		
Weight (net) (TAVJUA/TAVJUD)	lbs.	113/116		144/147		165/168
Sound Pressure Level (H speed)	dB(A)	52		54		50
Pipe Connections	Liquid	in.		3/8 (Braze)		
	Gas	in.		5/8 (Braze)		
	Condensate Drain	in.		3/4 (fpt)		
Refrigerant				R32		
Refrigerant Control				Electronic Expansion Valve		
Maximum Overcurrent Protective Device	A			15		
Minimum Circuit Amps	A	4.9		6.5		8.6

Note

*1. Nominal cooling capacities are based on the following conditions: 80 °FDB / 67 °FWB (26.7 °CDB / 19.4 °CWB) return air temperature; 95 °FDB (35 °CDB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.

*2. Nominal heating capacities are based on the following conditions: 70 °FDB (21.1 °CDB) return air temperature; 47 °FDB / 43 °FWB (8.3 °CDB / 6.1 °CWB) outdoor temperature; 25 ft. (7.6 m) equivalent refrigerant piping.

*3. External static pressures are indicated as rated / maximum allowable range.

Electric Heater Options

ELECTRICAL HEATER CAPACITY

Model Name	3kW	5kW	6kW	8kW	10kW	15kW	19kW	20kW	25kW
FXTA09AAVJUA(D)	■								
FXTA12AAVJUA(D)	■	■							
FXTA18AAVJUA(D)	■		■						
FXTA24AAVJUA(D)	■	■	■	■	■				
FXTA30AAVJUA(D)	■		■	■	■	■			
FXTA36AAVJUA(D)	■		■	■	■	■			
FXTA42AAVJUA(D)		■	■	■	■	■	■	■	■
FXTA48AAVJUA(D)		■	■	■	■	■	■		■
FXTA54AAVJUA(D)		■	■	■	■	■			■
FXTA60AAVJUA(D)		■	■	■	■	■		■	■

Applications:



OFFICE



HOTELS



RESIDENTIAL

Kits and Accessories



The optional Daikin Zoning Kit (DZK) increases the flexibility of the Daikin VRV systems by adding a Zoning Box to an indoor unit fan coil, allowing several separate ducts to supply air to different individually-controlled zones in the building. A zone can be a room, part of room, or several rooms. This flexible and scalable Zoning Kit integrates seamlessly with the indoor unit fan coil controls. The DZK system controls work to establish the required set-point, fan speed and mode of operation that is then requested to the VRV indoor unit via the Daikin zone controller. This allows the internal DZK control algorithms to look at the number of zone dampers in operation, and at what position the dampers need to be and adjust the VRV indoor unit operation accordingly. The DZK system is not directly compatible with the suite of Daikin centralized control options such as *iTM*.

A complete Daikin Zoning Kit consists of Zoning Box (with Control Board), Wired Thermostat, and Wireless Thermostats. The optional DZK *BACnet* Interface enables any *BACnet/IP* compatible Building Management System to be used for remote monitoring and control of the DZK.

Wired Thermostat

The 4th generation DZK introduces a software redesign for the Wired thermostat. The revised software offers a simplistic interface for commissioning DZK controls for an enhanced user experience.



The Wired thermostat in the DZK is a graphical colored, touch-screen interface with text menus, intuitive icons, and guided scheduling capability. It displays temperatures and operating values, and selects the operating mode for the system.


Wireless Thermostats

The optional Wireless thermostat offers a backlit, low energy E Ink display with capacitive touch buttons. The user can adjust the zone set point temperature, set user mode schedules, activate local ventilation, and more.



The optional Wireless Lite thermostat offers a sleek, simple user interface to adjust the local zone set point temperature using led-lit capacitive touch buttons.

Now with *BACnet*™/IP compatibility



Zoning Box with Control Box (Model Depends on Indoor Unit)

The Zoning Box in the Daikin Zoning Kit mounts easily on Daikin's Indoor Unit FXMQ-P or FXSQ series fan coils. It consists of the enclosure, individually motorized dampers, and a control box. It is available in different sizes and damper configurations and by utilizing ducts for air supply it can be used to control the air temperature in up to 6 zones. The wired thermostat and the wireless thermostats provide temperature inputs and user interfaces for programming and adjustment of the control functions for each zone.



Daikin *BACnet* HUB4 Module

The DZK *BACnet*™ HUB module will work with any *BACnet/IP* & *BACnet/MSTP* compatible Building Management System. The DZK *BACnet* Hub is now Wi-Fi capable and provides remote access via the Airzone Cloud app or device web browser. (DZK-BACnet-HUB4)




DAIKIN ZONING KIT (DZK) - GENERAL TECHNICAL DATA											
DZK Model	DZKS015E3-4	DZKS015E4-3	DZKS030E4-3	DZKS030E5-4	DZKS048E4-4	DZKS048E6-4	DZK030E4-4	DZK030E5-4	DZK048E4-4	DZK048E6-4	
Height	in.	9-5/8	9-5/16	9-5/8	9-5/16	9-5/8	9-5/16	10-7/16	10-1/4	10-7/16	10-1/4
Width	in.	34-3/16		43-5/8		53-7/16		43-9/16		53-7/16	
Depth	in.	10-7/16									
Weight	lb.	16	18	18	20	18	23	18	20	20	23
No. of Zones		3	4	4	5	4	6	4	5	4	6
Ø of Outlets	in.	8	6	8	6	8	6	8	6	8	6
Power Supply	VAC	110/230 VAC									
	ph	1									
	Hz	60									

DAIKIN ZONING KIT (DZK) - COMPATIBILITY

VRV Indoor Unit	DZKS015E4-4	DZKS015E4-4	DZKS030E4-4	DZKS030E5-4	DZKS048E4-4	DZKS048E6-4
FXSQ15TAVJU	■	■				
FXMQ15/18/24TBVJU			■	■		
FXMQ30/36/48TBVJU					■	■
DZK-MTS-4-W*	■	■	■	■	■	■
DZK-ZTS-4-W	■	■	■	■	■	■
DZK-LTS-4-W	■	■	■	■	■	■
DZK-BACNET-HUB4	■	■	■	■	■	■

*Minimum (1) required per DZK Zoning Kit

CONTROLS CONNECTION OF FXMQ_TBVJU AND DZK (WITHOUT BACNET™)





Outdoor Units



VRV EMERION

Air-Cooled Heat Recovery



Daikin VRV EMERION is available in single and dual-module lineups. The introduction of new 16-20 T single modules allows a system capacity of up to 40 Tons with just two modules. This helps reduce the overall space required for mechanical equipment and optimizes total project costs.

Features and Benefits

- » New Simple and Stylish design with expanded line up with single-module units from 6 – 20 T and dual-modules up to 40 T.
- » Space-saving 16 – 20 T single module units provide up to 34% footprint and up to 500 lbs./unit weight reduction compared to previous series².
- » High energy efficiency with IEERs up to 30.0 delivers up to 30% efficiency increase compared to previous VRV systems.
- » Year-round comfort and energy savings with Daikin's Variable Refrigerant Temperature technology (VRT), compared to standard VRF and previous VRV systems.
- » Increased piping lengths of up to 361 ft. vertical separation between ODU and IDU provide additional application flexibility compared to previous VRV systems¹.
- » Heating down to -13°F as standard and high heating capacities at 17°F make it an ideal choice for all-electric heat pump solutions.
- » Continuous heating during defrost capability with single module (16 T – 20 T) and all dual module systems¹. Only available on Heat Recovery
- » Hot gas defrost circuit allows for installation without base pan heater.
- » Sealed e-box design with an ingress protection rating of IP55 provides for high dust and moisture protection.
- » Dual-fuel ready with connectivity to Daikin communicating gas furnace or all-electric heat pump heating for optimized operational costs based on utility rates.
- » Design flexibility to enlarge system from single to a dual-module without changes to installed main pipe sizes for phased installation or tenant fit-out buildings.
- » Meets several local code compliance certifications such as OSHPD Seismic, Miami Dade Wind, and Chicago pressure relief codes.
- » Reduced wiring costs with up to 34% reduction in MCA values compared to previous series.



- » Engineered for ease of installation and service with three-segment panel design.
- » Enhanced installation and serviceability with increased space for easy field piping connections to service valves¹.
- » Simplified diagnosis with built-in data recorder which stores up to 45 minutes of operational data.
- » Integrates with new Daikin HERO ecosystem, an IoT-based remote monitoring and diagnostics platform. Available Fall of 2022.

¹ Refer to engineering and installation manuals for application rules.

² Model specific; check product specification for details.



* Complete commercial warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.



VRV **EMERION**





VRV EMERION CERTIFIED DATA - HEAT RECOVERY, -230V/60HZ/3PH, 460V/60HZ/3PH

Product #	Capacity (Tons)	IEER Non-Ducted	IEER Ducted	IEER Mixed	SCE Non-Ducted	SCE Ducted	SCE Mixed	COP @ 47°F Non-Ducted	COP @ 47°F Ducted	COP @ 47°F Mixed	COP @ 17°F Non-Ducted	COP @ 17°F Ducted	COP @ 17°F Mixed	EER Non-Ducted	EER Ducted	EER Mixed
REY072AA	6	28.00	23.00	25.50	26.10	22.00	24.05	4.35	3.58	3.97	2.50	2.40	2.45	15.70	12.80	14.25
REY096AA	8	30.00	25.30	27.65	26.10	21.10	23.60	4.30	3.56	3.93	2.48	2.25	2.37	14.60	12.80	13.70
REY0120AA	10	27.50	23.50	25.50	26.10	22.20	24.15	4.00	3.48	3.74	2.38	2.25	2.32	13.20	12.40	12.80
REY0144AA	12	26.50	22.50	24.50	25.60	22.10	23.85	3.80	3.35	3.58	2.20	2.10	2.15	12.50	12.00	12.25
REY0168AA	14	24.00	21.40	22.70	25.60	22.30	23.95	3.50	3.20	3.35	2.10	2.10	2.10	11.50	11.10	11.30
REY0192AA	16	24.00	21.00	22.50	26.60	22.80	24.70	3.85	3.45	3.65	2.05	2.05	2.05	12.30	11.50	11.90
REY0216AA	18	23.00	20.50	21.75	25.50	21.90	23.70	3.70	3.25	3.48	2.05	2.05	2.05	11.50	11.00	11.25
REY0240AA	20	21.60	19.70	20.65	25.60	21.80	23.70	3.45	3.20	3.33	2.05	2.05	2.05	11.00	10.80	10.90
REY0264AA	22	23.90	19.20	21.55	26.20	18.20	22.20	3.70	3.20	3.45	2.35	2.10	2.23	12.00	10.60	11.30
REY0288AA	24	23.20	19.30	21.25	23.40	20.00	21.70	3.60	3.27	3.44	2.41	2.13	2.27	12.00	11.00	11.50
REY0312AA	26	22.80	19.20	21.00	24.40	20.80	22.60	3.60	3.25	3.43	2.35	2.10	2.23	11.30	10.80	11.05
REY0336AA	28	22.10	18.60	20.35	23.40	19.80	21.60	3.60	3.23	3.42	2.20	2.10	2.15	10.50	10.60	10.55
REY0360AA	30	21.00	18.20	19.60	23.00	19.40	21.20	3.60	3.21	3.41	2.05	2.05	2.05	11.50	10.70	11.10
REY0384AA	32	22.00	18.80	20.40	22.00	17.00	19.50	3.40	3.25	3.33	2.05	2.05	2.05	10.70	10.50	10.60
REY0408AA	34	21.50	18.40	19.95	21.90	18.40	20.15	3.40	3.25	3.33	2.05	2.05	2.05	10.70	10.50	10.60
REY0432AA	36	21.10	18.10	19.60	20.30	18.20	19.25	3.40	3.25	3.33	2.05	2.05	2.05	10.70	10.10	10.40
REY0456AA	38	20.20	17.50	18.85	18.90	18.00	18.45	3.40	3.25	3.33	2.05	2.05	2.05	9.90	9.80	9.85
REY0480AA	40	19.40	17.20	18.30	16.90	16.50	16.70	3.40	3.25	3.33	2.05	2.05	2.05	9.70	9.60	9.65

Certified efficiency data in accordance with ANSI/AHRI Standard 1230 2014, "Performance Rating of Variable Refrigerant Flow Multi-Split Air Conditioning and Heat Pump Equipment" for the VRV series. The VRV EMERION series has been designed and optimized to meet or exceed the latest minimum efficiency requirements in 10 C.F.R. Part 431 as determined by the U.S. Department of Energy (DOE) and baseline efficiencies as defined by ASHRAE 90.1 2016. Systems under 65MBH are currently certified to AHRI 210/240. IEER ratings are as defined in ASHRAE 90.1 2016.


DETAILED OPERATION RANGES FOR VRV EMERION REYQ_A HEAT RECOVERY OUTDOOR UNITS



TECHNICAL COOLING FEATURE FOR VRV EMERION REYQ_A HEAT RECOVERY OUTDOOR UNITS

Technical Cooling - Cooling operation extended from 23°F ambient air temperature down to -4°.

The Technical Cooling feature is engaged by field settings on the outdoor unit and on branch selector boxes. It requires addition of snow hoods to the unit and allows operation down to -4°F DB ambient temperature in cooling mode. See the Engineering Data book for complete application rules and contact your local Daikin representative for wind cover specification requirements.



VRV EMERION

Air-Cooled Heat Recovery (cont)



TECHNICAL DATA FOR VRV EMERION - AATJA/AAYDA HEAT RECOVERY OUTDOOR UNITS

		6 Ton	8 Ton	10 Ton	12 Ton	14 Ton	16 Ton	18 Ton	20 Ton	
Model	208-230V/3Ph/60Hz	REYQ72AATJB	REYQ96AATJB	REYQ120AATJB	REYQ144AATJB	REYQ168AATJB	REYQ192AATJB	REYQ216AATJB	REYQ240AATJB	
	460V/3Ph/60Hz	REYQ72AAYDB	REYQ96AAYDB	REYQ120AAYDB	REYQ144AAYDB	REYQ168AAYDB	REYQ192AAYDB	REYQ216AAYDB	REYQ240AAYDB	
	Combination									
Performance	Rated Cooling Capacity	BTU/h	69,000	92,000	114,000	138,000	160,000	184,000	206,000	228,000
	Rated Heating Capacity	BTU/h	77,000	103,000	129,000	154,000	180,000	206,000	232,000	256,000
	Operation Range Cooling	°F (°C) DB				-4* - 122 (-20* - 50)				
	Operation Range Heating	°F (°C) WB				-13 - 60 (-25 - 15.6)				
	Sound Pressure	dB(A)	58	61	61	65	65	67	68	69
	Airflow	CFM	6200	8965	8965	9675	9675	13650	14505	14505
	Fan ESP, Standard/Max	in. W.G.				0.12 / 0.32				
Compressor	Compressors, all inverter	Qty	1			2				
	Revolutions per minute	RPM	4212	4482 + 4482	5934 + 5934	5496 + 5496	6684 + 6684	5586 + 5586	6294 + 6294	7272 + 7272
	Capacity Control Range	%	7-100	4-100	3-100	3-100	2-100	4-100	3-100	3-100
Refrigerant Piping, Layout	Maximum Vertical Pipe Length Above Unit	ft.				164 (361 With Field Setting)*				
	Maximum Vertical Pipe Length Below Unit	ft.				130 (361 With Field Setting)*				
	Maximum Vertical Pipe Length Between IDU	ft.				100				
	Maximum Actual Pipe Length	ft.				541				
	Maximum Equivalent Pipe Length	ft.				620				
	Maximum Total Pipe Length	ft.				3,280				
Refrigerant Piping, Connections	Liquid Pipe, Main Line	in.	3/8	3/8	1/2	1/2	5/8	5/8	5/8	5/8
	Suction Gas Pipe, Main Line	in.	3/4	7/8	1-1/8	1-1/8	1-1/8	1-1/8	1-1/8	1-3/8
	Discharge Gas Pipe, Main Line	in.	5/8	3/4	3/4	7/8	7/8	1-1/8	1-1/8	1 1/8
Connection Ratio	Standard Connectable Indoor Unit Ratio	%				50 - 200 ¹				
	Maximum Number of Indoor Units	Qty	12	16	20	25	29	33	37	41
Electrical	Maximum Overcurrent Protection, MOP (208-230V / 460V)	A	30 / 15	35 / 20	40 / 20	50 / 25	60 / 25	60 / 30	70 / 30	80 / 40
	Minimum Circuit Amps, MCA (208-230V / 460V)	A	27.3 / 12.4	34.1 / 16.4	36.5 / 16.6	47.8 / 21.3	54.9 / 24.9	59.8 / 28.3	67.2 / 29.9	73.7 / 33.4
	Compressor Rated Load Amps, (208-230V / 460V)	A	11.1 / 5.1	7.6 + 7.6 / 3.4 + 3.5	10.5 + 10.6 / 4.8 + 4.8	10.0 + 15.8 / 4.5 + 7.2	12.5 + 20.0 / 5.7 + 9.1	16.6 + 16.6 / 7.5 + 7.6	20.0 + 20.0 / 9.1 + 9.1	24.3 + 24.4 / 11.0 + 11.1
Unit	Factory Refrigerant Charge	lbs.	23.4			25.8				
	Weight (208-230V / 460V)	lbs.	509 / 525	710 / 725	712 / 728	785 / 800	787 / 802	957 / 972	957 / 972	957 / 972
	Dimensions (H x W x D)	in.	65-3/8 x 36-5/8 x 30-1/8		65-3/8 x 48-13/16 x 30-1/8			65-3/8 x 68-7/8 x 30-1/8		

¹Varies based on indoor model selected *Refer to engineering and installation manuals for rules and conditions



	22 Ton	24 Ton	26 Ton	28 Ton	30 Ton	32 Ton	34 Ton	36 Ton	38 Ton	40 Ton
REYQ264AATJB	REYQ288AATJB	REYQ312AATJB	REYQ336AATJB	REYQ360AATJB	REYQ384AATJB	REYQ408AATJB	REYQ432AATJB	REYQ456AATJB	REYQ480AATJB	
REYQ264AAYDB	REYQ288AAYDB	REYQ312AAYDB	REYQ336AAYDB	REYQ360AAYDB	REYQ384AAYDB	REYQ408AAYDB	REYQ432AAYDB	REYQ456AAYDB	REYQ480AAYDB	
1xREYQ120AA 1xREYQ144AA	2xREYQ144AA	1xREYQ144AA 1xREYQ168AA	2xREYQ168AA	1xREYQ168AA 1xREYQ192AA	2xREYQ192AA	1xREYQ192AA 1xREYQ216AA	2xREYQ216AA	1xREYQ216AA 1xREYQ240AA	2xREYQ240AA	
252,000	274,000	296,000	320,000	342,000	364,000	388,000	410,000	434,000	456,000	
282,000	294,000	320,000	338,000	376,000	386,000	394,000	404,000	414,000	424,000	
-4* - 122 (-20* - 50)										
-13 - 60 (-25 - 15.6)										
67	69	69	69	70	71	71	72	72	73	
8965 + 9675	9675 + 9675	9675 + 9675	9675 + 9675	9675 + 13650	13650 + 13650	13650 + 14505	14505 + 14505	14505 + 14505	14505 + 14505	
0.12 / 0.32										
2 + 2										
(5934 + 5934) + (5496 + 5496)	(5496 + 5496) + (5496 + 5496)	(5496 + 5496) + (6684 + 6684)	(6684 + 6684) + (6684 + 6684)	(6684 + 6684) + (5586 + 5586)	(5586 + 5586) + (5586 + 5586)	(5586 + 5586) + (6294 + 6294)	(6294 + 6294) + (6294 + 6294)	(6294 + 6294) + (7272 + 7272)	(6294 + 6294) + (7272 + 7272)	(7272 + 7272) + (7272 + 7272)
1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100
164 (361 With Field Setting)*										
130 (361 With Field Setting)*										
100										
541										
620										
3280										
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
1-3/8	1-3/8	1-3/8	1-3/8	1-5/8	1-5/8	1-5/8	1-5/8	1-5/8	1-5/8	1-5/8
1-1/8	1-1/8	1-1/8	1-1/8	1-3/8	1-3/8	1-3/8	1-3/8	1-3/8	1-3/8	1-3/8
50 - 200 ¹										
45	49	54	58	62	64					
40 + 50 / 20 + 25	50 + 50 / 25 + 25	50 + 60 / 25 + 25	60 + 60 / 25 + 25	60 + 60 / 25 + 30	60 + 60 / 30 + 30	60 + 70 / 30 + 30	70 + 80 / 30 + 30	70 + 80 / 30 + 40	80 + 80 / 40 + 40	
36.5 + 47.8 / 16.6 + 21.3	47.8 + 47.8 / 21.3 + 21.3	47.8 + 54.9 / 21.3 + 24.9	54.9 + 54.9 / 24.9 + 24.9	54.9 + 59.8 / 24.9 + 28.3	59.8 + 59.8 / 28.3 + 28.3	59.8 + 67.2 / 28.3 + 29.9	67.2 + 67.2 / 29.9 + 29.9	67.2 + 73.7 / 29.9 + 33.4	73.7 + 73.7 / 33.4 + 33.4	
(10.5 + 10.6) + (10.0 + 15.8) / (4.8 + 4.8) + (4.5 + 7.2)	(10.0 + 15.8) + (10.0 + 15.8) / (4.5 + 7.2) + (4.5 + 7.2)	(10.0 + 15.8) + (12.5 + 20.0) / (4.5 + 7.2) + (5.7 + 9.1)	(12.5 + 20.0) + (12.5 + 20.0) / (5.7 + 9.1) + (5.7 + 9.1)	(12.5 + 20.0) + (16.6 + 16.6) / (5.7 + 9.1) + (7.5 + 7.6)	(16.6 + 16.6) + (16.6 + 16.6) / (7.5 + 7.6) + (7.5 + 7.6)	(16.6 + 16.6) + (20.0 + 20.0) / (7.5 + 7.6) + (9.1 + 9.1)	(20.0 + 20.0) + (20.0 + 20.0) / (9.1 + 9.1) + (9.1 + 9.1)	(20.0 + 20.0) + (24.3 + 24.3) / (9.1 + 9.1) + (11.0 + 11.1)	(24.3 + 24.3) + (24.3 + 24.4) / (11.0 + 11.1) + (11.0 + 11.1)	
25.8 + 25.8										
712 + 785 / 728 + 800	785 + 785 / 800 + 800	785 + 787 / 800 + 802	787 + 787 / 802 + 802	787 + 957 / 802 + 972	957 + 957 / 972 + 972					
(65-3/8 x 48-13/16 x 30-1/8) + (65-3/8 x 48-13/16 x 30-1/8)				(65-3/8 x 48-13/16 x 30-1/8) + (65-3/8 x 68-7/8 x 30-1/8)	(65-3/8 x 68-7/8 x 30-1/8) + (65-3/8 x 68-7/8 x 30-1/8)					



Daikin VRV EMERION is available in single and dual-module lineups. The introduction of new 16-20 T single modules allows a system capacity of up to 40 Tons with just two modules. This helps reduce the overall space required for mechanical equipment and optimizes total project costs.

Features and Benefits

- » New Simple and Stylish design with expanded line up with single module units from 6-20T and dual-modules up to 40T
- » Space-saving 16 - 20 T single module units provide up to 34% footprint and up to 500 lbs./unit weight reduction compared to previous series²
- » High energy efficiency with IEERs up to 28.5 delivers up to 30% efficiency increase
- » Year-round comfort and energy saving with Daikin's Variable Refrigerant Temperature Technology (VRT)
- » Heating down to -13°F as standard and high heating capacities at 17°F make it an ideal choice for all-electric heat pump solutions
- » Hot gas defrost circuit allows for installation without base pan heater
- » High dust moisture protection with an IP55 rated sealed E-box
- » Dual-Fuel ready with connectivity to Daikin communicating gas furnace or all-electric heat pump heating for optimized operational cost based on utility rates
- » Increased piping lengths of up to 361 ft. vertical separation between ODU and IDU provide additional application flexibility compared to previous VRV systems¹
- » Design flexibility to enlarge system from single to a dual-module without changes to installed main pipe sizes for phased installation or tenant fit-out buildings
- » Local code compliance-ready from factory via alignment with compliance needs, such as OSHPD Seismic, Miami Dade Wind, and Chicago Pressure relief code
- » Reduced wiring costs with up to 27.4% reduction in MCA values compared to previous series
- » Engineered for ease of installation and service with three-segment panel design
- » Factory ships with increase space for easy field piping connection to service valves



- » Built-in data recorder to store up to 40 minutes of operational data
- » Integrates with new Daikin HERO ecosystem, an IoT-based remote monitoring and diagnostics platform
- » Connect non standard VRV terminal units and AHUs with Daikin VRV EMERION leveraging Daikin Air Handling Unit Integration Kit to extend benefits of inverter technology to custom terminal units and AHUs. A kit consists of One Control Box and One EEV box. Offered via EKEQMCBAV3-US and EKEQFCBAV3-US.

¹ Refer to engineering and installation manuals for application rules.

² Model specific; check product specification for details.



* Complete commercial warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.



VRV **EMERION**

AHRI CERTIFIED®
www.ahridirectory.org
Variable Refrigerant Flow (VRF) Multi-Split AC and HP
AHRI Standard 1230



OUTDOOR UNITS

VRV EMERION CERTIFIED DATA - HEAT PUMP, -230V/60HZ/3PH, 460V/60HZ/3PH

Product #	Capacity [Tons]	IEER Non-Ducted	IEER Ducted	IEER Mixed	COP @ 47°F Ducted	COP @ 47°F Mixed	COP @ 17°F Non-Ducted	COP @ 17°F Ducted	COP @ 17°F Mixed	EEER Non-Ducted	EEER Ducted	EEER Mixed
RXYQ72AA	6	27.00	21.40	24.20	4.00	3.54	3.77	2.49	2.42	2.46	15.20	13.00
RXYQ96AA	8	28.50	24.80	26.65	4.10	3.52	3.81	2.53	2.42	2.48	14.30	12.80
RXYQ120AA	10	26.60	23.40	25.00	3.77	3.43	3.60	2.46	2.42	2.44	12.60	12.00
RXYQ144AA	12	25.40	22.90	24.15	3.70	3.36	3.53	2.18	2.12	2.15	12.40	11.70
RXYQ168AA	14	23.40	21.20	23.30	3.40	3.33	3.37	2.18	2.12	2.15	11.20	11.00
RXYQ192AA	16	23.60	21.20	22.40	3.66	3.44	3.55	2.22	2.12	2.17	11.60	11.60
RXYQ216AA	18	22.20	21.00	21.60	3.62	3.32	3.47	2.18	2.12	2.15	11.01	10.90
REYQ240AA	20	21.80	19.60	20.70	3.34	3.20	3.27	2.16	2.12	2.14	11.00	10.60
REYQ264AA	22	22.60	19.20	20.90	3.50	3.24	3.37	2.33	2.12	2.23	11.20	10.00
REYQ288AA	24	22.40	19.20	20.80	3.50	3.31	3.41	2.41	2.12	2.27	11.40	10.40
REYQ312AA	26	21.80	19.20	20.50	3.50	3.22	3.36	2.35	2.12	2.24	10.70	10.20
REYQ336AA	28	21.40	18.50	19.95	3.50	3.20	3.35	2.18	2.12	2.15	10.10	10.20
REYQ360AA	30	20.40	18.50	19.45	3.50	3.20	3.35	2.14	2.12	2.13	11.00	10.10
REYQ384AA	32	21.40	18.80	20.10	3.35	3.24	3.30	2.18	2.12	2.15	10.20	10.15
REYQ408AA	34	21.30	18.10	19.70	3.35	3.24	3.30	2.18	2.12	2.15	10.20	9.80
REYQ432AA	36	20.60	17.20	18.90	3.35	3.24	3.30	2.18	2.12	2.15	10.20	9.50
REYQ456AA	38	19.80	16.80	18.30	3.30	3.22	3.26	2.18	2.12	2.15	9.60	9.50
REYQ480AA	40	19.00	16.40	18.40	3.20	3.20	3.20	2.18	2.12	2.15	9.60	9.50

Certified efficiency data in accordance with ANSI/AHRI Standard 1230 2014, "Performance Rating of Variable Refrigerant Flow Multi-Split Air Conditioning and Heat Pump Equipment" for the VRV series. The VRV EMERION series has been designed and optimized to meet or exceed the latest minimum efficiency requirements in 10 C.F.R. Part 431 as determined by the U.S. Department of Energy (DOE) and baseline efficiencies as defined by ASHRAE 90.1 2016. Systems under 65MBH are currently certified to AHRI 210/240. IEER ratings are as defined in ASHRAE 90.1 2016.

DETAILED OPERATION RANGES FOR VRV EMERION REYQ_A HEAT RECOVERY OUTDOOR UNITS




TECHNICAL COOLING FEATURE FOR VRV EMERION REYQ_A HEAT RECOVERY OUTDOOR UNITS

Technical Cooling -
Cooling operation
extended from 23°F
ambient air temperature
down to -4°.

The Technical Cooling
feature is engaged by field
settings on the outdoor
unit and on branch selector
boxes. It requires addition
of snow hoods to the unit
and allows operation
down to -4°F DB
ambient temperature in
cooling mode.

See the Engineering
Data book for complete
application rules and
contact your local Daikin
representative for wind
cover specification
requirements.





TECHNICAL DATA FOR VRV EMERION - AATJA/AAYDA HEAT PUMP OUTDOOR UNITS

		6 Ton	8 Ton	10 Ton	12 Ton	14 Ton	16 Ton	18 Ton	20 Ton	
Model	208-230V/3Ph/60Hz	RXYQ72AATJB	RXYQ96AATJB	RXYQ120AATJB	RXYQ144AATJB	RXYQ168AATJB	RXYQ192AATJB	RXYQ216AATJB	RXYQ240AATJB	
	460V/3Ph/60Hz	RXYQ72AAYDB	RXYQ96AAYDB	RXYQ120AAYDB	RXYQ144AAYDB	RXYQ168AAYDB	RXYQ192AAYDB	RXYQ216AAYDB	RXYQ240AAYDB	
	Combination									
Performance	Rated Cooling Capacity	BTU/h	69,000	92,000	114,000	138,000	160,000	184,000	206,000	228,000
	Rated Heating Capacity	BTU/h	77,000	103,000	126,000	154,000	180,000	206,000	232,000	248,000
	Operation Range Cooling	°F (°C) DB				23 – 122 (-5 – 50)				
	Operation Range Heating	°F (°C) WB				-13 – 60 (-25 – 15.6)				
	Sound Pressure	dB(A)	58	61	61	65	65	67	68	69
	Airflow	CFM	6200	8965	8965	9675	9675	13650	14505	14505
	Fan ESP, Standard/Max	in. W.G.				0.12 / 0.32				
Compressor	Compressors, all inverter	Qty	1			2				
	Revolutions per minute	RPM	4212	4482 + 4482	5934 + 5934	5496 + 5496	6684 + 6684	5586 + 5586	6294 + 6294	7272 + 7272
	Capacity Control Range	%	7-100	4-100	3-100	3-100	2-100	4-100	3-100	3-100
Refrigerant Piping, Layout	Maximum Vertical Pipe Length Above Unit	ft.				164 (361 With Field Setting)*				
	Maximum Vertical Pipe Length Below Unit	ft.				130 (361 With Field Setting)*				
	Maximum Vertical Pipe Length Between IDU	ft.				98				
	Maximum Actual Pipe Length	ft.				540				
	Maximum Equivalent Pipe Length	ft.				623				
	Maximum Total Pipe Length	ft.				3280				
Refrigerant Piping, Connections	Liquid Pipe, Main Line	in.	3/8	3/8	1/2	1/2	5/8	5/8	5/8	
	Suction Gas Pipe, Main Line	in.	3/4	7/8	1-1/8	1-1/8	1-1/8	1-1/8	1-1/8	1-3/8
Connection Ratio	Standard Connectable Indoor Unit Ratio	%				50 - 200 ¹				
	Maximum Number of Indoor Units	Qty	12	16	20	25	29	33	37	41
Electrical	Maximum Overcurrent Protection, MOP (208-230V / 460V)	A	30 / 15	35 / 20	40 / 20	50 / 25	60 / 30 (25 ²)	60 / 35 (30 ²)	70 / 35 (30 ²)	80 / 40
	Minimum Circuit Amps, MCA (208-230V / 460V)	A	27.3 / 12.4	34.1 / 16.4	36.5 / 16.6	47.8 / 21.3	54.9 / 24.9	59.8 / 28.3	67.2 / 29.9	73.7 / 33.4
	Compressor Rated Load Amps, (208-230V / 460V)	A	11.1 / 5.1	7.6 + 7.6 / 3.4 + 3.5	10.5 + 10.6 / 4.8 + 4.8	10.0 + 15.8 / 4.5 + 7.2	12.5 + 20.0 / 5.7 + 9.1	16.6 + 16.6 / 7.5 + 7.6	20.0 + 20.0 / 9.1 + 9.1	24.3 + 24.4 / 11.0 + 11.1
Unit	Factory Refrigerant Charge	lbs.	15.2	24.9	25.4	25.8	25.8	25.8	25.8	
	Weight (208-230V / 460V)	lbs.	496 / 507	683 / 694	683 / 694	750 / 761	750 / 761	904 / 915	904 / 915	
	Dimensions (H x W x D)	in.	65-3/8 x 36-5/8 x 30-1/8		65-3/8 x 48-13/16 x 30-1/8			65-3/8 x 68-7/8 x 30-1/8		

¹Varies based on indoor model selected ²UL 60335-2-40 calculated MOP values *Refer to engineering and installation manuals for rules and conditions



	22 Ton	24 Ton	26 Ton	28 Ton	30 Ton	32 Ton	34 Ton	36 Ton ²	38 Ton	40 Ton
	RXYQ264AATJB	RXYQ288AATJB	RXYQ312AATJB	RXYQ336AATJB	RXYQ360AATJB	RXYQ384AATJB	RXYQ408AATJB	RXYQ432AATJB	RXYQ456AATJB	RXYQ480AATJB
	RXYQ264AAYDB	RXYQ288AAYDB	RXYQ312AAYDB	RXYQ336AAYDB	RXYQ360AAYDB	RXYQ384AAYDB	RXYQ408AAYDB	RXYQ432AAYDB	RXYQ456AAYDB	RXYQ480AAYDB
	1 x RXYQ120AA 1 x RXYQ144AA	2 x RXYQ144AA	1 x RXYQ144AA 1 x RXYQ168AA	2 x RXYQ168AA	1 x RXYQ168AA 1 x RXYQ192AA	2 x RXYQ192AA	1 x RXYQ192AA 1 x RXYQ216AA	2 x RXYQ216AA	1 x RXYQ216AA 1 x RXYQ240AA	2 x RXYQ240AA
	252,000	274,000	296,000	320,000	342,000	364,000	388,000	410,000	434,000	456,000
	282,000	294,000	320,000	338,000	376,000	386,000	394,000	404,000	414,000	424,000
	23 – 122 (-5 – 50)									
	-13 – 60 (-25 – 15.6)									
	67	69	69	69	70	71	71	72	72	73
	8965 + 9935	9935 + 9935	9935 + 9935	9935 + 9935	9935 + 13665	13665 + 13665	13665 + 14510	14510 + 14510	14510 + 14510	14510 + 14510
	0.12 / 0.32									
	2 + 2									
	(5934 + 5934) + (5496 + 5496)	(5496 + 5496) + (5496 + 5496)	(5496 + 5496) + (6684 + 6684)	(6684 + 6684) + (6684 + 6684)	(6684 + 6684) + (5586 + 5586)	(5586 + 5586) + (5586 + 5586)	(5586 + 5586) + (6294 + 6294)	(6294 + 6294) + (6294 + 6294)	(6294 + 6294) + (7272 + 7272)	(7272 + 7272) + (7272 + 7272)
	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100	1-100
	164 (361 With Field Setting)*									
	130 (361 With Field Setting)*									
	98									
	540									
	623									
	3280									
	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
	1-3/8	1-3/8	1-3/8	1-3/8	1-5/8	1-5/8	1-5/8	1-5/8	1-5/8	1-5/8
	50 - 200 ¹									
	45	49	54	58	62	64				
	40 + 50 / 20 + 25	50 + 50 / 25 + 25	50 + 60 / 25 + 30 (25 + 25 ²)	60 + 60 / 30 + 30 (25 ² + 25 ²)	60 + 60 / 30 + 35 (25 ² + 30 ²)	60 + 60 / 35 + 35 (30 ² + 30 ²)	60 + 70 / 35 + 35 (30 ² + 30 ²)	70 + 70 / 35 + 35 (30 ² + 30 ²)	70 + 80 / 35 + 40 (30 ² + 40)	80 + 80 / 40 + 40
	36.5 + 47.8 / 16.6 + 21.3	47.8 + 47.8 / 21.3 + 21.3	47.8 + 54.9 / 21.3 + 24.9	54.9 + 54.9 / 24.9 + 24.9	54.9 + 59.8 / 24.9 + 28.3	59.8 + 59.8 / 28.3 + 28.3	59.8 + 67.2 / 28.3 + 29.9	67.2 + 67.2 / 29.9 + 29.9	67.2 + 73.7 / 29.9 + 33.4	73.7 + 73.7 / 33.4 + 33.4
	(10.5 + 10.6) + (10.0 + 15.8) / (4.8 + 4.8) + (4.5 + 7.2)	(10.0 + 15.8) + (10.0 + 15.8) / (4.5 + 7.2) + (4.5 + 7.2)	(10.0 + 15.8) + (12.5 + 20.0) / (4.5 + 7.2) + (5.7 + 9.1)	(12.5 + 20.0) + (12.5 + 20.0) / (5.7 + 9.1) + (5.7 + 9.1)	(12.5 + 20.0) + (16.6 + 16.6) / (5.7 + 9.1) + (7.5 + 7.6)	(16.6 + 16.6) + (16.6 + 16.6) / (7.5 + 7.6) + (7.5 + 7.6)	(16.6 + 16.6) + (20.0 + 20.0) / (9.1 + 9.1) + (9.1 + 9.1)	(20.0 + 20.0) + (20.0 + 20.0) / (9.1 + 9.1) + (9.1 + 9.1)	(20.0 + 20.0) + (24.3 + 24.4) / (9.1 + 9.1) + (11.0 + 11.1)	(24.3 + 24.4) + (24.3 + 24.4) / (11.0 + 11.1) + (11.0 + 11.1)
	25.4 + 25.8	25.8 + 25.8	25.8 + 25.8	25.8 + 25.8	25.8 + 25.8	25.8 + 25.8	25.8 + 25.8	25.8 + 25.8	25.8 + 25.8	25.8 + 25.8
	683 + 750/ 694 + 761	750 + 750/ 761 + 761	750 + 750/ 761 + 761	750 + 750/ 761 + 761	750 + 904 / 761 + 915	904 + 904 / 915 + 915				
	(65-3/8 x 48-13/16 x 30-1/8) + (65-3/8 x 48-13/16 x 30-1/8)					(65-3/8 x 68-7/8 x 30-1/8) + (65-3/8 x 68-7/8 x 30-1/8)				

VRV IV X

Air-Cooled Heat Recovery



Engineered and assembled in North America, Daikin's VRV IV X Heat Recovery adapts VRV to North American HVAC market needs by expanding the applications in which VRV can be leveraged to solve traditional HVAC challenges. Packed with advanced technology, the VRV IV X is the industry's first 3-phase variable refrigerant flow system with dual-fuel capability. The new series is equipped with features to optimize initial capital required on phased installations and provides ease of service and maintenance.

Features and Benefits

- » Adapting VRV to North American market needs
 - Industry's first 3-phase variable refrigerant flow system to integrate with communicating gas furnaces.
 - Design flexibility to enlarge system from single to dual module or dual to triple module without change to installed main pipe sizes¹.
 - Engineered to optimize capital on phased and tenant fit out commercial buildings.
 - Choice of gas furnace or heat pump heating for optimizing operational costs based on utility cost.
 - Year round comfort and energy savings with Variable Refrigerant Temperature (VRT) technology.
- » Technology that matters
 - Engineered with Daikin's patented vapor injection compressor technology.
 - Corrosion resistant up to 1000¹ hours Daikin Blue Fin coating as factory standard.
 - Heat exchanger engineered with a bottom refrigerant circuit that allows installation without base pan heater.
 - Refrigerant cooled inverter technology keeps PCB cool independent of ambient temperature.
- » Engineered for maintenance
 - New service window provides ease of access to the multi-functional display without removing the main electrical panel. The built-in multi-functional display is utilized for commissioning and maintenance and quickly converts to digital gauges to provide refrigerant pressure and temperatures.
 - Multi-functional display eliminates the need to connect gauges during regular maintenance checks.
 - Ease of commissioning with ability to program off site and upload using configurator tool.

VRV IV X

Applications:




- Field performable intermittent outdoor fan operation to help minimize snow accumulation on fan blades when the system is in thermal off.
- Seamless integration with T-Series and *Flex Branch Selector* Boxes, M, P, and T-Series indoor units.
- Compatible with the full suite of Daikin VRV controls.
- Outstanding 10-Year Parts Warranty* as standard.

* Complete commercial warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com.

¹ When testing in accordance to ASTM B117 methodology.

¹ Refer to engineering manuals for design rules and pipe sizes.







VRV IV X CERTIFIED DATA - HEAT RECOVERY, 208-230V/60HZ/3PH, 460V/60HZ/3PH

Product #	Capacity (Tons)	IEER Non-Ducted	IEER Ducted	IEER Mixed	SCE Non-Ducted	SCE Ducted	SCE Mixed	COP @ 47°F Non-Ducted	COP @ 47°F Ducted	COP @ 47°F Mixed	COP @ 17°F Non-Ducted	COP @ 17°F Ducted	COP @ 17°F Mixed	EER Non-Ducted	EER Ducted	EER Mixed
REYQ72XA	6	25.20	21.30	23.25	26.10	22.00	24.05	4.30	3.68	3.99	2.50	2.25	2.38	15.80	13.90	14.85
REYQ96XA	8	27.80	21.90	24.85	26.40	21.10	23.75	4.23	3.56	3.90	2.63	2.31	2.47	14.60	12.50	13.55
REYQ120XA	10	25.50	22.60	24.05	26.00	22.00	24.00	3.81	3.48	3.65	2.54	2.28	2.41	13.20	12.30	12.75
REYQ144XA	12	23.50	21.60	22.55	25.50	22.00	23.75	3.75	3.42	3.59	2.16	2.12	2.14	11.90	11.60	11.75
REYQ168XA	14	22.30	20.40	21.35	25.50	22.20	23.85	3.55	3.30	3.43	2.08	2.05	2.07	10.70	10.70	10.70
REYQ192XA	16	22.60	21.40	22.00	26.60	22.80	24.70	3.85	3.67	3.76	2.50	2.37	2.44	13.00	13.00	13.00
REYQ216XA	18	23.10	21.70	22.40	25.50	21.90	23.70	3.76	3.52	3.64	2.34	2.20	2.27	12.40	12.30	12.35
REYQ240XA	20	22.20	20.00	21.10	25.60	21.80	23.70	3.68	3.39	3.54	2.34	2.16	2.25	11.60	11.70	11.65
REYQ264XA	22	21.60	18.00	19.80	26.10	18.20	22.15	3.62	3.20	3.41	2.22	2.07	2.15	11.20	10.40	10.80
REYQ288XA	24	21.00	17.90	19.45	23.30	19.90	21.60	3.51	3.20	3.36	2.20	2.06	2.13	11.00	10.30	10.65
REYQ312XA	26	20.40	18.00	19.20	24.30	20.70	22.50	3.56	3.20	3.38	2.09	2.05	2.07	9.90	9.90	10.00
REYQ336XA	28	20.00	17.30	18.65	23.30	19.80	21.55	3.53	3.20	3.37	2.12	2.05	2.09	9.90	9.50	9.70
REYQ360XA	30	20.00	18.80	19.40	23.00	19.40	21.20	3.56	3.20	3.38	2.25	2.10	2.18	10.90	10.60	10.75
REYQ384XA	32	19.00	17.60	18.30	21.90	17.00	19.45	3.21	3.20	3.21	2.22	2.06	2.14	9.70	9.90	9.80
REYQ408XA	34	17.20	17.70	17.45	21.80	18.30	20.05	3.21	3.20	3.21	2.09	2.05	2.07	9.80	9.70	9.75
REYQ432XA	36	16.20	17.30	16.75	20.20	18.10	19.15	3.21	3.20	3.21	2.08	2.06	2.07	9.80	9.70	9.75
REYQ456XA	38	16.20	16.70	16.45	18.80	17.90	18.35	3.21	3.20	3.21	2.07	2.05	2.06	9.30	9.50	9.40

Certified efficiency data in accordance with ANSI/AHRI Standard 1230 2014, "Performance Rating of Variable Refrigerant Flow Multi-Split Air Conditioning and Heat Pump Equipment" for the VRV series. The VRV IV X series has been designed and optimized to meet or exceed the latest minimum efficiency requirements in 10 C.F.R. Part 431 as determined by the U.S. Department of Energy (DOE) and baseline efficiencies as defined by ASHRAE 90.1 2016. Systems under 65MBH are currently certified to AHRI 210/240. IEER ratings are as defined in ASHRAE 90.1 2016.

DETAILED OPERATION RANGES FOR VRV IV X REYQ_X HEAT RECOVERY OUTDOOR UNITS




TECHNICAL COOLING FEATURE FOR VRV IV X REYQ_X HEAT RECOVERY OUTDOOR UNITS

Technical Cooling - Cooling operation extended from 23°F ambient air temperature down to -4°.

The Technical Cooling feature is engaged by field settings on the outdoor unit and on branch selector boxes. It requires addition of snow hoods to the unit and allows operation down to -4°F DB ambient temperature in cooling mode.

See the Engineering Data book for complete application rules and contact your local Daikin representative for wind cover specification requirements.



VRV IV X

Air-Cooled Heat Recovery (cont.)



TECHNICAL DATA FOR VRV IV X-TATJA/TAYDA HEAT RECOVERY OUTDOOR UNITS

		6 Ton	8 Ton	10 Ton	12 Ton	14 Ton	16 Ton	18 Ton	20 Ton	
Model	208-230V/3Ph/60Hz	REYQ72XBTJA	REYQ96XBTJA	REYQ120XBTJA	REYQ144XBTJA	REYQ168XBTJA	REYQ192XBTJA	REYQ216XBTJA	REYQ240XBTJA	
	460V/3Ph/60Hz	REYQ72XBYDA	REYQ96XBDY	REYQ120XBYDA	REYQ144XBYDA	REYQ168XBYDA	REYQ192XBYDA	REYQ216XBYDB	REYQ240XBYDA	
	Combination						2 x REYQ96XA	1 x REYQ96XA 1 x REYQ120XA	2 x REYQ120XA	
Performance	Rated Cooling Capacity	BTU/h	69,000	92,000	114,000	138,000	156,000	184,000	206,000	228,000
	Rated Heating Capacity	BTU/h	77,000	103,000	129,000	154,000	174,000	206,000	232,000	256,000
	Standard Operation Range Cooling	°F (°C) DB				23 to 122				
	Standard Operation Range Heating	°F (°C) WB				-13 to 60				
	Sound Pressure	dB(A)	65	65	65	66	66	68	68	68
	Airflow	CFM	7283	7989	7989	9480	9480	7989 + 7989	7989 + 7989	7989 + 7989
Compressor	Fan ESP, Standard/Max	in. W.G.				0.12 / 0.32				
	Compressors, all inverter	Qty			1			2		
	Revolutions per minute	RPM	3738	5142	6888	5214	6330	5214 + 5214	5994 + 5994	6702 + 6702
Refrigerant Piping, Layout	Capacity Control Range	%	15-100	13-100	11-100	14-100	12-100	6-100	6-100	5-100
	Maximum Vertical Pipe Length Above Unit	ft.				164 (295 With Field Setting)				
	Maximum Vertical Pipe Length Below Unit	ft.				130 (195 With Field Setting)				
	Maximum Vertical Pipe Length Between IDU	ft.				100				
	Maximum Actual Pipe Length	ft.				541				
	Maximum Equivalent Pipe Length	ft.				620				
Refrigerant Piping, Connections	Maximum Total Pipe Length	ft.				3,280				
	Liquid Pipe, Main Line	in.	3/8	3/8	1/2	1/2	5/8	5/8	5/8	5/8
	Suction Gas Pipe, Main Line	in.	3/4	7/8	1-1/8	1-1/8	1-1/8	1-1/8	1-1/8	1-3/8
Connection Ratio	Discharge Gas Pipe, Main Line	in.	5/8	3/4	3/4	7/8	7/8	1-1/8	1-1/8	1-1/8
	Standard Connectable Indoor Unit Ratio	%	70 - 200 ¹			50 - 200 ¹				
	Maximum Number of Indoor Units	Qty	12	16	20	25	29	33	37	41
Electrical	Maximum Overcurrent Protection, MOP (208-230v/460v)	A	45 / 25	45 / 25	50 / 25	70 / 40	70 / 40	45 + 45 / 25 + 25 /	45 + 50 / 25 + 25 /	50 + 50 / 25 + 25 /
	Minimum Circuit Amps, MCA (208-230v/460v)	A	38.1 / 18.9	38.1 / 21.1	43.0 / 21.1	58.3 / 27.9	61.9 / 31.1	38.1 + 38.1 / 21.1 + 21.1 /	38.1 + 43.0 / 21.1 + 21.1 /	43.0 + 43.0 / 21.1 + 21.1 /
	Compressor Rated Load Amps, (208-230v/460v)	A	20.8 / 9.4	23.3 / 10.5	28.2 / 12.8	42.6 / 19.3	49.0 / 22.2	24.7 + 24.7 / 11.2 + 11.2 /	28.5 + 28.5 / 12.9 + 12.9 /	29.0 + 29.0 / 13.5 + 13.5 /
Unit	Factory Refrigerant Charge	lbs.			25.8			25.8 + 25.8		
	Weight	lbs.	727	727	727	793	793	727 + 727	727 + 727	727 + 727
	Dimensions (H x W x D)	in.			66-11/16 x 48-7/8 x 30-3/16			66-11/16 x 48-7/8 x 30-3/16 +		66-11/16 x 48-7/8 x 30-3/16

¹Varies based on indoor model selected

OPERATION RANGE FOR ALL VRV IV X HEAT RECOVERY OUTDOOR UNITS

Cooling°F DB	-4* - 122
Heating°F WB	-13 - 60

*Application rules apply



22 Ton	24 Ton	26 Ton	28 Ton	30 Ton	32 Ton	34 Ton	36 Ton	38 Ton
REYQ264XBTJA	REYQ288XBTJA	REYQ312XBTJA	REYQ336XBTJA	REYQ360XBTJA	REYQ384XBTJA	REYQ408XBTJA	REYQ432XBTJA	REYQ456XBTJA
REYQ264XBYDA	REYQ288XBYDA	REYQ312XBYDB	REYQ336XBYDA	REYQ360XBYDA	REYQ384XBYDA	REYQ408XBYDA	REYQ432XBYDA	REYQ456XBYDA
1x REYQ120XB 1x REYQ144XB	2x REYQ144XB	1x REYQ144XB 1x REYQ168XB	2x REYQ168XB	3x REYQ120XB	2x REYQ120XB 1x REYQ144XB	1x REYQ120XB 2x REYQ144XB	2x REYQ168XB	2x REYQ144XB 1x REYQ168XB
252,000	274,000	296,000	320,000	342,000	364,000	388,000	410,000	430,000
282,000	294,000	320,000	338,000	376,000	386,000	394,000	405,000	414,000
23 to 122								
-13 to 60								
69	69	69	69	70	71	71	71	71
7989 + 9480	9480 + 9480	9480 + 9480	9480 + 9480	7989 + 7989 + 7989	7989 + 7989 + 9480	7989 + 9480 + 9480	9480 + 9480 + 9480	9480 + 9480 + 9480
0.12 / 0.32								
2				3				
6504 + 5214	4794 + 4794	5286 + 5286	5664 + 5664	6606 + 6606 + 6606	6426 + 6426 + 5070	6162 + 4470 + 4470	4350 + 4350 + 4350	4470 + 4470 + 4470
5-100	7-100	7-100	6-100	4-100	3-100	3-100	5-100	4-100
164 (295 With Field Setting)								
130 (195 With Field Setting)								
100								
541								
620								
3,280								
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
1-3/8	1-3/8	1-3/8	1-3/8	1-5/8	1-5/8	1-5/8	1-5/8	1-5/8
1-1/8	1-1/8	1-1/8	1-1/8	1-3/8	1-3/8	1-3/8	1-3/8	1-3/8
50 - 200 ¹								
45	49	54	58	64				
50 + 70 / 25 + 40	70 + 70 / 40 + 40	70 + 70 / 40 + 40	70 + 70 / 40 + 40	50 + 50 + 50 / 25 + 25 + 25	50 + 50 + 70 / 25 + 25 + 40	50 + 70 + 70 / 25 + 40 + 40	70 + 70 + 70 / 40 + 40 + 40	70 + 70 + 70 / 40 + 40 + 40
43.0 + 58.3 / 21.1 + 27.9	58.3 + 58.3 / 27.9 + 27.9	58.3 + 61.9 / 27.9 + 31.1	61.9 + 61.9 / 31.1 + 31.1	43.0 + 43.0 + 43.0 / 21.1 + 21.1 + 21.1	43.0 + 43.0 + 58.3 / 21.1 + 21.1 + 27.9	43.0 + 58.3 + 58.3 / 21.1 + 27.9 + 27.9	58.3 + 58.3 + 58.3 / 27.9 + 27.9 + 27.9	58.3 + 58.3 + 61.9 / 27.9 + 27.9 + 31.1 /
32.9 + 42.1 / 14.9 + 19.0	43.5 + 43.5 / 19.7 + 19.7	46.5 + 46.5 / 21.0 + 21.0	50.1 + 50.1 / 22.7 + 22.7	32.7 + 32.7 + 32.7 / 14.8 + 14.8 + 14.8	33.8 + 33.8 + 43.7 / 15.3 + 15.3 + 19.8	35.7 + 45.1 + 45.1 / 16.2 + 20.4 + 20.4	45.1 + 45.1 + 45.1 / 20.4 + 20.4 + 20.4	47.0 + 47.0 + 47.0 / 21.3 + 21.3 + 21.3
25.8 + 25.8				25.8 + 25.8 + 25.8				
727 + 793	793 + 793	793 + 793	793 + 793	727 + 727 + 727	727 + 727 + 793	727 + 793 + 793	793 + 793 + 793	793 + 793 + 793
66-11/16 x 48-7/8 x 30-3/16 + 66-11/16 x 48-7/8 x 30-3/16				66-11/16 x 48-7/8 x 30-3/16 + 66-11/16 x 48-7/8 x 30-3/16 + 66-11/16 x 48-7/8 x 30-3/16				

For additional technical information please refer to specific Engineering Data Books.

High-Efficiency All-Electric Heat Pump Hot and Chilled Water Solutions




Daikin's LT hydrobox (HXY48TAVJU) offers an all-electric means of refrigerant to water heat exchange providing an efficient method for hot and cold-water generation for many hydronic solutions including high-efficiency space heating and cooling. The LT hydrobox combines with Daikin's VRV systems for expanded indoor unit flexibility with hydronic integration. Delivering water from 50°F – 113°F without the need for a backup electric heater, for use in underfloor heating and cooling, air handling units, and low-temperature radiators, making it an ideal choice in both new construction and renovation applications.

The stylish and compact wall hung unit with front access and minimal clearance requirements make it ideal for installation in tight spaces and ease of maintenance.

Features and Benefits

- » Direct control over the leaving water temperature for a wide leaving water temperature range down to 50°F in cooling and up to 113°F in heating.
- » Eliminates the need for gas connection or oil tanks to generate hot or cold water
- » Space-saving contemporary wall hung design
- » Seamless integration with VRV IV X systems¹
- » Save time on system design as all water components are fully integrated with direct control over leaving water temperature. Factory installed hydronic accessories include:

Applications:



- Flow switch
- Safety relief valve
- Expansion tank
- Pump
- Strainer
- Auto air vent valve
- Inlet/outlet temp sensors

¹ Refer to the engineering manuals for detailed design conditions.



* Complete warranty details available from your local distributor, manufacturer's representative, www.daikincomfort.com.





SPECIFICATIONS

Model	HXY48TAVJU	
Power Supply	V/ph/Hz	208/230VAC 60 Hz, 1-Phase
Nominal Capacity	Cooling* ¹ Heating* ²	Btu/h (kW) Btu/h (kW)
Pump	Type Nr of Speeds Cooling Nominal ESP Heating Nominal ESP	DC Motor Inverter Controlled ft hd (kPa) ft hd (kPa)
Dimensions (H x W x D)	in. (mm)	35 1/16 x 18 7/8 x 13 1/2 (890 x 480 x 344)
Weight (Dry)	lbs (kg)	97 (44)
Casing	(Color / Material)	White / Precoated Sheet Metal
Sound	Power Level Pressure Level	dBA dBA
Water Flow Rate Range	gpm (l/min)	3.4 - 11.9 (15 - 45)
Pump Control Method	Water Inlet/Outlet Delta T Control	
Delta T Range	°F (°C)	
Outlet Temp. Range	Cooling Heating	°F (°C) °F (°C)
Ambient Temperature Range	Cooling Heating	°F (°C) °F (°C)
Pipe Connections	Liquid Gas Water Side Connection* ³	in. (mm) in. (mm) in. (mm)
Refrigerant Control	Electronic Expansion Valve	
Maximum Overcurrent Protection	A	15
Minimum Circuit Ampacity	A	2.5

NOTE:

*¹ Nominal Cooling Conditions


*² Nominal Heating Conditions

*³ Adaptor Shipped Loose with IDU (BSPP to NPT)

Ambient: 95°F DB, LWT: 64.4°F, Delta T: 9°F, Flow Rate: 9.5 gpm

Ambient: 44.6°F DB / 42.8°F WB, LWT: 95°F, Delta T: 9°F, Flow Rate: 10.6 gpm

Installation Example



VRV IV X, VRV EMERION

Indoor Units 80-97% AFUE
Communicating Gas Furnace



Features

- » **Compatible with VRV IV X and VRV EMERION outdoor units.** Available from 60,000 Btu up to 120,000 Btu
- » **Durable heat exchanger** – Unique tubular stainless-steel construction formed using wrinkle-bend technology results in an extremely durable heat exchanger. Paired with a stainless-steel secondary heat exchanger, this combination provides for reliability, durability and efficiency.
- » **Modulating gas valve** – Operates between 35% - 100% capacity, providing precise efficiency and the ultimate in comfort.
- » **Continuous air circulation** – Provides filtration and keeps air moving throughout your home to help maintain comfort.
- » **Self-diagnostic control board** – continuously monitors the system for consistent, reliable operation.
- » **Quiet, variable-speed induced draft blower** – provides precise control and enhanced energy-efficient performance as compared to single-speed blowers.





COMFORTABLE WARRANTY* PROTECTION

* Complete commercial warranty details available from your local Daikin manufacturer's representative or distributor or online at www.daikincomfort.com.



CXTQ All Aluminum Coil

- » Available in 2, 3, 4, and 5-Ton capacities
- » Engineered for VRV IV X outdoor unit
- » Factory installed electronic expansion valve with PID control loop for precision capacity control
- » Seamless integration to full suite of Daikin controls using onboard control board
- » Air cleaner and humidifier integration capable¹
- » UV and rust resistant, 5VA rated thermoplastic drain pan with integrated secondary drain
- » Foil-faced insulation covers internal casing to reduce cabinet condensation
- » Split seam front for easy installation and service access
- » Light weight all aluminum evaporator coil
- » Ships factory standard up flow with easy field conversion to downflow¹
- » Backed by a 10-Year Parts Limited Warranty*

¹Rules apply, refer to installation manual for details.

INDOOR – CXTQ

Model Name		CXTQ24TASBLU	CXTQ36TASBLU	CXTQ48TASBLU	CXTQ60TASBLU
Power Supply					
Nominal Tons		2	3	4	5
*1,*3 Cooling Capacity	Btu/h (kW)	24,000 (7.0)	36,000 (10.6)	48,000 (14.1)	60,000 (17.6)
*2,*3 Heating Capacity	Btu/h (kW)	27,000 (7.9)	40,000 (11.7)	54,000 (15.8)	66,000 (19.4)
Casing / Color		Daikin Slate Gray			
Dimensions (H x W x D)	in. (mm)	22-1/16 x 17-23/32 x 24-7/32 (560 x 450 x 615)	22-1/16 x 17-23/32 x 24-7/32 (560 x 450 x 615)	30-1/16 x 21-7/32 x 24-7/32 (764 x 539 x 615)	30-1/16 x 24-23/32 x 24-7/32 (764 x 628 x 615)
Coil	Type	Cased Upflow/Downflow A-coil			
	*4 Air pressure drop	in w.g.	0.089"	0.240"	0.310"
Weight		lbs (kg)	46 (20.9)	52 (23.6)	72 (32.7)
Pipe Connections	Liquid	in. (mm)	3/8" (9.5)	3/8" (9.5)	3/8" (9.5)
	Gas	in. (mm)	5/8" (15.8)	5/8" (15.8)	5/8" (15.8)
	Drain	in. (mm)	3/4" (19.1)	3/4" (19.1)	3/4" (19.1)
Safety devices					
Refrigerant Control					
Connectible Outdoor Unit					
Fuse					
Electronic Expansion Valve					
VRV IV X					

Daikin VRV AURORA

Heat Recovery | 208-230V & 460V



Daikin VRV AURORA series heat recovery systems introduce a new benchmark for variable refrigerant flow system technology by integrating advanced technologies to provide comfort, control, energy efficiency and reliability. The Daikin VRV AURORA series heat recovery systems set a new industry standard for heating and cooling solutions by delivering high heat capacities at low ambient applications.

Features and Benefits

- » Variable refrigerant flow system Industry's first air-cooled system that delivers heating down to -22°F (-30°C) as standard
- » Daikin's inverter based vapor injection compressor is designed to deliver heating capacity of up to 100% of nominal at 0°F (-18°C), up to 85% of nominal at -13°F (-25°C) and up to 60% of nominal at -22°F (-30°C)
- » Optimized efficiencies delivered by dedicated all-inverter compressors and inverter fan motors
- » Refrigerant-cooled efficient and stable inverter board operation, independent of ambient conditions
- » Hot gas base pan circuit allows installation without an additional drain pan heater
- » Designed to provide continuous heating during defrost and oil return**
- » Engineered with Daikin vapor injection compressor for optimized part load efficiencies
- » Added peace of mind with Auto Changeover ability to back up (auxiliary) heat

VRV

Applications:



- » Long pipe lengths up to 1640 ft total and ability to connect up to 41*** indoor units with up to 100 ft vertical separation between indoor units provides design and installation flexibility
- » Corrosion resistant, 1000 hours salt spray tested Daikin PE blue fin heat exchanger
- » Ships factory standard with coil guards
- » Outstanding 10-Year Parts Warranty* as standard.

* Complete commercial warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com

** Multi modules only for continuous heating during defrost

***Varies by model






VRV AURORA HEAT RECOVERY CERTIFIED DATA - HEAT RECOVERY, 208-230V/60HZ/3PH AND 460V/60HZ/3PH

Product#	Capacity (Tons)	IEER Non-Ducted	IEER Ducted	IEER Mixed	SCHE Non-Ducted	SCHE Ducted	SCHE Mixed	COP @ 47°F Non-Ducted	COP @ 47°F Ducted	COP @ 47°F Mixed	COP @ 17°F Non-Ducted	COP @ 17°F Ducted	COP @ 17°F Mixed	EER Non-Ducted	EER Ducted	EER Mixed
RELQ72T	6	24.00	20.80	22.40	26.10	22.60	24.30	4.30	3.68	3.99	2.50	2.30	2.40	15.80	13.70	14.70
RELQ96T	8	24.80	19.10	21.90	25.70	19.70	22.70	4.23	3.42	3.83	2.50	2.25	2.37	15.30	12.50	13.90
RELQ120T	10	23.40	19.60	21.50	26.70	21.10	24.00	3.98	3.51	3.74	2.25	2.25	2.25	13.70	12.40	13.00
RELQ144T	12	22.50	18.60	20.50	25.50	23.80	24.60	3.81	3.55	3.68	2.20	2.20	2.20	12.90	12.60	12.70
RELQ192T	16	22.10	19.00	20.50	25.50	21.20	23.30	3.85	3.57	3.71	2.20	2.15	2.17	12.50	12.70	12.60
RELQ240T	20	21.10	18.60	19.80	24.90	20.80	22.80	3.68	3.49	3.59	2.20	2.13	2.16	12.30	11.70	12.00


Certified efficiency data in accordance with ANSI/AHRI Standard 1230 2014, "Performance Rating of Variable Refrigerant Flow Multi-Split Air Conditioning and Heat Pump Equipment" for the VRV series. The VRV AURORA series has been designed and optimized to meet or exceed the latest minimum efficiency requirements in 10 C.F.R. Part 431 as determined by the U.S. Department of Energy (DOE) and baseline efficiencies as defined by ASHRAE 90.1 2016. Systems under 65MBH are currently certified to AHRI 210/240. IEER ratings are as defined in ASHRAE 90.1 2016.


DETAILED OPERATION RANGES FOR VRV RELQ_T HEAT RECOVERY OUTDOOR UNITS



TECHNICAL COOLING FEATURE FOR VRV RELQ_T HEAT RECOVERY OUTDOOR UNITS

Technical Cooling - Cooling operation extended from 23°F ambient air temperature down to -4°. The Technical Cooling feature is engaged by field settings on the outdoor unit and on branch selector boxes. It requires addition of wind covers to the unit and allows operation down to -4°F DB ambient temperature in cooling mode. See the Engineering Data book for complete application rules and contact your local Daikin representative for wind cover specification requirements.





- » Compressor technology with new spiral design and injection valves for precise refrigerant control
- » Strong and efficient motors for optimized compressor performance and part load efficiencies
- » Patented back pressure control mechanism to minimize scroll pressure losses

TECHNICAL DATA FOR VRV AURORA RELQ_TATJA/TAYDA HEAT RECOVERY OUTDOOR UNITS

Model	208-230V/3Ph/60Hz	460V/3Ph/60Hz	Combination	6 Ton	8 Ton	10 Ton
				RELQ72TBTJA	RELQ96TBTJA	RELQ120TBTJA
				RELQ72TAYDA	RELQ96TAYDA	RELQ120TAYDA
Performance	Rated Cooling Capacity	BTU/h	69,000	92,000	114,000	
	Rated Heating Capacity	BTU/h	77,000	103,000	129,000	
	Operation Range Cooling	°F (°C) DB		23° to 122		
	Operation Range Heating	°F (°C) WB		-22 to 60		
	Sound Pressure	dB(A)	60	61	64	
	Airflow (Cooling)	CFM	6956	7989	8806	
	Airflow (Heating)	CFM	7283	7283	7283	
	Fan ESP, Standard/Max	in. Wg		0.12 / 0.32		
Compressor	Compressors, all inverter	Qty		1		
	Revolutions per minute	RPM	3738	3342	4350	
	Capacity Control Range	%	11-100	10-100	9-100	
Refrigerant Piping, Layout	Maximum Vertical Pipe Length Above Unit	ft.		164 (295 With Field Setting)		
	Maximum Vertical Pipe Length Below Unit	ft.		131 (195 With Field Setting)		
	Maximum Vertical Pipe Length Between IDU	ft.		100		
	Maximum Actual Pipe Length	ft.		541		
	Maximum Equivalent Pipe Length	ft.		620		
	Maximum Total Pipe Length	ft.		1,640		
Refrigerant Piping, Connections	Liquid Pipe (Main Line)	in.	3/8	3/8	1/2	
	Suction Gas Pipe (Main Line)	in.	3/4	7/8	1-1/8	
	Discharge Gas Pipe (Main Line)	in.	5/8	3/4	3/4	
Connection Ratio	Standard Connectable Indoor Unit Ratio	%		70 - 200 ²		
	Maximum Number of Indoor Units	Qty	12	16	20	
Electrical	Maximum Overcurrent Protection, MOP (RELQ_TATJA / RELQ_TAYDA)	A	70 / 35	80 / 45	90 / 50	
	Minimum Circuit Amps, MCA (RELQ_TATJA / RELQ_TAYDA)	A	60.8 / 28.1	76.5 / 39.8	83.4 / 43.4	
	Compressor Rated Load Amps, RLA (RELQ_TATJA / RELQ_TAYDA)	A	20.7 / 9.4	36.8 / 16.6	39.3 / 17.8	
Unit	Factory Refrigerant Charge	lbs.		25.8		
	Weight	lbs.	727	793	793	
	Dimensions (H x W x D)	in.		66-11/16 X 48-7/8 X 30-3/16		

¹ Cooling operation can be extended down to -4°F with application rules and conditions

² Varies based on indoor model selected



			12 Ton	16 Ton	20 Ton
Model	208-230V/3Ph/60Hz		RELQ144TATJA	RELQ192TATJA	RELQ240TATJA
	460V/3Ph/60Hz		RELQ144TAYDA	RELQ192TAYDA	RELQ240TAYDA
	Combination		2 x RELQ72T	2 x RELQ96T	2 x RELQ120T
Performance	Rated Cooling Capacity	BTU/h	138,000	184,000	228,000
	Rated Heating Capacity	BTU/h	154,000	206,000	256,000
	Operation Range Cooling	°F (°C) DB	23 ¹ to 122		
	Operation Range Heating	°F (°C) WB	-22 to 60		
	Sound Pressure	dB(A)	63	64	67
	Airflow (Cooling)	CFM	7283 + 7283	7989 + 7989	8806 + 8806
	Airflow (Heating)	CFM	6956 + 6956	7283 + 7283	7283 + 7283
	Fan ESP, Standard/Max	in. Wg	0.12 / 0.32		
Compressor	Compressors, all inverter	Qty	2		
	Revolutions per minute	RPM	3786 + 3786	3294 + 3294	4230 + 4230
	Capacity Control Range	%	6~100	5~100	4~100
Refrigerant Piping, Layout	Maximum Vertical Pipe Length Above Unit	ft.	164 (295 With Field Setting)		
	Maximum Vertical Pipe Length Below Unit	ft.	131 (195 With Field Setting)		
	Maximum Vertical Pipe Length Between IDU	ft.	100		
	Maximum Actual Pipe Length	ft.	541		
	Maximum Equivalent Pipe Length	ft.	620		
	Maximum Total Pipe Length	ft.	1,640		
Refrigerant Piping, Connections	Liquid Pipe (Main Line)	in.	1/2	5/8	5/8
	Suction Gas Pipe (Main Line)	in.	1-1/8	1-1/8	1-3/8
	Discharge Gas Pipe (Main Line)	in.	7/8	1-1/8	1-1/8
Connection Ratio	Standard Connectable Indoor Unit Ratio	%	70 - 200 ²		
	Maximum Number of Indoor Units	Qty	25	33	41
Electrical	Maximum Overcurrent Protection, MOP (RELQ_TATJA / RELQ_TAYDA)	A	70 + 70 / 35 + 35	80 + 80 / 45 + 45	90 + 90 / 50 + 50
	Minimum Circuit Amps, MCA (RELQ_TATJA / RELQ_TAYDA)	A	60.8 + 60.8 / 28.1 + 28.1	76.5 + 76.5 / 39.8 + 39.8	83.4 + 83.4 / 43.4 + 43.4
	Compressor Rated Load Amps, RLA (RELQ_TATJA / RELQ_TAYDA)	A	21.6 + 21.6 / 9.8 + 9.8	38.1 + 38.1 / 17.3 + 17.3	40.4 + 40.4 / 18.3 + 18.3
Unit	Factory Refrigerant Charge	lbs.	25.8 + 25.8		
	Weight	lbs.	2 x 727	2 x 793	2 x 793
	Dimensions (H x W x D)	in.	66-11/16 X 48-7/8 X 30-3/16 + 66-11/16 X 48-7/8 X 30-3/16		

Daikin VRV AURORA

Heat Pump | 208-230V & 460V



Daikin VRV AURORA series systems introduce a new benchmark for variable refrigerant flow system technology by integrating advanced technologies to provide comfort, control, energy efficiency and reliability. The Daikin VRV AURORA series systems set a new industry standard for heating and cooling solutions by delivering high heat capacities at low ambient applications.

Features and Benefits

- » Variable refrigerant flow system Industry's first air-cooled system that delivers heating capacities down to -22°F (-30°C) as standard
- » Daikin's inverter based vapor injection compressor is designed to deliver heating capacity of up to 100% of nominal at 0°F (-18°C), up to 85% of nominal at -13°F (-25°C) and up to 60% of nominal at -22°F (-30°C)
- » Year round comfort and energy savings with Variable Refrigerant Temperature technology (VRT)
- » Refrigerant-cooled efficient and stable inverter board operation, independent of ambient conditions
- » Hot gas base pan circuit allows installation without an additional drain pan heater
- » Added peace of mind with Auto Changeover ability to back up (auxiliary) heat

VRV

Applications:



- » Long pipe lengths up to 1640 ft. total and ability to connect up to 41** indoor units with up to 100 ft. vertical separation between indoor units provides design and installation flexibility
- » Corrosion resistant, 1000 hours salt spray tested Daikin PE blue fin heat exchanger
- » Ships factory standard with coil guards
- » Outstanding 10-Year Parts Warranty* as standard.

* Complete commercial warranty details available from your local distributor or manufacturer's representative or at www.daikincomfort.com

** Varies by model






VRV AURORA HEAT PUMP CERTIFIED DATA - HEAT PUMP, 208-230V/60HZ/3PH, 460V/60HZ/3PH

Product#	Capacity [Tons]	IEER Non-Ducted	IEER Ducted	IEER Mixed	COP @ 47°F Non-Ducted	COP @ 47°F Ducted	COP @ 47°F Mixed	COP @ 17°F Non-Ducted	COP @ 17°F Ducted	COP @ 17°F Mixed	EER Non-Ducted	EER Ducted	EER Mixed
RXLQ72T	6	24.00	20.40	22.20	4.37	3.73	4.05	2.52	2.31	2.42	15.10	13.00	14.05
RXLQ96T	8	24.70	18.90	21.80	4.29	3.49	3.89	2.51	2.26	2.39	14.90	12.30	13.60
RXLQ120T	10	23.30	19.40	21.35	4.05	3.56	3.81	2.27	2.26	2.27	13.50	12.20	12.85
RXLQ144T	12	22.40	18.20	20.30	3.86	3.56	3.71	2.21	2.21	2.21	12.70	12.40	12.55
RXLQ192T	16	22.00	18.80	20.40	3.90	3.61	3.76	2.22	2.16	2.19	12.30	12.50	12.40
RXLQ240T	20	21.00	18.60	19.80	3.77	3.53	3.65	2.22	2.13	2.18	12.10	11.50	11.80


Certified efficiency data in accordance with ANSI/AHRI Standard 1230 2014, "Performance Rating of Variable Refrigerant Flow Multi-Split Air Conditioning and Heat Pump Equipment" for the VRV series. The VRV AURORA series has been designed and optimized to meet or exceed the latest minimum efficiency requirements in 10 C.F.R. Part 431 as determined by the U.S. Department of Energy (DOE) and baseline efficiencies as defined by ASHRAE 90.1 2016. Systems under 65MBH are currently certified to AHRI 210/240. IEER ratings are as defined in ASHRAE 90.1 2016.

DETAILED OPERATION RANGES FOR VRV RXLO_T HEAT PUMP OUTDOOR UNITS



Daikin VRV AURORA

Heat Pump | 208-230V & 460V (cont.)



- » Compressor technology with new spiral design and injection valves for precise refrigerant control
- » Strong and efficient motors for optimized compressor performance and part load efficiencies
- » Patented back pressure control mechanism to minimize scroll pressure losses

TECHNICAL DATA FOR VRV AURORA RXLQ_T

Model	208-230V/3Ph/60Hz	6 Ton		8 Ton		10 Ton	
		RXLQ72TBTJA		RXLQ96TBTJA		RXLQ120TBTJA	
		RXLQ72TBYDA		RXLQ96TBYDA		RXLQ120TBYDA	
Performance	Rated Cooling Capacity	BTU/h	69,000	92,000	114,000		
	Rated Heating Capacity	BTU/h	77,000	103,000	129,000		
	Operation Range Cooling	°F (°C) DB		23 to 122			
	Operation Range Heating	°F (°C) WB		-22 to 60			
	Sound Pressure	dB(A)	60	61	64		
	Airflow	CFM	7283	7989	8806		
	Fan ESP, Standard/Max	in. Wg		0.12 / 0.32			
Compressor	Compressors, all inverter	Qty		1			
	Revolutions per minute	RPM	3738	3294	4350		
	Capacity Control Range	%	11~100	13~100	12~100		
Refrigerant Piping, Layout	Maximum Vertical Pipe Length Above Unit	ft.		164 (295 With Field Setting)			
	Maximum Vertical Pipe Length Below Unit	ft.		131 (195 With Field Setting)			
	Maximum Vertical Pipe Length Between IDU	ft.		100			
	Maximum Actual Pipe Length	ft.		541			
	Maximum Equivalent Pipe Length	ft.		620			
Refrigerant Piping, Connections	Maximum Total Pipe Length	ft.		1,640			
	Liquid Pipe (Main Line)	in.	3/8	3/8	1/2		
	Suction Gas Pipe (Main Line)	in.	3/4	7/8	1-1/8		
Connection Ratio	Standard Connectable Indoor Unit Ratio	%		70 - 200 ¹			
	Maximum Number of Indoor Units	Qty	12	16	20		
Electrical	Maximum Overcurrent Protection, MOP (RXLQ_TATJA / RXLQ_TAYDA)	A	70 / 35	80 / 45	90 / 50		
	Minimum Circuit Amps, MCA (RXLQ_TATJA / RXLQ_TAYDA)	A	60.8 / 28.1	76.5 / 39.8	83.4 / 43.4		
	Compressor Rated Load Amps, RLA (RXLQ_TATJA / RXLQ_TAYDA)	A	23.9 / 10.4	42.2 / 18.3	41.4 / 18.0		
Unit	Factory Refrigerant Charge	lbs.		25.8			
	Weight	lbs.	727	793	793		
	Dimensions (H x W x D)	in.		66-11/16 X 48-7/8 X 30-3/16			

¹Varies based on indoor model selected



			12 Ton	16 Ton	20 Ton
Model	208-230V/3Ph/60Hz		RXLQ144TATJA	RXLQ192TATJA	RXLQ240TATJA
	460V/3Ph/60Hz		RXLQ144TAYDA	RXLQ192TAYDA	RXLQ240TAYDA
	Combination		2xRXLQ72T	2xRXLQ96T	2xRXLQ120T
Performance	Rated Cooling Capacity	BTU/h	138,000	184,000	228,000
	Rated Heating Capacity	BTU/h	154,000	206,000	256,000
	Operation Range Cooling	°F (°C) DB	23 to 122		
	Operation Range Heating	°F (°C) WB	-22 to 60		
	Sound Pressure	dB(A)	63	64	67
	Airflow (Cooling)	CFM	7283 + 7283	7989 + 7989	8806 + 8806
	Fan ESP, Standard/Max	in. Wg		0.12 / 0.32	
	Compressors, all inverter	Qty		2	
Compressor	Revolutions per minute	RPM	3804 + 3804	3342 + 3342	4230 + 4230
	Capacity Control Range	%	6-100	6-100	6-100
	Maximum Vertical Pipe Length Above Unit	ft.	164 (295 With Field Setting)		
Refrigerant Piping, Layout	Maximum Vertical Pipe Length Below Unit	ft.	131 (195 With Field Setting)		
	Maximum Vertical Pipe Length Between IDU	ft.	100		
	Maximum Actual Pipe Length	ft.	541		
	Maximum Equivalent Pipe Length	ft.	620		
	Maximum Total Pipe Length	ft.	1,640		
Refrigerant Piping, Connections	Liquid Pipe (Main Line)	in.	1/2	5/8	5/8
	Suction Gas Pipe (Main Line)	in.	1-1/8	1-1/8	1-3/8
Connection Ratio	Standard Connectable Indoor Unit Ratio	%		70 - 200 ¹	
	Maximum Number of Indoor Units	Qty	25	33	41
Electrical	Maximum Overcurrent Protection, MOP (RXLQ_TATJA / RXLQ_TAYDA)	A	70 + 70 / 35 + 35	80 + 80 / 45 + 45	90 + 90 / 50 + 50
	Minimum Circuit Amps, MCA (RXLQ_TATJA / RXLQ_TAYDA)	A	60.8 + 60.8 / 28.1 + 28.1	76.5 + 76.5 / 39.8 + 39.8	83.4 + 83.4 / 43.4 + 43.4
	Compressor Rated Load Amps, RLA (RXLQ_TATJA / RXLQ_TAYDA)	A	23.9 + 23.9 / 10.4 + 10.4	40.8 + 40.8 / 17.7 + 17.7	41.7 + 41.7 / 18.2 + 18.2
Unit	Factory Refrigerant Charge	lbs.		25.8 + 25.8	
	Weight	lbs.	2 x 727	2 x 793	2 x 793
	Dimensions (H x W x D)	in.	66-11/16 X 48-7/8 X 30-3/16 + 66-11/16 X 48-7/8 X 30-3/16		

VRV T-Series Water-Cooled

Heat Pump | Heat Recovery
208-230V | 460V



VRV T-Series Water-Cooled systems are equivalent to 4-pipe chilled water systems, but also offer a viable alternative to Water Source Heat Pump solutions. Each connected indoor unit can provide heating and cooling independently to suit zone requirements making these systems suitable for both open plan, or cellar applications with different operation requirements.

Features and Benefits

- » Flexible System design with increased diversity up to 150%¹ compared to previous VRV water-cooled generation
- » Triple-stack capable to deliver up to 36 tons in 11.5 ft ceiling height
- » Flexible and easy installation with field selectable top or front refrigerant connections
- » Design flexibility with long piping lengths up to 980 ft. total (540 ft. max. linear liquid piping length) and up to 100 ft. vertical separation between indoor units
- » Engineered with heat rejection cancellation technology² to minimize mechanical room conditioning requirements
- » Year round comfort and energy efficiency by combining VRV and VRT technologies
- » Wide water temperature operation range - Can be applied to both geothermal and boiler/tower applications as standard with condenser water inlet temperature as low as 14°F in heating and 23°F in cooling is possible.
- » 2-9V variable water flow control logic² as standard to increase waterside system operational efficiencies
- » Refrigerant cooled inverter technology to deliver consistent and reliable PCB operations
- » Easy commissioning with ability to program settings off site using new configurator tool
- » 3-digit 7-segment digital display on the unit for improved and faster configuration, commissioning, and troubleshooting
- » Engineered for easy service with drop-down switch box to access key components

¹ Model specific, check product specification for details

² Refer to installation manual for field settings and other requirements to activate this feature




Water side

Connects to cooling tower and/or boiler combination or set up as geothermal.

Refrigerant side

Connects to Daikin's line-up of VRV indoor units

The condensers are smaller and can be stacked, reducing the installation space and increasing the customers' usable square footage.



This is a simple system that allows manifolding together up to three condensers to form one system of up to 36 tons. The condensers are designed for internal mounting only.

* 6-ton model (RWEYQ72PC) is PC series. T and PC series models cannot be combined to form multi-module systems.


VRV Water-Cooled System series design is based on a modular design concept. It is composed of unified condensing units that require simply connecting a two-pipe refrigerant network for heat pump applications or a three-pipe refrigerant network for heat recovery applications. Water-cooled condensers are available in 6*, 8, 10 and 12 tons.

VRV T-SERIES WATER-COOLED CERTIFIED DATA, 208-230V/60HZ/3PH AND 460V/60HZ/3PH

Function	System Name	Tonnage	IEER Non-Ducted	IEER Ducted	IEER Mixed	SCHE Non-Ducted (Heat Recovery only)	SCHE Ducted (Heat Recovery only)	SCHE Mixed (Heat Recovery only)	EER Non-Ducted	EER Ducted	EER Mixed	COP @ 68°F Non-Ducted	COP @ 68°F Ducted	COP @ 68°F Mixed
Heat Pump	RWEQ72T	6 Tons	24.1	22.3	23.2	N/A	N/A	N/A	14.0	14.0	14.0	4.89	4.78	4.84
	RWEQ96T	8 Tons	30.8	25.4	28.1	N/A	N/A	N/A	19.6	15.4	17.5	6.27	5.8	6.035
	RWEQ120T	10 Tons	29.4	23.5	26.45	N/A	N/A	N/A	16	13.6	14.8	6.1	5.55	5.83
	RWEQ144T	12 Tons	24.3	19.8	22.05	N/A	N/A	N/A	15.4	12.6	14.0	6.01	5.33	5.67
	RWEQ192T	16 Tons	26.8	24.7	25.75	N/A	N/A	N/A	16.5	14.6	15.55	5.82	5.82	5.82
	RWEQ216T	18 Tons	26.3	23.8	25.05	N/A	N/A	N/A	15.0	13.8	14.4	5.68	5.62	5.65
	RWEQ240T	20 Tons	25.7	22.7	24.2	N/A	N/A	N/A	14.0	12.8	13.4	5.52	5.38	5.45
	RWEQ264T	22 Tons	23.5	2.00	21.75	N/A	N/A	N/A	13.5	12.1	12.8	5.34	4.96	5.15
	RWEQ288T	24 Tons	20.9	18.8	19.85	N/A	N/A	N/A	12.6	11.3	11.95	5.3	4.81	5.06
	RWEQ312T	26 Tons	21.9	21.8	21.85	N/A	N/A	N/A	13.7	12.7	13.2	5.5	4.86	5.18
	RWEQ336T	28 Tons	21.5	21.4	21.45	N/A	N/A	N/A	13.5	12.3	12.9	5.42	4.73	5.08
	RWEQ360T	30 Tons	21.2	20.2	20.7	N/A	N/A	N/A	12.4	11.7	12.05	5.3	4.7	5.0
	RWEQ384T	32 Tons	19.5	17.9	18.7	N/A	N/A	N/A	12	11	11.5	4.53	4.12	4.33
	RWEQ408T	34 Tons	18.2	17.2	17.7	N/A	N/A	N/A	11.1	10.7	10.9	4.35	4.03	4.19
	RWEQ432T	36 Tons	17.0	16.6	16.8	N/A	N/A	N/A	10.5	10.3	10.4	4.19	3.92	4.06
Heat Recovery	RWEQ72T	6 Tons	24.1	22.3	23.2	17.8	19.2	18.5	14.0	14.0	14.0	4.89	4.78	4.84
	RWEQ96T	8 Tons	30.8	25.4	28.1	25.7	21.3	23.5	19.6	15.4	17.5	6.27	5.8	6.035
	RWEQ120T	10 Tons	29.4	23.5	26.45	26.3	22.5	24.4	16	13.6	14.8	6.1	5.55	5.83
	RWEQ144T	12 Tons	24.3	19.8	22.05	26.5	22.7	24.6	15.4	12.6	14	6.01	5.33	5.67
	RWEQ192T	16 Tons	26.8	24.7	25.75	26.0	22.9	24.45	16.5	14.6	15.55	5.82	5.82	5.82
	RWEQ216T	18 Tons	26.3	23.8	25.05	25.5	22.1	23.8	15.0	13.8	14.4	5.68	5.62	5.65
	RWEQ240T	20 Tons	25.7	22.7	24.2	25.4	21.9	23.65	14.0	12.8	13.4	5.52	5.38	5.45
	RWEQ264T	22 Tons	23.5	2.00	21.75	25.2	19.2	22.2	13.5	12.1	12.8	5.34	4.96	5.15
	RWEQ288T	24 Tons	20.9	18.8	19.85	23.5	20.0	21.75	12.6	11.3	11.95	5.3	4.81	5.06
	RWEQ312T	26 Tons	21.9	21.8	21.85	24.5	20.7	22.6	13.7	12.7	13.2	5.5	4.86	5.18
	RWEQ336T	28 Tons	21.5	21.4	21.45	23.5	20.0	21.75	13.5	12.3	12.9	5.42	4.73	5.08
	RWEQ360T	30 Tons	21.2	20.2	20.7	23.2	19.1	21.15	12.4	11.7	12.05	5.3	4.7	5.0
	RWEQ384T	32 Tons	19.5	17.9	18.7	22.0	19.1	20.55	12.0	11.0	11.5	4.53	4.12	4.33
	RWEQ408T	34 Tons	18.2	17.2	17.7	21.2	18.5	19.85	11.1	10.7	10.9	4.35	4.03	4.19
	RWEQ432T	36 Tons	17.0	16.6	16.8	20.5	17.7	19.1	10.5	10.3	10.4	4.19	3.92	4.055

Certified efficiency data in accordance with ANSI/AHRI Standard 1230 2014, "Performance Rating of Variable Refrigerant Flow Multi-Split Air Conditioning and Heat Pump Equipment" for the VRV T-Series Water-Cooled. The VRV T-Series Water-Cooled has been designed and optimized to meet or exceed the latest minimum efficiency requirements in 10 C.F.R. Part 431 as determined by the U.S. Department of Energy (DOE) and baseline efficiencies as defined by ASHRAE 90.1 2016. Systems under 65MBH are currently certified to AHRI 210/240. IEER ratings are as defined in ASHRAE 90.1 2016.

DETAILED STANDARD OPERATION RANGES FOR VRV T-SERIES WATER-COOLED CONDENSING UNITS



VRV T-Series Water-Cooled

Heat Pump or Heat Recovery
208-230V



A modular, energy-efficient and reliable alternative to centralized equipment

Features and Benefits

- » Flexible System design with increased diversity up to 150%¹ compared to previous VRV water-cooled generation
- » Small condensers can be triple stacked for reduced installation space and increased usable square footage
- » Larger (than previous models) single-system capacity and modular concept ensures wider application range for accommodating floor-by-floor loads of commercial buildings
- » Year round comfort and energy efficiency by combining VRV and VRT technologies

- » Can be applied to both geothermal and boiler/tower applications as standard with condenser water inlet temperature as low as 14°F in heating and 23°F in cooling is possible
- » 2-9V variable water flow control logic² as standard to increase waterside system operational efficiencies
- » Refrigerant cooled inverter technology to deliver consistent and reliable PCB operations
- » Engineered for easy service with drop-down switch box to access key components

¹ Model specific, check product specification for details

² Refer to installation manual for field settings and other requirements to activate this feature

VRV T-SERIES UNIFIED HEAT PUMP AND HEAT RECOVERY 208-230V & 460V

		6 Ton	8 Ton	10 Ton	12 Ton	14 Ton	16 Ton	18 Ton	20 Ton
Model	208-230V/3Ph/60Hz	RWEQ72TBTJA	RWEQ96TBTJA	RWEQ120TBTJA	RWEQ144TBTJA	RWEQ168TBTJA	RWEQ192TBTJA	RWEQ216TBTJA	RWEQ240TBTJA
	460V/3Ph/60Hz	RWEQ72TBYDA	RWEQ96TBYDA	RWEQ120TBYDA	RWEQ144TBYDA	RWEQ168TBYDA	RWEQ192TBYDA	RWEQ216TBYDA	RWEQ240TBYDA
	Combination					RWEQ72T RWEQ96T	2 x RWEQ96T	RWEQ96T RWEQ120T	2 x RWEQ120T
Performance	Rated Cooling Capacity ¹	BTU/h	69,000	92,000	114,000	138,000	156,000	184,000	206,000
	Rated Heating Capacity ²	BTU/h	69,000	92,000	114,000	138,000	156,000	184,000	206,000
	Sound Pressure Level @ 3 ft.	dB(A)	50	54	55	60.5		57	57.5
Refrigerant Piping	System Configuration: Heat Pump: HP, Heat Recovery: HR		HP	HR	HP	HP	HR	HP - HR	HP
	Liquid Pipe (Main Line)	in.	3/8	3/8	3/8	3/8	1/2	1/2	5/8 - 5/8
	Suction Gas Pipe (Main Line)	in.	3/4	5/8	7/8	3/4	1-1/8	7/8	1-1/8 - 1-1/8
Connection Ratio	Discharge Gas Pipe (Main Line)	in.	N/A	3/4	N/A	7/8	N/A	1-1/8	7/8 - 7/8
	Standard Connectable Indoor Unit Ratio ³	%	50 - 130				50 - 150		
	Maximum Number of Indoor Units	Qty.	12	16	20	25	1-1/4	33	37
Water Side (Standard)	BPHE Inlet Pipe (Female Thread)	in.	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	2 x 1-1/4	2 x 1-1/4
	BPHE Outlet Pipe (Female Thread)	in.	1-1/4	1-1/4	1-1/4	1-1/4	3/8	2 x 1-1/4	2 x 1-1/4
	Drain Pipe (Female Thread)	in.	1/2	3/8	3/8	3/8	60.5	2 x 3/8	2 x 3/8
Water Side (Geothermal)	Maximum System Water Pressure (BPHE)	psi	285				464		
	Standard Inlet Water Temperature Range Cooling	°F					50 - 113		
	Standard Inlet Water Temperature Range Heating	°F					50 - 113		
Unit	Recommended Inlet Water Flow Rate per Module (minimum)	gpm					15.9 - 39.6 (13.2)		
	Inlet Water Temperature Range Cooling ⁴	°F	27 - 113				23 - 113		
	Inlet Water Temperature Range Heating ⁴	°F					14 - 95		
Electrical (208-230V)	Water Flow Rate ⁵	gpm					21.2 - 39.6		
	Weight (230V/460V)	lbs.	434.3 / 440.9	434.3 / 440.9	438.7 / 445.3	438.7 / 445.3		2 X 440.9 / 2 X 440.9	438.7 + 434.3 / 445.3 + 440.9
	Dimensions (H x W x D)	in.	38-9/16 x 30-1/8 x 22-1/16		38-9/16 x 30-1/8 x 22-1/16			38-9/16 x (30-1/8 x 2) x 22-1/16	
Electrical (460V)	Maximum Overcurrent Protection (MOP)	V	40	40	50	60		40 + 40	40 + 50
	Minimum Circuit Amps (MCA)	A	37.9	38.3	45.2	52.6		38.3 + 38.3	38.3 + 45.2
Compressor	Maximum Overcurrent Protection (MOP)	A	20	20	25	25		20 + 20	25 + 25
	Minimum Circuit Amps (MCA)	A	17.2	17.3	20.4	23.8		17.3 + 17.3	17.3 + 20.4
Compressor	Compressor Type						Inverter		
	Compressor Capacity Control	%	23 - 100	16 - 100	14 - 100	11 - 100		8 - 100	8 - 100

¹ Indoor temp.: 80°FDB, 67°FWB/inlet water temp.: 85°F/ Equivalent piping length : 25 ft., level difference : 0 ft.

² Indoor temp.: 70°FDB, 60°FWB/inlet water temp.: 70°F / Equivalent piping length: 25 ft., level difference : 0 ft.

³ Varies based on indoor and condensing unit model selected; refer to Engineering Manual for details.



RWEQ_TATJA/TAYDA

22 Ton		24 Ton		26 Ton		28 Ton		30 Ton		32 Ton		34 Ton		36 Ton									
RWEQ264TBTJA	RWEQ288TBTJA*	RWEQ312TBTJA*	RWEQ336TBTJA*	RWEQ360TBTJA*	RWEQ384TBTJA*	RWEQ408TBTJA*	RWEQ432TBTJA*	RWEQ264TBYDA	RWEQ288TBYDA*	RWEQ312TBYDA*	RWEQ336TBYDA*	RWEQ360TBYDA*	RWEQ384TBYDA*	RWEQ408TBYDA*	RWEQ432TBYDA*								
RWEQ120T RWEQ144T	2x RWEQ144TB	2x RWEQ96TB RWEQ120TB	RWEQ96TB 2x RWEQ120TB	3x RWEQ120TB	2x RWEQ120TB RWEQ144TB	RWEQ120TB 2x RWEQ144TB	3x RWEQ144TB	252,000	274,000	296,000	320,000	342,000	366,000	388,000	402,000								
252,000	274,000	298,000	320,000	342,000	366,000	388,000	402,000	61.5	63.5	59	59.5	60	62	64	65								
HP	HR	HP	HR	HP	HR	HP	HR	HP	HR	HP	HR	HP	HR	HP	HR								
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4								
1-3/8	1-1/8	1-3/8	1-1/8	1-3/8	1-1/8	1-3/8	1-1/8	1-5/8	1-3/8	1-5/8	1-3/8	1-5/8	1-3/8	1-5/8	1-3/8								
N/A	1-3/8	N/A	1-3/8	N/A	1-3/8	N/A	1-3/8	N/A	1-5/8	N/A	1-5/8	N/A	1-5/8	N/A	1-5/8								
50 - 150																							
45	49	54	58	62	64	64	64																
2 x 1-1/4	2 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4																
2 x 1-1/4	2 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4																
2 x 3/8	2 x 3/8	3 x 3/8	3 x 3/8	3 x 3/8	3 x 3/8	3 x 3/8	3 x 3/8																
464																							
50 - 113																							
50 - 113																							
15.9 - 39.6 (13.2)																							
23 - 113																							
14 - 95																							
21.2 - 39.6																							
2 x 438.7 / 2 x 445.3	2 x 438.7 / 2 x 445.3	2 x 434.3 + 438.7 2 x 440.9 + 445.3	434.3 + 2 x 438.7 440.9 + 2 x 445.3	434.3 + 2 x 438.7 / 440.9 + 2 x 445.3	3 x 438.7 / 3 x 445.3	3 x 438.7 / 3 x 445.3	3 x 438.7 / 3 x 445.3																
38-9/16 x 30-1/8 x 22-1/16																							
50 + 60	60 + 60	40 + 40 + 50	40 + 50 + 50	50 + 50 + 50	50 + 50 + 50	50 + 60 + 60	60 + 60 + 60																
45.2 + 52.6	52.6 + 52.6	38.3 + 38.3 + 45.2	38.3 + 45.2 + 45.2	45.2 + 45.2 + 45.2	45.2 + 45.2 + 52.6	45.2 + 52.6 + 52.6	52.6 + 52.6 + 52.6																
25 + 25	25 + 25	20 + 20 + 25	20 + 25 + 25	25 + 25 + 25	25 + 25 + 25	25 + 25 + 25	25 + 25 + 25																
20.4 + 23.8	23.8 + 23.8	17.3 + 17.3 + 20.4	17.3 + 20.4 + 20.4	20.4 + 20.4 + 20.4	20.4 + 20.4 + 23.8	20.4 + 23.8 + 23.8	23.8 + 23.8 + 23.8																
Inverter																							
6 - 100	5 - 100	5 - 100	5 - 100	5 - 100	4 - 100	4 - 100	4 - 100																

⁴ Application rules apply below 50°F. Please contact your local Daikin office for design assistance and approval.

⁵ Please note that a water strainer (standard accessory for the T-Series, field supplied for the PC-series) is required for each condensing unit.

⁶ PC series model. Some features and benefits may not be available for this model.

VRV T-Series Water-Cooled

Heat Pump or Heat Recovery | 460V



A modular, energy-efficient and reliable alternative to centralized equipment

Features and Benefits

- » Flexible System design with increased diversity up to 150%¹ compared to previous VRV water-cooled generation
- » Small condensers can be triple stacked for reduced installation space and increased usable square footage
- » Larger (than previous models) single-system capacity and modular concept ensures wider application range for accommodating floor-by-floor loads of commercial buildings
- » Year round comfort and energy efficiency by combining VRV and VRT technologies

- » Can be applied to both geothermal and boiler/tower applications as standard with condenser water inlet temperature as low as 14°F in heating and 23°F in cooling is possible
- » 2-9V variable water flow control logic² as standard to increase waterside system operational efficiencies
- » Refrigerant cooled inverter technology to deliver consistent and reliable PCB operations
- » Engineered for easy service with drop-down switch box to access key components

¹ Model specific, check product specification for details

² Refer to installation manual for field settings and other requirements to activate this feature

VRV T-SERIES UNIFIED HEAT PUMP AND HEAT RECOVERY 208-230V & 460V

		6 Ton	8 Ton	10 Ton	12 Ton	14 Ton	16 Ton	18 Ton	20 Ton
Model	208-230V/3Ph/60Hz	RWEQ72TBTJA	RWEQ96TBTJA	RWEQ120TBTJA	RWEQ144TBTJA	RWEQ168TBTJA	RWEQ192TBTJA	RWEQ216TBTJA	RWEQ240TBTJA
	460V/3Ph/60Hz	RWEQ72TBYDA	RWEQ96TBYDA	RWEQ120TBYDA	RWEQ144TBYDA	RWEQ168TBYDA	RWEQ192TBYDA	RWEQ216TBYDA	RWEQ240TBYDA
	Combination					RWEQ72T RWEQ96T	2 x RWEQ96T	RWEQ96T RWEQ120T	2 x RWEQ120T
Performance	Rated Cooling Capacity ¹	BTU/h	69,000	92,000	114,000	138,000	156,000	184,000	206,000
	Rated Heating Capacity ²	BTU/h	69,000	92,000	114,000	138,000	156,000	184,000	206,000
	Sound Pressure Level @ 3 ft.	dB(A)	50	54	55	60.5		57	57.5
Refrigerant Piping	System Configuration: Heat Pump: HP, Heat Recovery: HR		HP	HR	HP	HP	HR	HP - HR	HP
	Liquid Pipe (Main Line)	in.	3/8	3/8	3/8	3/8	1/2	1/2	1/2
	Suction Gas Pipe (Main Line)	in.	3/4	5/8	7/8	3/4	1-1/8	7/8	1-1/8 - 1-1/8
Connection Ratio	Discharge Gas Pipe (Main Line)	in.	N/A	3/4	N/A	7/8	N/A	1-1/8	7/8 - 7/8
	Standard Connectable Indoor Unit Ratio ³	%	50 - 130		50 - 150				
	Maximum Number of Indoor Units	Qty.	12	16	20	25	1-1/4	33	37
Water Side (Standard)	BPHE Inlet Pipe (Female Thread)	in.	1-1/4	1-1/4	1-1/4	1-1/4	1-1/4	2 x 1-1/4	2 x 1-1/4
	BPHE Outlet Pipe (Female Thread)	in.	1-1/4	1-1/4	1-1/4	1-1/4	3/8	2 x 1-1/4	2 x 1-1/4
	Drain Pipe (Female Thread)	in.	1/2	3/8	3/8	3/8	60.5	2 x 3/8	2 x 3/8
Water Side (Geothermal)	Maximum System Water Pressure (BPHE)	psi	285				464		
	Standard Inlet Water Temperature Range Cooling	°F					50 - 113		
	Standard Inlet Water Temperature Range Heating	°F					50 - 113		
Unit	Recommended Inlet Water Flow Rate per Module (minimum)	gpm					15.9 - 39.6 (13.2)		
	Inlet Water Temperature Range Cooling ⁴	°F	27 - 113				23 - 113		
	Inlet Water Temperature Range Heating ⁴	°F					14 - 95		
Electrical (208-230V)	Water Flow Rate ⁵	gpm					21.2 - 39.6		
	Weight (230V/460V)	lbs.	434.3 / 440.9	434.3 / 440.9	438.7 / 445.3	438.7 / 445.3		2 X 440.9 / 2 X 440.9	438.7 + 434.3 / 445.3 + 440.9
	Dimensions (H x W x D)	in.	38-9/16 x 30-1/8 x 22-1/16		38-9/16 x 30-1/8 x 22-1/16			38-9/16 x (30-1/8 x 2) x 22-1/16	
Electrical (460V)	Maximum Overcurrent Protection (MOP)	V	40	40	50	60		40 + 40	40 + 50
	Minimum Circuit Amps (MCA)	A	37.9	38.3	45.2	52.6		38.3 + 38.3	38.3 + 45.2
Compressor	Maximum Overcurrent Protection (MOP)	A	20	20	25	25		20 + 20	25 + 25
	Minimum Circuit Amps (MCA)	A	17.2	17.3	20.4	23.8		17.3 + 17.3	17.3 + 20.4
Compressor Type							Inverter		
Compressor Capacity Control		%	23 - 100	16 - 100	14 - 100	11 - 100		8 - 100	8 - 100
¹ Indoor temp.: 80°FDB, 67°FWB/inlet water temp.: 85°F/ Equivalent piping length : 25 ft., level difference : 0 ft.					² Indoor temp.: 70°FDB, 60°FWB/inlet water temp.: 70°F / Equivalent piping length: 25 ft., level difference : 0 ft.				
					³ Varies based on indoor and condensing unit model selected; refer to Engineering Manual for details.				

¹ Indoor temp.: 80°FDB, 67°FWB/inlet water temp.: 85°F/ Equivalent piping length : 25 ft., level difference : 0 ft.

² Indoor temp.: 70°FDB, 60°FWB/inlet water temp.: 70°F / Equivalent piping length: 25 ft., level difference : 0 ft.

³ Varies based on indoor and condensing unit model selected; refer to Engineering Manual for details.



RWEQ_TATJA/TAYDA

22 Ton		24 Ton		26 Ton		28 Ton		30 Ton		32 Ton		34 Ton		36 Ton									
RWEQ264TBTJA	RWEQ288TBTJA*	RWEQ312TBTJA*	RWEQ336TBTJA*	RWEQ360TBTJA*	RWEQ384TBTJA*	RWEQ408TBTJA*	RWEQ432TBTJA*	RWEQ264TBYDA	RWEQ288TBYDA*	RWEQ312TBYDA*	RWEQ336TBYDA*	RWEQ360TBYDA*	RWEQ384TBYDA*	RWEQ408TBYDA*	RWEQ432TBYDA*								
RWEQ120T RWEQ144T	2x RWEQ144TB	2x RWEQ96TB RWEQ120TB	RWEQ96TB 2x RWEQ120TB	3x RWEQ120TB	2x RWEQ120TB RWEQ144TB	RWEQ120TB 2x RWEQ144TB	3x RWEQ144TB	252,000	274,000	296,000	320,000	342,000	366,000	388,000	402,000								
252,000	274,000	298,000	320,000	342,000	366,000	388,000	402,000	61.5	63.5	59	59.5	60	62	64	65								
HP	HR	HP	HR	HP	HR	HP	HR	HP	HR	HP	HR	HP	HR	HP	HR								
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4								
1-3/8	1-1/8	1-3/8	1-1/8	1-3/8	1-1/8	1-3/8	1-1/8	1-5/8	1-3/8	1-5/8	1-3/8	1-5/8	1-3/8	1-5/8	1-3/8								
N/A	1-3/8	N/A	1-3/8	N/A	1-3/8	N/A	1-3/8	N/A	1-5/8	N/A	1-5/8	N/A	1-5/8	N/A	1-5/8								
50 - 150																							
45	49	54	58	62	64	64	64																
2 x 1-1/4	2 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4																
2 x 1-1/4	2 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4	3 x 1-1/4																
2 x 3/8	2 x 3/8	3 x 3/8	3 x 3/8	3 x 3/8	3 x 3/8	3 x 3/8	3 x 3/8																
464																							
50 - 113																							
50 - 113																							
15.9 - 39.6 (13.2)																							
23 - 113																							
14 - 95																							
21.2 - 39.6																							
2 x 438.7 / 2 x 445.3	2 x 438.7 / 2 x 445.3	2 x 434.3 + 438.7 2 x 440.9 + 445.3	434.3 + 2 x 438.7 440.9 + 2 x 445.3	434.3 + 2 x 438.7 / 440.9 + 2 x 445.3	3 x 438.7 / 3 x 445.3	3 x 438.7 / 3 x 445.3	3 x 438.7 / 3 x 445.3																
38.9/16 x 30.1/8 x 22.1/16																							
50 + 60	60 + 60	40 + 40 + 50	40 + 50 + 50	50 + 50 + 50	50 + 50 + 50	50 + 60 + 60	60 + 60 + 60																
45.2 + 52.6	52.6 + 52.6	38.3 + 38.3 + 45.2	38.3 + 45.2 + 45.2	45.2 + 45.2 + 45.2	45.2 + 45.2 + 52.6	45.2 + 52.6 + 52.6	52.6 + 52.6 + 52.6																
25 + 25	25 + 25	20 + 20 + 25	20 + 25 + 25	25 + 25 + 25	25 + 25 + 25	25 + 25 + 25	25 + 25 + 25																
20.4 + 23.8	23.8 + 23.8	17.3 + 17.3 + 20.4	17.3 + 20.4 + 20.4	20.4 + 20.4 + 20.4	20.4 + 20.4 + 23.8	20.4 + 23.8 + 23.8	23.8 + 23.8 + 23.8																
Inverter																							
6 - 100	5 - 100	5 - 100	5 - 100	5 - 100	4 - 100	4 - 100	4 - 100																

⁴ Application rules apply below 50°F. Please contact your local Daikin office for design assistance and approval.

⁵ Please note that a water strainer (standard accessory for the T-Series, field supplied for the PC-series) is required for each condensing unit.

⁶ PC series model. Some features and benefits may not be available for this model.

VRV S-series (R-32)

Heat Pump | 208-230V

R32

Small Size, Robust Possibility.

The Daikin VRV-S elevates the renowned VRV air-cooled technology with its sleek, compact design tailored for small-scale installations without compromising performance. The Daikin VRV-S comes integrated with Variable Refrigerant Temperature (VRT) technology that supports optimal comfort throughout the year while maintaining overall energy efficiency.

Leveraging the engineering design opportunities of R-32, the new Daikin VRV-S provides an expansion of the product offering as well as several improvements compared to the previous Daikin VRV IV S-series. The new Daikin VRV-S improvements include the addition of a 2-ton size, single-fan chassis in all sizes, longer pipe lengths, efficiency, and capacity improvements, and more!

Light Commercial and Residential

A highly efficient solution, the Daikin VRV-S can provide cooling and heating for up to 9 zones. With many different indoor unit options, systems can be paired with a mix of ducted and duct-free indoor units for a customizable system. Designed for flexibility and versatility, the Daikin VRV-S system provides long piping lengths, which are accommodating and space-saving for almost any floor layout.

Low GWP R-32 Refrigerant:

Aligning with Daikin's goals of decarbonization, sustainability, and advancement towards clean energy, Daikin VRV-S models feature Low GWP R-32 refrigerant. Widely used and proven around the globe, easily available, efficient, and affordable, R-32 is an ideal choice to replace R-410A. Additionally, R-32 is a single component refrigerant offering simplicity and flexibility in charging and reclaiming (compared to blended refrigerants)



Capacity Range: 2 to 5 tons

Applications:



OFFICE



HOTELS



RESIDENTIAL



SCHOOLS

Features, Benefits, and Improvements:

- » Addition of a 2-ton model for a complete 2- to 5-ton offering
- » Long pipe lengths with vertical separation up to 164 ft. and total pipe length up to 984 ft.
- » Compact, space-saving single fan chassis design across all sizes
- » Dependable operation in extreme ambient conditions of up to 122°F¹
- » Compact height of only 34-1/4" to support a range of applications
- » Efficient operation and year-round energy savings through Variable Refrigerant Temperature (VRT) technology
- » Improved efficiencies in heating and cooling operation compared to the previous R-410A lineup
- » Quiet operation with sound levels as low as 56 dB(A)
- » Ease of retrofit of existing R-410A installation with the ability to re-use larger diameter refrigerant pipes via field setting
- » Optional base pan heater to defrost base pan in cooler climate applications
- » Increased nominal capacity compared to previous R-410A lineup up to 60,000 Btu/hr for the 5T model

¹ Conditions/rules apply. Refer to the Installation and Engineering Manual for details.




DAIKIN VRV-S SERIES		Model Name	RXTA24AAVJU	RXTA36AAVJU	RXTA48AAVJU	RXTA60AAVJU
STYLE	ODU Style	Fan Type	Single Fan			
PERFORMANCE	Nominal Cooling Capacity	BTU/H	24,000	36,000	48,000	60,000
	Nominal Heating Capacity	BTU/H	27,000	40,000	52,000	60,000
	Operation Range Cooling	°F DB	23 to 122			
	Operation Range Heating	°F WB	-4 to 60			
	Power	V/P/HZ	208-230/1/60			
	Sound Pressure Level @ 3ft	dB(A)	56	56	56	57
REFRIGERANT PIPING	Refrigerant		R-32			
	Refrigerant Quantity	lbs.	7.5	7.5	7.5	7.5
	Liquid Pipe (Main Line)	in.	3/8			
	Suction Gas Pipe (Main Line)	in.	5/8			
	Vertical Drop	ft.	164			
	Vertical Rise	ft.	130			
	Maximum vertical pipe length between IDU	ft.	49			
	Actual Pipe Length (Equivalent Length)	ft.	394 (492)			
	Total Piping Length	ft.	984			
CONNECTION RATIO	Connectable Indoor Unit Ratio	%	50-130			
	Number of Indoor Units	Qty	4	6	8	9
UNIT	Outdoor Unit Size	(HxWxD)	34-1/4 x 43-5/16 x 18-1/8			
	Weight	lbs.	220			
FAN	Airflow	CFM	3000			
	Fan Motor Output and Quantity	kW	0.20 x 1			
ELECTRICAL	Maximum Over Current Protection (MOP)	A	20	20	30	35
	Minimum Circuit Amps (MCA)	A	19.8	19.8	29.4	34.6
COMPRESSOR	Compressor Type	Type	Daikin Swing	Daikin Swing	Daikin Swing	Daikin Swing
	Capacity Control	%	14-100	14-100	14-100	14-100

Daikin VRV-S outdoor heat pumps are compatible only with the R-32 indoor units. R-410A-based indoor units are not compatible with the new Daikin VRV-S heat pump.




The Daikin Swing Compressor

- » Daikin VRV-S SERIES built with the highly reliable Daikin swing compressor
- » Daikin's swing compressor technology integrates all the moving parts into one component
- » The integration minimizes abrasion between moving parts and refrigerant leakage through gaps from high to low pressure zones
- » Daikin's swing compressors deliver higher compressor efficiencies than a standard rotary compressor



VRT mode control selection to match user preferences

Basic mode is selected to maintain optimal comfort. VRT is selected to save energy and prevent excessive cooling.



- » Can boost capacity above 100% if needed.
- The refrigerant temperature can go lower in cooling than the set minimum.
- » Gives priority to very fast reaction speed.
- The refrigerant temperature cannot drop too low to know the

- » Gives priority to fast reaction speed.
- The refrigerant temperature goes down fast to keep the room setpoint stable.

- » Gives priority to efficiency.
- The refrigerant temperature goes down gradually giving priority to the efficiency of the system instead of the reaction speed.

Installation Space




VRV EMERSON / VRV IV X / VRV IV / VRV AURORA

Installation Space Examples

- » The installation space requirement shown in the figure is a reference for cooling.
- » During installation, install the units using the most appropriate of the patterns shown in the figure for the location in question, taking into consideration human traffic and wind.

- » If the number of units installed is more than that shown in the pattern in the figure, install the units so that there is no air short circuiting.
- » Consider the space needed for the refrigerant piping when installing the units, as determined by local codes.
- » If the space requirements in the figure do not apply, contact your contractor or Daikin directly.



Notes

1. Heights of walls in case of Patterns 1 and 2:

Front: 59in

Suction side: 19-5/8in

Side: Height unrestricted.


Installation space shown in this drawing is based on the cooling operation at 95°F outdoor air temperature.

When the design outdoor temperature exceeds 95°F or the load exceeds maximum ability because of much generation load of heat in all outdoor unit, take the suction-side space more broadly than the space shown in this drawing.

2. If the above wall heights are exceeded then $h2/2$ and $h1/2$ should be added to the front and suction side service spaces respectively as shown in the figure.

3. When installing, the units most appropriate pattern should be selected in order to obtain the best fit in the space available, always bearing in mind the need to leave enough space for a person to pass between the units and wall and for the air to circulate freely.

4. The units should be installed to leave sufficient space at the front for the field refrigerant piping work to be carried out comfortably.






VRV

T-Series Water Cooled System

1. In case of a single installation [inch.]
2. In case of multiple unit installation [inch.]
3. Top view
4. Side view
5. Condensing unit
6. Service Space (front side)
7. Service Space (back side)
8. Space for installing water piping must be ample enough to remove the front panel.







9. Ventilation space (refer to Engineering Data Book for further details)
10. Secure spaces in the front, back, and top sides as same as the case of single installation.

11. Service space above the unit for refrigerant piping (refer to Engineering Data Book for further details)

VRV IV S-series

In case of series installation, some space between the units is needed for wiring with conduit and servicing.

1. Where there is an obstacle on the suction side:
 - (a) No obstacle above
 - (1) Stand alone installation
 - Obstacle on the suction side only
 - Obstacle on both sides
2. Where there is an obstacle on the discharge side:
 - (a) No obstacle above
 - (1) Stand alone installation



Unit values are in inches

Piping Length



The long piping length provides more design flexibility, which can match even large-sized buildings.

Air-cooled system piping length

For connection of only VRV indoor units

	VRV EMERION, VRV IV X, VRV IV & VRV AURORA	VRV IV-S
Max. actual piping length	541 ft.	230 ft. (3-Ton: 164 ft.)
Max. equivalent piping length	623 ft.	295 ft. (3-Ton: 213 ft.)
Max. total piping length	3281 ft. (AURORA: 1640 ft.)	984 ft. (3-Ton: 820 ft.)
Max. level difference between the outdoor units and the indoor units	295 ft. [†] (EMERION: 361 ft.)	98 ft.
Max. level difference between the indoor units	100 ft.*	49 ft. (3-Ton: 33 ft.)
Max. distance from 1st refrigerant branch joint	295 ft.	130 ft.

Piping for VRV EMERION VRV IV X, VRV IV, VRV AURORA, and VRV IV-S

		ACTUAL PIPING LENGTH		EXAMPLE	EQUIVALENT PIPING LENGTH	
		VRV EMERION, VRV IV X/ VRV IV/ VRV AURORA	VRV IV-S		VRV EMERION, VRV IV X/ VRV IV/ VRV AURORA	VRV IV-S
Maximum allowable piping length	Refrigerant piping length	541 ft.	164 ft. 230 ft.	a+b+c+d+e	623 ft	213 ft 295 ft
	Total piping length	3281 ft. AURORA: 1640 ft.	820 ft. 984 ft.	a+b+c+d+e+f+g+h+i	—	— —
	Between the first indoor unit-branch and the farthest indoor unit	295 ft.*	98 ft. 98 ft.	b+c+d+e	—	— —

		LEVEL DIFFERENCE			EXAMPLE
		VRV EMERION, VRV IV X/ VRV IV/ VRV AURORA	VRV IV-S	3-Ton 4-5 Ton	
Maximum allowable level difference	Between the outdoor units (multiple use on the same circuit)	16 ft.	n/a	n/a	—
	Between the indoor units	98 ft.	33	49	s
	Between the outdoor units and the indoor units	295 ft. (EMERION: 361 ft.) [†]	98	98	r
	If the outdoor unit is above the indoor units	295 ft. (EMERION: 361 ft.) [†]	98	98	r

* No special requirements up to 131 ft. The maximum actual piping length can be 295 ft., depending on conditions. Various conditions and requirements have to be met to allow utilization of 295 ft. piping length. Be sure to refer to the Engineering Data Book for details of these conditions and requirements.

[†] Refer to installation manuals for details of the conditions and requirements




Water-cooled system piping length

Water-Cooled systems provide considerable design flexibility with total piping lengths of up to 980 ft. and vertical separation of up to 164 ft.* between condensing units and indoor units.

For connection of only VRV indoor units


Actual piping length between the VRV T-Series and indoor units: 540ft. (equivalent piping length: 623ft.)



REFRIGERANT PIPING LIMITATIONS	LIMITATIONS
Linear piping between condensing unit and furthest located fan coil unit (equivalent), ft.	540 (623)
Total "one-way" piping in the complete piping network, ft.	980
Vertical (height) separation between the condensing unit and the fan coil units (if condensing unit is below)*, ft.	164 (130)
Vertical (height) separation between fan coil units, ft.	98
Linear piping between 1st REFNET and furthest located fan coil unit, ft.	130 (295)**

* Conditions apply when the condenser is lower than indoor units. Refer to your local Daikin representative for further information.

** Conditions/rules apply. Refer to Installation manual for further details.



VRV Accessories

Branch Selector Boxes

New *Flex Branch Selector* for Ultimate Flexibility

Daikin's new *Flex Branch Selector* boxes are engineered to be compact and provide flexibility in design, installation, maintenance, and service. Packed with Daikin's state of the art technology, the new *Flex Branch Selector* boxes fit in tight mechanical spaces (common in ceilings) combined with flexibility in piping configuration and movable E-box makes the new design an ideal choice for commercial buildings.

Main Features and Benefits

Flexible

- » Design flexibility with versatile piping configurations of Left or Right or Pass through layouts.
- » Engineered for tight ceiling spaces with a compact height of 9½" and 0"1 service clearance between the slab and the top of the *Flex Branch Selector* box.
- » Flexibility to expand design with up to 121 ports and 230Mbh¹ down stream capacity by connecting multiple boxes in series.
- » Ability to optimize installed system cost by reducing *REFNETs* and braze joints in pass thru configuration vs non-pass through configuration.
- » Simple electrical configurations with flexibility to re-position E-box.²
- » Ability to mix and match Daikin *Flex Branch Selector* boxes and standard branch selector box for ultimate design flexibility.

¹ Refer to engineering manuals for design rules

² Feature available for BSF4Q54TVJ (4-port) model only




Installation Flexibility


- » Ease of maintenance with access to electronic expansion valve (EEV) heads and motor via side access panel.
- » Eliminate cross piping with refrigerant pipe identification labels.
- » Simple electrical and communication wiring with connection from the front side of E-box.²

Innovative

- » Daikin's high specification EEV enables precise refrigerant control for high comfort in user spaces and reliable system operation.
- » Hermetically sealed to prevent condensate build up within the unit, eliminating the need for a condensate drain pan and plumbing connections for a simple installation.
- » Low ambient cooling down to -4°F¹ for simple and integrated system design.




From Left




Left and Pass Thru

OR




From Right




Right and Pass Thru


Factory Default Rear E-box






Field Convertible to Left Sided



Field Convertible to Right Sided



OR




*Available on 4 port only.

TECHNICAL DATA FOR MULTI-PORT BRANCH SELECTOR BOXES

Model	BSF4Q54TVJ	BSF6Q54TVJ	BSF8Q54TVJ
Number of Branches	4	6	8
Maximum capacity index per branch		54	
Max Total Capacity Index when in Parallel/ when in Series	144	216 / 162	290 / 162
Max Number of Connectable Indoor Units Per Branch		5	
Max total capacity Index under BS Units Connected in Series		230	
Connecting Pipes	Indoor Unit	Liquid in.	3/8 (1/4) Brazing
		Gas in.	5/8 (1/2) Brazing
	Outdoor unit	Liquid in.	5/8 Brazing
		Suction Gas in.	1-1/8 Brazing
		HP/LP Gas in.	1-1/8 Brazing
Electrical	Power Supply	ph/V/Hz	Single phase / 208-230V / 60Hz
	Maximum Overcurrent Protection, MOP	A	15
	Minimum Circuit Amps, MCA	A	0.4 0.6 0.8
Sound Level	Operating sound	dB (A)	37 40.5 40.5
	Max. sound	dB (A)	47 50 50
Weight	lbs.	49	73 81
Dimensions (H x W x D)	in.	9-1/2 x 13-3/4 x 23-3/4	9-1/2 x 23-3/8 x 23-3/4

MULTI-PORT BRANCH SELECTOR BOX INSTALLATION SPACE



MINIMUM CLEARNACE | BSF4Q54TVJ | BSF6Q54TVJ | BSF8Q54TVJ

A	in.	20
B	in.	3/16

VRV Accessories

Branch Selector Boxes (cont.)

Branch Selector Boxes for Heat Recovery Systems

Providing flexibility and minimizing mechanical and electrical installation costs, Daikin's branch selector boxes are ideal for spaces that require individual heating and cooling control.

- » New *Flex Branch Selector* models offered in 4, 6, and 8 port.
- » Ability to connect multiple branch selector boxes in series or in parallel when using *Flex Branch Selector* Box
- » Extend phase installation capability of *VRV EMERION* and *VRV IV X* by leveraging *Flex Branch Selector* box ability to add on additional boxes in series
- » Wide range of product offerings with 1, 4, 6, 8, 10 and 12 port options
- » No drain or condensate consideration required
- » Unlimited number of unused ports per box or system
- » Reduce electrical and mechanical installation costs
- » Ultimate flexibility – Choose multi-port or single-port styles to customize your design

Branch Selector Boxes Compatibility

Single-Port and Multi-Port Branch Selector Boxes BS-TVJ and BSF-TVJ series are compatible with *VRV EMERION*, *VRV IV X*, *VRV IV* and *VRV T-Series* Water-Cooled Heat Recovery Units.



BSQ36TAVJ, BSQ60TAVJ,
& BSQ96TAVJ Single Port



BS4Q54TAVJ



BS6Q54TAVJ, BS8Q54TVJ




BSF4Q54TVJ




BS10Q54TVJ, BS12Q54TAVJ



BSF6Q54TVJ



BSF8Q54TVJ





Daikin's branch selector boxes are ideal for spaces that require individual heating and cooling control.

STANDARD MULTI-PORT T-SERIES

TECHNICAL DATA - MULTI-PORT T-SERIES BRANCH SELECTOR BOXES

Model	BS4Q54TAVJ	BS10Q54TAVJ	BS12Q54TAVJ
Number of branches	4	10	12
Maximum capacity index per branch		54	
Maximum total capacity index	144		290
Maximum connectable indoor units per branch		5	
Connecting Pipes	IU	Liquid in. Ø1/4, Ø3/8 Gas in. Ø1/2, Ø5/8	
	OU	Liquid in. Ø3/8 Suction Gas in. Ø7/8 HP/LP Gas in. Ø3/4	Ø5/8 Ø1-1/8 Ø1-1/8
Electrical	Power Supply	ph/V/Hz	1/208-230/60
	Maximum Overcurrent Protection, MOP	A	15
	Minimum Circuit Amps, MCA	A	1 1.2
Mass (Weight)	lbs.	49	101 106
Dimensions (H x W x D)	in.	11-3/4 x 14-9/16 x 18-15/16	11-3/4 x 32-5/16 x 18-15/16

STANDARD T-SERIES MULTI PORT BRANCH SELECTOR BOXES INSTALLATION SPACE






MINIMUM CLEARANCE	BS4Q54TAVJ	BS10Q54TAVJ	BS12Q54TAVJ
A in.	20		
B in.	11-3/4		

SINGLE PORT BRANCH SELECTOR BOXES

TECHNICAL DATA FOR SINGLE-PORT BRANCH SELECTOR BOXES

Model	BSQ36TAVJ	BSQ60TAVJ	BSQ96TAVJ
Number of branches	1	1	1
Maximum capacity index	36	60	96
Maximum connectable indoor units	4	8	8
Connecting Pipes	IU	Liquid in. Ø3/8 Gas in. Ø7/8	
	OU	Liquid in. Ø3/8 Suction Gas in. Ø5/8 HP/LP Gas in. Ø1/2	Ø7/8 Ø7/8 Ø3/4
Electrical	Power Supply	ph/V/Hz	1/208-230/60
	Maximum Overcurrent Protection, MOP	A	15
	Minimum Circuit Amps, MCA	A	0.1
Mass (Weight)	lbs.	24	24 31
Dimensions (H x W x D)	in.		8-1/8 x 15-1/4 x 12-13/16

SINGLE-PORT BRANCH SELECTOR BOX INSTALLATION SPACE



MINIMUM CLEARANCE	BSQ36TAVJ	BSQ60TAVJ	BSQ96TAVJ
A in.	10	10	12
B in.	10	10	12
C in.	-	13-3/4	15-3/4
D in.	12	13-3/4	15-3/4
E in.	12	12	11-13/16

For additional technical information and all equipment installation and application limitations please refer to the specific Engineering Data Books.

VRV Accessories

REFNET | Pipe Joints

REFNET

REFNET joints distribute correct flow of refrigerant in every branch of the piping network. Sourced locally and complies to ASTM E-84 Class A low flame and smoke spread index requirements.



REFNET Joint



REFNET Header

VRV IV X, VRV IV / VRV AURORA Heat Pump

OPTIONAL ACCESSORIES		RXYQ72 - 96T RXYQ72 - 96X RXLQ72 - 96T	RXYQ120-168T RXYQ120-168X RXLQ120T	RXYQ192-336T RXYQ192-336X RXLQ144-240T	RXYQ360-408T RXYQ360-408X RXYQ360-480MBH
Distributed piping	REFNET Header	KHP26M22H (max. 4 branch) KHP26M33H (max. 8 branch)		KHP26M22H (max. 4 branch) KHP26M33H (max. 8 branch) KHP26M72H (max. 8 branch)	KHP26M22H (max. 4 branch) KHP26M33H (max. 8 branch) KHP26M72H (max. 8 branch) KHP26M73HU (max. 8 branch)
	REFNET Joint	KHP26A22T, KHP26A33T		KHP26A22T, KHP26A33T, KHP26M72TU	KHP26A22T, KHP26A33T, KHP26M72TU, KHP26M73TU
Outdoor unit multi connection piping kit		—		BHFP2P100U	BHFP2P151U

VRV EMERION / VRV IV X / VRV IV / VRV AURORA Heat Recovery

OPTIONAL ACCESSORIES		REYQ72 - 96A REYQ72 - 96X RELQ72 - 96T	REYQ120-168A REYQ120-168X REYQ120-168T	REYQ192-480A REYQ192-336X REYQ192-336T	REYQ360-456X REYQ360-456T
Distributed piping	REFNET header	KHP25M33H (max. 8 branch)		KHP25M33H (max. 8 branch) KHP25M72H (max. 8 branch)	KHP25M33H (max. 8 branch) KHP25M72H (max. 8 branch) KHP25M73HU (max. 8 branch)
	REFNET joint	KHP25A22T KHP25A33T		KHP25A22T KHP25A33T KHP25M72TU	KHP25A22T KHP25A33T KHP25M72TU KHP25M73TU
Outdoor unit multi connection piping kit		—		BHFP26P100U ¹	BHFP26P151U

¹Reducer pipe kit KHP26P100UA is required for REYQ26A-480A models

VRV T-Series Water-Cooled Heat Pump / Heat Recovery and VRV IV-S

UNIT MODEL NUMBER	VRV T-SERIES WATER-COOLED					VRV IV-S
	RWFQ96T	RWFQ120T	RWFQ144T	RWFQ192 - 288T	RWFQ312 - 432T	RXTQ36TAVJ9A RXTQ48TAVJUA RXTQ60TAVJUA
REFNET Header	Heat Pump	KHP26M22H (Max 4 branch) KHP26M33H (Max 8 branch)	KHP26M22H (Max 4 branch), KHP26M33H (Max 8 branch) KHP26M72H (Max 8 branch)	KHP26M22H (Max 4 branch), KHP26M33H (Max 8 branch) KHP26M72H (Max 8 branch), KHP26M73HU (Max 8 branch)	KHP26M22H (Max 4 branch) KHP26M33H (Max 8 branch)	KHP26M22H (Max. 4 branch) KHP26M33H (Max. 8 branch)
	Heat Recovery	KHP25M33H (Max 8 branch)	KHP25M33H (Max 8 branch) KHP25M72H (Max 8 branch)	KHP25M33H (Max 8 branch), KHP25M72H (Max 8 branch) KHP25M73HU (Max 8 branch)	KHP25M33H (Max 8 branch), KHP25M72H (Max 8 branch) KHP25M73HU (Max 8 branch)	—
REFNET Joint	Heat Pump	KHP26A22T, KHP26A33T	KHP26A22T, KHP26A33T, KHP26M72TU	KHP26A22T, KHP26A33T, KHP26M72TU, KHP26M73TU	KHP26A22T	KHP26A22T
	Heat Recovery	KHP25A22T, KHP25A33T	KHP25A22T, KHP25A33T, KHP25M72TU	KHP25A22T, KHP25A33T, KHP25M72TU, KHP25M73TU	KHP25A22T	—
Outdoor Unit Multi Piping Connection Kit	Heat Pump	—	—	BHFP22T84U	BHFP22T126U	—
	Heat Recovery	—	—	BHFP26T84U	BHFP26T126U	—

Hail Guard Kits

The optional hail guard kit for VRV3-phase enables optimal airflow for efficient heat transfer while providing condenser coil protection from hail damage in severe climates. Each hail guard kit, that is field installed, consists of 4 panels (Right, Left, Front and Back).

Hail Guard Kit for VRV IV X, VRV IV, and VRV AURORA

QUANTITY OF KITS PER ODU MODELS					PANEL DIMENSIONS (H X W X D)				
VRV IV	R_YQ72T	R_YQ96-168T	R_YQ192T	R_YQ216-336T	R_YQ360-456T	Right Panel	Left Panel	Front Panel	Front Panel
VRV AURORA		R_LQ72-120T		R_LQ144-240T					
VRV IV X HP	RXYQ72X	RXYQ96-168X	RXYQ192X	RXYQ216-336X	RXYQ360-456X				
VRV IV X HR		REYQ72-168X		REYQ192-336X	REYQ360-408X				
VRV4HGS-K1	1		1					45 ^{7/8} " x 13 ^{1/4} " x 4"	45 ^{7/8} " x 32 ^{5/8} " x 4"
VRV4HGL-K1		1	1	2	3			45 ^{7/8} " x 24" x 4"	45 ^{7/8} " x 44 ^{3/4} " x 4"

*Refer engineering and installation manual for more detail.

Hail Guard Kit for VRV EMERION

QUANTITY OF KITS PER ODU MODELS			
VRV EMERION	RXYQ72A / REYQ72A	RXYQ96-168A / REYQ96-168A	RXYQ192-240A / REYQ192-240A-240A
VRV6HGM-K1	1		
VRV6HGL-K1		1	
VRV6HGX-L-K1			1



Snow/Wind Hood Kits

The optional Snow/Wind Hood Kits mount over the heat exchanger coil to protect from snow build-up and wind in cold climates. The Hoods install easily to condensing units using existing screw taps with no modification required. Different kits can be ordered for different job requirements.

VRV IV / IV X AURORA	KIT PART NUMBER	CHASSIS SIZE	KIT INCLUSION	
VRV-SHS-FR	Small Chassis	Front Hood	Rear Hood	
VRV-SHL-FR	Large Chassis	Front Hood	Rear Hood	
VRV-SH-RL	Both Chassis	Right Hood	Left Hood	
VRV-SHS-T	Small Chassis	Top Hood		
VRV-SHL-T	Large Chassis	Top Hood		

VRV EMERION	KIT PART NUMBER	CHASSIS SIZE	KIT INCLUSION	
VRV6-SHM-FR	Medium Chassis	Front Hood	Rear Hood	
VRV6-SHL-FR	Large Chassis	Front Hood	Rear Hood	
VRV6-SHXL-FR	X-Large Chassis	Front Hood	Rear Hood	
VRV6-SH-RL	All Chassis	Right Hood	Left Hood	
VRV6-SHM-T	Medium Chassis	Top Hood		
VRV6-SHL-T	Large Chassis	Top Hood		
VRV6-SHXL-T	X-Large Chassis	Top Hood		

NUMBER OF KITS REQUIRED FOR EACH OUTDOOR SYSTEM						
MODEL TYPE						
		NUMBER OF MODULES				
		VRV6-SHM-FR				
		VRV6-SHXL-FR				
		VRV6-SHM-T				
		VRV6-SHL-T				
		VRV6-SH-RL				
		VRV6-SHS-FR				
		VRV6-SHL-T				
		VRV6-SHS-T				
VRV EMERION	208-230V / 460V	RXYQ72A, REYQ72A RXYQ96-168A, REYQ96-168A RXYQ192-240A, REYQ192-240A RXYQ264-336A, REYQ264-336A RXYQ360A, REYQ360A RXYQ384-480A, REYQ384-480A	Single Single Single Dual Dual Dual	1 1 1 2 1 2	1 1 1 2 1 2	1 1 1 1 1 1
VRV AURORA	208-230V / 460V / 575V	R_LQ72-120T R_LQ144-240T	Single Dual			1 2
VRV IV Heat Recovery Heat Pump	208-230V / 460V	R_YQ72T R_YQ96-168T R_YQ192T R_YQ216-336T R_YQ360-456T*	Single Single Dual Dual Triple			1 1 1 2 3
VRV IV X Heat Recovery	208-230V / 460V	REYQ72-168X REYQ192-336X REYQ360-456X	Single Dual Triple			1 2 3
VRV IV X Heat Pump	208-230V / 460V	RXYQ72X RXYQ96-168X RXYQ192X RXYQ216-336X RXYQ360-408X	Single Single Dual Dual Triple			1 1 1 2 3

*Up to 408 on Heat Pump

Air Handling Unit (AHU) Integration Kit



Designed for High Efficiency


The Daikin Air Handling Unit Integration Kit enables a non-VRV Air Handling Unit to be fully integrated into a Daikin VRV system, allowing the benefits of inverter technology to extend to custom terminal units and air handling equipment.

Designed for high system efficiency, the Air Handling Unit Integration Kit offers a seamless integration and optimized design flexibility for Air Handling Units while keeping total installation and commissioning time to a minimum.

A kit consists of one Control Box and one EEV Box. Two different control methods can be used for an evaporator coil of up to 16 tons.

Features and Benefits

- » Enables non-VRV Air Handling Units to be seamlessly integrated into a Daikin VRV system
- » Integrates to VRV Heat Pump and Heat Recovery systems*
- » Daikin DIII-NET communication compatible — can be used with both Daikin *iTM* and *Navigation* controller
- » Separate Control Box and EEV Box accommodates flexible installation
- » Available with two control methods:
 - EKEQMCBAV3-US (Z-Control)
 - Standard VRV indoor unit room temperature control
 - EKEQFCBAV3-US (W-Control)
 - Field supplied temperature sensor
 - Field supplied DDC controller with 0-10V capability)



* Important! For any VRV systems that utilize the AHU integration kits to perform as intended, the DX coil(s) in the non-VRV AHU unit(s) must meet the range of criteria set forth in the AHU Integration Kit Selection Guide and all associated piping and combination rules (refer to IOD-7041A and IOD-7042A), and should be installed in accordance to the installation manual provided with the EKEQ control boxes.





ELECTRONIC EXPANSION VALVE BOX SPECIFICATIONS		EKEXV50-US	EKEXV63-US	EKEXV80-US	EKEXV100-US	EKEXV125-US	EKEXV140-US	EKEXV200-US	EKEXV250-US	EKEXV400-US	EKEXV500-US
Nominal Capacity	BTU/h	18,000	24,000	30,000	36,000	48,000	60,000	72,000	96,000	144,000	192,000
AHU Heat Exchanger Cooling Capacity Range	BTU/h	17,000-21,000	21,500-26,500	27,000-34,500	34,000-42,000	42,500-52,500	53,000-60,000	60,500-84,000	84,500-105,000	120,000-169,000	170,000-210,000
AHU Heat Exchanger Heating Capacity Range	BTU/h	19,000-24,000	24,200-30,000	30,500-38,000	38,500-47,000	47,500-59,000	59,500-67,500	68,000-94,500	95,000-118,500	136,000-187,500	188,000-236,500
AHU Heat Exchanger Refrigerant Volume Range	in ³	46-100	101-126	127-161	162-201	202-251	252-281	282-402	403-503	564-804	806-1006
Power Supply	V/ph/Hz	208-230/1/60									
Weight	lbs.	6.4									
Height	in.	15-3/4									
Width	in.	8-1/2									
Depth	in.	3-1/16									
Pipe Connections	in.	1/2 x 1/4	3/8 x 5/8				3/4 x 3/8	7/8 x 3/8	1-1/8 x 1/2	1-1/8 x 5/8	

*Important! For any VRV systems that utilize the AHU integration kits to perform as intended, the DX coil(s) in the non-VRV AHU unit(s) must meet the range of criteria set forth in the AHU Integration Kit Selection Guide and all associated piping and combination rules (refer to IOD-7041A and IOD-7042A), and should be installed in accordance to the installation manual provided with the EKEQ control boxes.



Features and Benefits

- » Designed for both indoor and outdoor installation
- » Equipped with refrigerant filters on both sides of the expansion valve
- » Can be mounted up to 16 ft (5m) away from the air handling unit
- » Simplified installation with inlet and outlet brazed connections
- » Wide range that covers from 1.5 ton to 16 ton
- » Same EEVs as used in standard VRV Indoor product to deliver precise refrigerant control

Control Box


EKE _CBAV3-US



EKEQMCBAV3 - US

For use with both Daikin VRV indoor units and custom air handling units


- » Allows for discharge air control
- » Seamless integration of non-VRV air handling units with VRV IVHP and HR systems
- » Enables control of the AHU as a VRV Indoor unit when integrated with a Daikin remote control
- » Connect other VRV indoor units along with the AHU to the condensing units
- » Provides remote ON/OFF option when integrated with optional KRP4A71 board
- » Designed for both indoor and outdoor installations



EKEQFCBAV3 - US

For use with custom air handling units only

- » Seamlessly integrate non-VRV air handling units with VRV IVHP
- » Best suited for applications where 1 AHU is connected to 1 VRV system only
- » Connect up to 3 integration kits per VRV system to serve a large capacity AHU
- » Unified cooling and heating mode programming
- » Enables control of AHU unit using field temperature sensor and 0-10V field supplied DDC controller
- » Allows for discharge air temperature control





CONTROL BOX SPECIFICATIONS		EKEQMCBAV3-US (Z-Control)	EKEQFCBAV3-US (W-CONTROL)
Entering Air Temperature Limits	Cooling °F	57 WB - 77 WB	106 DB/90 WB
	Heating °F	50 DB - 80 DB	Min of 23 DB
Power Supply	V/ph/Hz	208-230/1/60	
Weight	lbs.	8	8.6
Height	in.	5-13/64	
Width	in.	15-3/4	
Depth	in.	9-3/8	
Connection Ratio		50 - 110%	90 - 110%
	EKEXV to AHU	16 ft.	16ft.
Max Piping Distance	ODU to AHU	Standard VRV outdoor unit piping limitations based on model selection apply	360 ft*
Max number of IDU/system			
VRVIDU + AHU		64	Not available
AHU Only		32	1

*Capacity de-rate applies beyond 164 ft

VRV System Compatibility

VRV System			AHU Integration Kit Type	
VRV System Type	Type	Series	EKEQMCBAV3-US	EKEQFCBAV3-US
			Z-Control	W-Control
Air-Cooled all voltages (3-Phase)	Heat Pump	RXYQ_PB		
		RXYQ_T*	✓	✓
		RXLQ_T*	✓	✓
		RXYQ_X*	✓	✓
	Heat Recovery	REYQ_PB		
		REYQ_PC	✓	
		REYQ_T*	✓	
		RELO_T*	✓	
		REYQ_X*	✓	
Air-Cooled all voltages (1-Phase)	Heat Pump	RXYMQ_P		
		RXTQ_T*	✓	✓
Water-Cooled all voltages (3-Phase)	Heat Pump	RWEYQ_P		
		RWEYQ_PC	✓	✓
		RWEQT*	✓	✓
	Heat Recovery	RWEYQ_P	✓	
		RWEYQ_PC	✓	
		RWEQT*	✓	



Ventilation





Daikin's Outside Air Processing Unit can be integrated with a VRV system to provide outside air treatment and air conditioning in a single system to meet code requirements. It adjusts the temperature of air from outdoors using a fixed discharge temperature control reducing air conditioning load.

In addition to Outside Air Processing Units, we also offer Energy Heat Recovery units. The Energy Heat Recovery VAM-GVJU series units combines compactness, energy conservation, and extensive operation range of outdoor temperatures. This series provides higher enthalpy efficiency, due to the greatly enhanced performance of the thin heat exchanging element. Furthermore, improved external static pressure offers more flexibility for installation.



OUTSIDE AIR PROCESSING UNIT, FXMQ_MFVJU		ENERGY RECOVERY VENTILATOR, VAM-GVJU	
VRV Refrigerant Piping		Connectable	Not connectable
VRV Control Wiring			Connectable
High Efficiency Filter (MERV 8 and MERV 13)		Option	Not available
Ventilation System		Air supply	Air supply and Air exhaust
Power Supply	V/ph/Hz		208-230/1/60
Airflow Rate	CFM	635 988 1236	305/300/170 470/470/390 600/600/500 1200/1200/930

FXMQ_MFVJU

100% Outside Air Processing Unit



Outside Air
Integration Possible

Filter
Included

Concealed, Powerful, Compact,
Quiet, Fresh Air Quality


This unit provides a zoned, decentralized approach to conditioning outside air. This helps to reduce ductwork and installation time while increasing efficiency and flexibility. Both outside air treatment and space conditioning can be provided from one compact, flexible and efficient VRV system. VRV indoor units and outdoor air processing unit can be connected to the same refrigerant line, enabling enhanced design flexibility.

Features and Benefits


- » Available in three capacities, nominal 48, 72 and 96 MBH
- » The nominal airflow rates are 635, 988, and 1,236 CFM respectively
- » External static pressure capabilities of up to 1.03" W.G. allows for flexibility with duct work and filtration choices
- » The indoor unit is controlled to a set cooling and heating discharge air temperature allowing the flexibility to integrate with a standard Daikin indoor unit or duct directly to the space
- » A low profile design of only 18.5" high reduces the required installation space and can eliminate mechanical rooms or additional structural supports associated with traditional OA systems
- » Indoor Air Quality options include MERV 8 and 13 filters and filter boxes
- » Can be connected to all North American Daikin VRV systems
- » Connects directly and seamlessly into the Daikin local and centralized controllers

Operational Characteristics

When the suction air temperature is between 66°F and 109°F, the Outside Air Processing Unit operates in cooling, and when between 23°F and 59°F, it operates in heating. The OA processing unit will work in energy saving fan only between 59°F and 66°F.




BRC1E73
(option)



Applications

- » Hotel/conference centers
- » Schools
- » Retail shopping centers
- » Large open- plan offices
- » Churches



FXMQ_MFVJU SPECIFICATIONS		4 TON	6 TON	8 TON
Model Name		FXMQ48MFVJU	FXMQ72MFVJU	FXMQ96MFVJU
Power Supply	V/ph/Hz		208-230/1/60	
Rated Cooling Capacity	BTU/h	48,000	72,000	96,000
Rated Heating Capacity	BTU/h	30,000	47,000	59,000
Airflow Rate	CFM	635	988	1,236
Weight	lbs.	190		271
Height	in.		18-1/2	
Width	in.	29-1/4		54-3/8
Depth	in.		43-5/16	
Sound Pressure	dB(A)	42		47
External Static Pressure	in. Wg	0.88	0.96	1.03
Pipe Connections	Gas	in. 5/8	3/4	7/8
	Liquid	in. 3/8		
Protection Devices			Fuse	
External Finish			Fan Motor Thermal Protector	
Operating Range - Cooling	°F		Galvanized Steel Plate	
Operating Range - Heating	°F		66 DB/59 WB - 109 DB/90 WB	
Discharge Air Temp. - Cooling	°F		23 DB to 59 DB	
Discharge Air Temp. - Heating	°F		55-77	
			64-86	

Nominal Conditions:

Cooling Mode
 Discharge Set Temperature: 64°F DB
 Outdoor: 91°F DB, 82°F WB (68% RH)
 Pipe Length: 25 ft.
 Level Difference: 0 ft.



Heating Mode
 Discharge Set Temperature: 77°F DB
 Outdoor: 32°F DB, 27°F WB (50% RH)
 Pipe Length: 25 ft.
 Level Difference: 0 ft.

Note: Specifications are subject to change without notice.

FXMQ_MFVJU ACCESSORIES

Model Name	FXMQ48MFVJU	FXMQ72MFVJU	FXMQ96MFVJU
Navigation Remote Controller	BRC1E73		
Wireless Remote Controller	BRC4C82		
Madoka Remote Controller	BRC1H71W		
Button Sensor Kit	KRCSH2018-01		
Remote Sensor Kit	KRCS01-1B		
Wiring Adaptor PCB (interface with aux/primary heater, humidifier, OA damper/fan)	KRP1C74		
Group Control Adaptor PCB (connects to external BMS)	KRP4A71		
High Efficiency Filter Kit (MERV 13)	DACA-MQ48F131K	DACA-MQ96F131K	
High Efficiency Filter Kit (MERV 8)	DACA-MQ48F-8-1K	DACA-MQ96F-8-1K	

FXMQ_MFVJU INSTALLATION SPACE





Helping to Improve Indoor Air Quality and Energy Efficiency


The VAM Energy Recovery Ventilator is designed to help improve indoor air quality and reduce the overall HVAC system power consumption. This is achieved by providing fresh outside air and recovering waste heat from exhaust air leaving the conditioned space.

Features and Benefits


- » Provides energy-saving heat recovery ventilation via a new heat exchanger with high temperature and enthalpy recovery efficiency
- » Design flexibility thanks to high static pressure fans and the capability for use in a wide range of climates (5°F to 122°F DB and 80% RH or less)*
- » Wide range of functions such as independent operation, interlock with other HVAC systems, and automatic night purge to reduce cooling loads and increase energy savings
- » Interlocked simultaneous operation with VRV indoor units through a single controller
- » Auto mode switches the ventilation mode (total heat exchange mode to bypass mode) according to the operating status of the air conditioner system
- » Pre-cooling/heating control function to delay the start of ventilation during air conditioner start-up for higher energy savings
- » Supply and exhaust fresh-up operation modes to control pressure within a space
- » Filter sign and display reset notifies when filter changes are required
- » ESP as high as 0.76" W.G.
- » Sound levels as low as 25.5 dB(A) for sound-sensitive installation locations

* Performance characteristics certified to AHRI Standard 1060 are only applicable to the cooling and heating operating conditions specified in the performance table of this document.

- The cooling effectiveness shall be based on 95°F DB / 78°F WB for the entering supply air and 75°F DB / 63°F WB for the entering exhaust air, at a leaving supply airflow of both 100% and 75% of the rated airflow.
- The heating effectiveness shall be based on 35°F DB / 33°F WB for the entering supply air and 70°F DB / 58°F WB for the entering exhaust air, at a leaving supply airflow of both 100% and 75% of the rated airflow.




Layout example



Applications

- » Hotel/conference centers
- » Schools
- » Retail shopping centers
- » Large open-plan offices
- » Churches




VAM SPECIFICATIONS				VAM300GVJU	VAM470GVJU	VAM600GVJU	VAM1200GVJU
Mode	Airflow	Effectiveness Type					
Heating ¹	100%	Sensible	%	60	62	68	68
		Latent	%	46	48	42	42
	75%	Sensible	%	63	66	72	72
		Latent	%	53	55	47	47
Cooling ¹	100%	Sensible	%	60.6	63	68	68
		Latent	%	29	30	34	34
	75%	Sensible	%	63.9	67	72	72
		Latent	%	40	38	37	37
Power Supply		V/ph/Hz		208-230/1/60			
Airflow Rate (H/M/L)	Heat Exchange Mode	CFM		305/300/170	470/470/390	600/600/500	1,200/1,200/930
	Bypass Mode			305/300/170	470/470/390	600/600/500	1,200/1,200/930
Weight		lbs.		71	121	148	346
Height		in.		12-1/16	15-1/4	15-1/4	30-7/8
Width		in.		34-5/8	43-11/16		63-3/4
Depth		in.		31-1/2	32-3/4	47-13/16	
Sound Pressure @ 208V (H/M/L)		dB(A)		34.5/31.5/21.5	40/37/33	40.1/37/33.1	43/39/35
External Static Pressure (H/M/L)		in. Wg		0.64/0.26/0.16	0.73/0.39/0.33	0.76/0.34/0.32	0.56/0.24/0.16
External Finish		Galvanized Steel Plate					
Insulation Material		Self-Extinguishing Urethane Foam					
Connection Duct Diameter		in.		8	10	14	
Ambient Conditions*		A		5°F ~ 122°F DB 80% RH or less			

*AHRI 1060 Performance characteristics certified to AHRI Standard 1060 are only applicable to the specified cooling and heating operation conditions, as specified within the performance table in this document.


¹Note: Certified in accordance with the AHRI ERV Certification Program, which is based on AHRI Standard 1060. Certified units may be found in the AHRI Directory at www.ahridirectory.org. Performance characteristics certified to AHRI Standard 1060 based on the following conditions:

- » The cooling effectiveness shall be based on 95°F DB / 78°F WB for the entering supply air and 75°F DB / 63°F WB for the entering exhaust air, at a leaving supply airflow of both 100% and 75% of the rated airflow.
- » The heating effectiveness shall be based on 35°F DB / 33°F WB for the entering supply air and 70°F DB / 58°F WB for the entering exhaust air, at a leaving supply airflow of both 100% and 75% of the rated airflow.

VAM-GVJU INSTALLATION EXAMPLE



Heat exchanger with high temperature and enthalpy efficiency



ACCESSORIES

Model Name	VAM300GVJU	VAM470GVJU	VAM600GVJU	VAM1200GVJU
Navigation Remote Controller*		BRC1E73		
Madoka Remote Controller		BRC1H71W		
PCB Adaptor for Humidifier		KRP50-2		



Hot Water Solutions



Daikin **Mega-Q**

All-Electric Hot water Generation System

Introducing Daikin *Mega-Q*

Hot water is used in everyday activities. In North America, gas, oil, electric, and steam boilers have been leveraged traditionally to generate hot water. Air-to-water heat pump technology offers an all-electric alternative for generating hot water, reducing dependence on fossil fuel systems. Daikin's inverter-driven Daikin *Mega-Q* system provides an all-electric hot water solution, making it an ideal choice for commercial buildings with large volume non-potable hot water demand.

Features and Benefits

- » All-electric heat pump technology for non-potable hot water generation in commercial applications.
- » Dependable hot water generation at ambient temperatures from -4°F DB to 109°F DB (from -20°C DB to 43°C DB).
- » Customizable high-leaving water temperatures from 140°F to 194°F (from 60°C to 90°C) with inlet water temperatures from 41°F to 176°F (from 5°C to 80°C).
- » Year-round high efficiencies with up to 4.6+ COP thanks to Daikin's inverter heat pump and cascade technologies.
- » Scalable and modular system design allows for up to 6 Daikin *Mega-Q* systems to connect to the same hydronic loop, achieving total nominal capacity of 720 MBH.
- » Flexible application design with a vertical separation of up to 65 ft. between the heat source unit and the cascade unit.
- » Modular and compact system design enables installation indoors or outdoors.
- » Built-in variable-speed water pump increases waterside system efficiencies compared to single-speed pumps and can handle water flow rates of up to 3.8 gallons per minute (GPM).



*Based on heating conditions at the outdoor temperature of 77°F DB/69.8°F WB, the outlet water temperature of 149°F, and the inlet water temperature of 75.2°F.



* Complete warranty details available from your local dealer/contractor or at www.daikincomfort.com. Daikin *Mega-Q* heat source unit (RXHWQ120MQTJA) and cascade unit (BWLP120TJU) come with a 5-Year Parts Limited Warranty where installation and commissioning requirements are satisfied. Other limitations and exclusions apply.

Daikin Mega-Q is an all-electric hot water generation system that is built upon 3 main components—heat source unit, cascade unit, and tank controller kit—providing some attributes of a central hot water generation system but with the flexibility of indoor or outdoor installation.

Mega-Q offers all-electric hot water generation for various non-potable water applications, such as multi-family buildings, offices, hotels, schools, and other large commercial applications.

This innovative system can supply non-potable hot water to commercial buildings even in outdoor ambient temperatures as low as -4°F. The dual refrigerant circuit split system design features Daikin's Inverter-driven heat pump technology. Coupled with an inverter-driven cascade unit, the *Mega-Q* supports reliable performance with customizable high-leaving hot water temperatures ranging from 140°F to 194°F with inlet water temperatures from 41°F to 176°F.

The Daikin *Mega-Q*:

1



REFRIGERANT
PIPING

2



HYDRONIC
PIPING

3



Heat Source Unit

- » High efficiency inverter air-cooled heat pump
- » R-410A refrigerant
- » Cascade unit – Refrigerant to water
- » Built-in inverter water pump
- » R-134A refrigerant

The heat source component of *Mega-Q* should be used for heating water for non-potable use only, not for other applications such as but not limited to space heating or cooling.

Tank Controller Kit

- » Connects to the hot water storage tank using three water temperature sensors
- » Controls up to 6 *Mega-Q* systems on the same hydronic loop


Note: Hot water storage tank is field supplied.

Flexible Installation




- » The heat source unit and cascade unit are installed outside side by side.

2



- » The cascade unit can be installed up to 65 feet away from the heat source unit, with the option to place it indoors.


3



- » Both the heat source unit and cascade unit can be installed indoors. Note that the heat source unit must be ducted to the outside.

Daikin Mega-Q

How it Works



+ Not required for operation of the Daikin *Mega-Q* system. Field supplied if used in applications.

Dual refrigerant circuit achieves high-temperature hot water output and high-efficiency operations.

Daikin *Mega-Q* takes advantage of the excellent low ambient temperature characteristics of R-410A combined with high temperature boiling characteristics of R-134A to generate high-temperature water up to 194°F.



RXHWQ120MQTJA + BWLP120TJU				
Sound (A scale)	Db	55 (Winter 59)		
Unit Model Name		Heat Source Unit		Cascade Unit
Model Name		RXHWQ120MQTJ*		
Power Supply		3 Phase 208/230V 60Hz		
Casing Color		Ivory White (5Y7.5/1)		
External Dimensions (H x W x D)		In. (mm)	66-11/16 (1694) x 48-7/8 (1242) x 30-3/16 (767)	60-1/16 (1525) x 35-3/16 (893) x 30 (762)
Heat Exchanger	Evaporator	Cross Fin Coil		Plate Heat Exchanger
	Condenser	Winding Spiral Tube Heat Exchanger		
Compressor	Model	Hermetically Sealed Scroll Type		
	Starting System	Soft Start (Inverter)		
	Motor Output	kW	(4.4 + 4.4)	(4.5 + 4.5)
Fan	Model	Propeller Fan		N/A
	Motor Output x Number	kW	0.75 x 2	N/A
	Air Flow	cfm (m ³ /min)	8228 (233)	N/A
	Drive System	Direct Drive		N/A
Water Pump		N/A		Non-Self-Priming Canned Pump
Connecting Pipe	Heat Source Unit	Liquid Side Pipe	in. (mm)	1/2 (12.7) C1220T (Brazed Connection)
		Gas Side Pipe	in. (mm)	1-1/8 (28.6) (Brazed Connection) *1
	Heat Source Unit Cascade Unit	Liquid Side Pipe	in. (mm)	1/2 (12.7) C1220T (Brazed Connection)
		Gas Side Pipe	in. (mm)	7/8 (22.2) C1220T (Brazed Connection) *1
	Cascade Unit	Liquid Side Pipe	in. (mm)	N/A
		Gas Side Pipe	in. (mm)	N/A
		Circulation (water) Pipe	in. (mm)	N/A
		Outlet (hot water) Pipe	in. (mm)	N/A
	Weight	lb. (kg)	695 (315)	639 (290)
	Safety Device		High pressure switch, Fan driver overload protector, Overcurrent relay, inverter overload protector	
	Defrost Method		Deicer	N/A
	Refrigerant	Refrigerant Name		R-410A
		System Charge	lbs. (kg)	18.1 (8.2)
		Control	Electronic Expansion Valve	
	Design Pressure	High Pressure	PSIG (Mpa)	478 (3.30)
		Low Pressure	PSIG (Mpa)	320 (2.21)

*1 The pipe diameter on the gas side of the heat source unit is different between the heat source unit and the cascade unit. When arranging piping, procure with the gas piping diameter between the heat source unit and the cascade unit.

UNIT MODEL NAME			TANK CONTROLLER KIT
Model			BRP26B2VJU
Controller Box	Power Supply		1-Phase 208/230V 60 Hz
	Exterior		Ivory White (5Y7.5/1)
	Dimensions	H x W x D	17-11/16(450) x 11-13/16(300) x 3-15/16(100)
	Weight	lbs. (kg)	23 (10.5)
External Output			Operation ON Malfunction
External Input			Operation ON Demand Control Hot Water Set Temperature Switch
Attached Sensor			Thermistor for hot water (Screw Type) x 3
Accessory			Remote Controller




Controls



What are your choices?


Zone Controllers



Multi-Zone Controller



Interface Solutions



External Equipment Control



Adaptors



Cloud Monitoring





VRV Control Systems Overview



Building/Home Automation System



Remote access



HERO Pro Edge

Intelligent Manager
(DCM601B71)



with BACnet™ Server Gateway Option (DCM014A51) or with Web IF (HTTP) software option (DCM007A51)



Interface for
use in BACnet
(DMS502B71)



Interface for
use in LonWorks®
(DMS504C71)



DIII-Net/BACnet
MS/TP Communication
Adaptor
(DTA118A72)



DIII-Net/Modbus®
Adaptor
(DTA116A51)

Interface Solutions

DIII-NET (Communications Transmission)

DIII-NET, Daikin's unique communication transmission system, links indoor units and various other building equipment in accordance with applications, scenarios and conditions and transmits vast amounts of information between them.


Limitations may apply to some models and functions.
Please contact your local sales office for details.

Note: BACnet is a registered trademark of the American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE). LonWorks is a trademark of Echelon Corporation registered in the United States and other countries. Modbus is a registered trademark of Modicon.

- DIII-NET Line
- BACnet/Ethernet or LonWorks network communication line
- RS485 Modbus line
- P1P2 line
- Connection line

Location
units
ent –
ale
em.

through BACnet™ MS/TP, Modbus®, or cloud integration



Zone Controllers and Integration



Third-party Thermostat

DKN Plus Interface



Daikin One Touch



Daikin One+ Smart Thermostat



Madoka Remote Controller



Navigation Remote Controller (BRC1E73)
(R-410A)



DKN Cloud Wi-Fi Adaptor




Wireless Remote Controller



Navigation Remote Controller (BRC1NRV71)

R32





BRC1E73 (R-410A), BRC1NRV71(R-32)

Navigation Remote Controller

The *Navigation* Remote Controller has been enhanced to meet the configuration requirements of Daikin's VRV indoor units. The BRC1E73 (R-410A), BRC1NRV71 (R-32) provides all the great features and options the market requires. The configurable display and operation buttons will provide as much or as little control as the project requires.

Features and Benefits

» Basic Operation


- On/Off, operation mode, set-point
- Up to 5 fan speeds selectable (enhanced)
- Airflow direction (enhanced)
- Individual louver airflow direction
- Dual airflow
- Auto-draft prevention (prevents air blowing directly on occupants)

» Function


- Configurable display — Detailed, Standard, and Simple
- Dual or single cool and heat set-points for occupied periods
- Independent setback set-points for unoccupied periods
- Automatic Setback by occupancy sensor
- Automatic Off by occupancy sensor
- Unwanted buttons/operation modes can be disabled
- Set-point range limitation
- Individual button prohibits/lockout
- Auto-changeover for Heat Recovery and Heat Pump systems with dual or single set-points
- Self-cleaning filter panel
- Automatic adjustment for Daylight Savings Time (DST) (enhanced)
- Built in 7, 5+2, 5+1+1, and 1 (everyday) schedule with up to 5 actions per day with independent cooling, heating and setback set-points

» More Features

- Backlit display
- Room temperature sensor
- 12/24 hour clock
- Fahrenheit/Celsius selectable
- English/French/Spanish languages selectable



Auto-changeover



- Remote control group - up to 16 indoor units
 Automatic changeover is available for Heat Pump system and Heat Recovery systems. The set-point for cooling and heating are configurable with a minimum differential of 0 to 7°F or single set-point. The changeover is automatically controlled to happen in either of the following two cases:

1. **Case 1:** Changeover at the primary changeover temperature after the guard timer expires.
 - In default, the primary changeover set-point is 1°F above cooling set-point or 1°F below heating set-point, which is configurable between 1°F – 4°F.
 - In default, the guard timer is 60 minutes, which is selectable among 15, 30, 60 (default) or 90 minutes.
 - The initiation of guard timer is built in to help prevent frequent changeover which may cause energy loss.
2. **Case 2:** Changeover at the secondary changeover temperature.
 - In default, the secondary changeover temperature is 1°F above the primary changeover temperature for cooling or 1°F below the primary changeover temperature for heating, which is configurable between 1°F – 4°F.
 - Case 2 will happen while the guard time is active in case 1.



Navigation Remote Controller (continued)

Configurable Display Mode – Detailed, Standard, Simple

DISPLAY MODE	DETAILED	STANDARD	SIMPLE NEW
Display Image			
On/Off status on LED (LED blinks when an error occurs)	■	■	■
Mode	■ 1	■ 1	■ 1
Set-point (Dual/Single)	■ 2	■ 2	■ 2
Room temperature	■	■	■
Fan speed	■ 3	■ 3	■ 3
Airflow direction (when a louver is available)	■		
Day and Time	■ 3		
Status icon	■ 3	■ 3	
Key lock icon	■	■	
Error message	■	■	

¹ OFF can be displayed instead of the operation mode while the unit is turned off with the field setting

² Can be removed from the display while the unit is turned off with a field setting

³ Can be removed from the display with a field setting

On/Off Display Option




Optional Face Decals – Hides unnecessary (locked/prohibited) buttons

USED WITH	SINGLE SET-POINT MODE			DUAL SET-POINT MODE		
	BRC1E72RM	BRC1E72RF	BRC1E72RMF	BRC1E72RM2	BRC1E72RF2	BRC1E72RMF2
On/Off	■	■	■	■	■	■
Mode	■			■	■	■
Fan			■			
Up, Down	■	■	■	■	■	■
Left, Right				■	■	■
Menu/Ok						
Cancel						


Clear display

- » Backlit display
 - Backlight helps operating in dark rooms.
- » Dot matrix display
 - A combination of fine dots enables various icons.
 - Large text display is easy to see.



Simple operation

- » Large buttons and arrow keys
 - Large buttons and arrow keys enable easy operation. Basic setting such as fan speed and temperature can be intuitively operated. For other settings just select the function from the menu list.



Individual Controllers (cont.)




Navigation Remote Controller (continued)


Energy saving

» Automatic Off by occupancy sensor[†]

- The indoor unit will turn off when it is determined that the room is unoccupied after a specified time has elapsed.
- Can be used in conjunction with the Auto Setback by sensor function



Automatic Off energy savings



College classroom sample (a summer Monday case)


1) 8:30 ON

The first period starts and the air conditioner starts the cooling operation.




2) 10:30 OFF

In the second period, the classroom is unoccupied and the air conditioner stops.




3) 13:00 ON

When the third period starts, operation starts again.




4) 15:00 OFF

After the third period, the classroom becomes vacant again and the air conditioner stops.




» Auto Setback by sensor[†]

- The cooling and heating set-points will gradually relax (configurable) internally when the room is determined to be unoccupied.
- The internal set-point will return to the original set-point when room occupancy is detected.



Automatic setback energy savings





Comfort

» Individual airflow direction[†]


- Airflow direction of each of the four air outlets can be controlled individually.
- (Positions 0 to 4, Swing, and No individual setting are selectable.)

» Auto airflow rate[†]

- Airflow rate is automatically controlled in accordance with the difference between room temperature and set temperature.

[†] Only available for VRV4-Way Flow Ceiling Suspended type FXUQ_P series and Ceiling Mounted Cassette (Round Flow with Sensing) type FXFQ_T series.

Individual airflow direction





BRC1H71W - *Madoka* Remote Controller


- » Easy Commissioning
 - Settings and configuration can be copied to and from the app or controller and applied to other controllers using Bluetooth® BLE technology
 - Selective display mode: Text, Icon, and Scale display
 - Field settings are categorized based on the application
 - Language: English, French, Spanish
 - Supports both Fahrenheit and Celsius
- » Basic Control functions
 - On/Off, operation mode, set-point
 - Up to 5 fan speeds selectable
 - Louver direction
 - Auto-draft prevention
- » Advanced functions
 - Setback logic
 - Set-point range limitation
 - Function Prohibition



Madoka
Remote Controller

DTST-ONE-ADA-A - Daikin *One+* Smart Thermostat for VRV, SkyAir, Single Zone and Multi-Zone System

- » A cloud-connected smart thermostat to control indoor temperature, humidity, and air quality.
- » Features
 - Capacitive multi-touch display with easy rotational dial and light pipe indication
 - Wi-Fi enabled smart thermostat with smartphone control, voice control and OTA update capability
 - Intelligent energy management with schedule and configurable energy and comfort functions
 - Auxiliary heater control (primary/secondary/emergency heat)



Daikin *One+* Smart
Thermostat

DTST-TOU-ADA-A - Daikin *One Touch* Smart Thermostat

- » Simple, elegant industrial design
- » Capacitive touchscreen user interface
- » Wi-Fi-enabled smart thermostat with iOS and Android app control
- » Voice control by *Amazon Alexa* and *Google Assistant*
- » Technical Specifications
 - Capacitive touch screen
 - Backlit, 3.5 inch MVA TFT LCD display
 - Wi-Fi
 - Bi-directional communications protocol for controlling HVAC system



Daikin *One Touch*
Thermostat

AZAI6WSCDKA - DKN Cloud Wi-Fi Adaptor

- » Remote control of VRV indoor units from iOS/Android smartphone app
- » Voice control capability through *Google Assistant* and *Amazon Alexa*
- » Provides Cloud API integration option for hotel and home automation integration developers
- » Features
 - On/Off
 - Mode
 - Error alert
 - Leveled user authority
 - Set-point
 - Fan speed
 - Room temperature
 - Louver position



DKN Cloud
Wi-Fi Adaptor



BRC4C82/BRC7E818/BRC7E83/BRC7E830 - Wireless Remote Controller

» The same operation modes and settings as with wired remote controllers are possible.

» Features

- On/Off
- Fan speed adjustment
- Operation mode
- Louver position adjustment
- Single set-point
- Reports system malfunctions

» A compact signal receiver unit (separate type) to be mounted into a wall or ceiling is included.

- The Ceiling Suspended and Wall-Mount indoor units use signal receivers that are mounted in the indoor unit.

* Wireless remote controller and signal receiver unit are sold as a set.



Wireless remote controller*



Signal receiver unit (separate type)*

INDIVIDUAL CONTROL CAPABILITIES

Communications	2 Wire / DIII-Net	2 Wire / DIII-Net	Infrared	2 Wire/ DIII-Net			
°F/°C Selector	●	●	●	●	●	°F only	●
Display		Blacklight LCD Display	Blacklight LCD Display	Multi-touch capacitive color display	Multi-touch capacitive color display		Backlight LCD Display
Room temperature display	●	●	●	●	●		●
Schedule and setback capabilities (with Time and Date display)	●	●	●	●	●		
User restriction options		●	●				●
On/Off, Operation mode, Set-point, Fan speed	●	●	●	●	●	●	●
Louver position adjustment	●	●	●	●	●	●	●
Reports system malfunctions	●	●	●	●	●	●	●
Space temperature sensor	●	●	●	●	●		●
Simultaneous operation with Daikin multi-zone controllers	●	●	●	Monitor only	Monitor only	●	●
Simultaneous operation with BACnet™ and LonWorks®	●	●	●	Monitor only	Monitor only	●	●
Group control capacity	Up to 16 indoor units*	Up to 16 indoor units	Up to 16 indoor units	Up to 16 indoor units	Up to 16 indoor units	Up to 16 indoor units	Up to 16 indoor units

* with future software update

Summary

REMOTE CONTROLLER COMPATIBILITY WITH VRV INDOOR UNITS

	FXFQ_TA	FXZQ	FXUQ	FXDQ	FXSQ	FXMQ	FXHQ	FXAQ	FXL(N)Q	FXTQ	FXEQ
Navigation remote controller (Wired remote controller)	■	■	■	■	■	■	■	■	■	■	■
Madoka Remote Controller	■	■	■	■	■	■	■	■	■	■	■
Wireless remote controller (Installed type signal receiver unit)		■						■	■		
Wireless remote controller (Separate type signal receiver unit)				■	■	■			■		
DKN Cloud Wi-Fi Adaptor	■	■	■	■	■	■	■	■	■	■	■

Summary

REMOTE CONTROLLER COMPATIBILITY WITH VRV INDOOR UNITS

	FXFA	FXTA	FXMA	FXSA
Navigation remote controller (Wired remote controller) – (R-32)	■	■	■	■



The Daikin *HERO* Pro Edge is a cloud-based VRV central controller that offers real-time remote control and monitoring, advanced analytics, and dashboard. The Daikin *HERO* Pro Edge can monitor and control multi-split, Daikin Rooftop Unit (RTU), Dedicated Outside Air Unit (DOAS) and non-Daikin systems. Daikin *HERO* Cloud Services is based upon a recurring license fee to access site information. The Daikin *HERO* Pro Edge includes first-year access to Daikin *HERO* Cloud Services for monitoring and control, licenses can be renewed in 1-year, 3-year or 5-year increments.

Easy Operation

- » Remote monitoring for Daikin VRV outdoor and indoor unit operation data across multiple sites
- » Accessible any time and from anywhere through the Daikin *HERO* Cloud Services web page or app
- » Intuitive, customizable dashboard provides quick status of connected units and sites
- » Animated piping diagram based on system mode of operation

Advanced Control Logic

- » Independent cool and heat setpoints or single setpoint in the occupied period
- » Independent setback setpoints in the unoccupied period
- » Weekly schedule with timed override
- » Auto changeover with configurable methods

Operational Data

- » Operation data are stored in the Daikin *HERO* Cloud Service in 1 minute intervals and stored for 5 years with the Daikin *HERO* Pro Edge activation.
 - Indoor unit and outdoor unit operation data
 - BACnet™ Client objects
 - WAGO® I/O system data
- » Operation data can be viewed in the Daikin *HERO* Cloud Services or downloaded as CSV files

Mini BMS Solution with Software and Hardware Options

- » Auto changeover, interlock, schedule and emergency stop for facility management.
- » DI, DO, AI, AO points integrated via the WAGO® I/O System
- » BACnet points (AI, AO, AV, BI, BO, BV, MSI, MSO, MSV) integrated with the Daikin *HERO* Pro Edge BACnet Client Option

Facility Management and Billing

- » Remote web or app access
- » Continuous commissioning by remotely adjusting the outdoor unit field settings
- » Tenant billing with the Daikin *HERO* Pro Edge PPD option
- » Demand control capabilities to set setpoint shift, control thermo-on/off or outdoor unit capacity based upon schedule setting

Prediction logic and Notifications

- » Utilizes predictive algorithms to alert users of potential failures
- » Prediction alerts can be accessed on the Daikin *HERO* Cloud Services dashboard and are also distributed through email



Internet

BACnet / IP

DOAS and other
third-party systemRemote
monitoring

3 DO
Fan
8 Di
kWh meter



RS485



WAGO I/O

Lighting
Fan
Pump
Sensor

Up to 64 indoor units /
7 outdoor unitsUp to 64 indoor units /
7 outdoor unitsAdd up to 6 additional
DIII-Net systems. Each
DIII-Net system can
support up to a
maximum of 64 indoor
units / 7 outdoor units.

512 indoor units / 56 outdoor units

Advanced Multi-Zone Controllers – Daikin *HERO* Pro Edge (cont.)



- » The Daikin *HERO* Cloud Service enables remote management for the Daikin VRV system with other general equipment integrated into the Daikin *HERO* Pro Edge so they can be accessed from the daikinhero.com or the Daikin *HERO* Cloud Services App.
- » The Daikin *HERO* Cloud Service is a powerful remote service tool where the Daikin VRV operation data is stored in the cloud for the last 5 years can be downloaded through the web function. Trend graphs of the system operation can be created allowing the service technicians to analyze and diagnose the system without visiting the job site. This feature will provide

the service technician with a view into the Daikin VRV system operation and performance prior to or after an abnormal issue has occurred.

- » Automatic Alert/Error e-mail enables prompt response by service personnel based on timely and precise knowledge of what happened in the system at the remote site.
- » Access to data prior to and after alarm generation as the error marker with time stamp indicates when the error occurred. Also, the trend charts has the ability to trend up to 40 data points at a time for easy diagnostics.






Tenant Billing (PPD Option)

The PPD (Power Proportional Distribution) option records all the operation duration, room temperature, electronic expansion valve opening ratio data, etc. Based on the recorded data, the energy consumption of the Daikin VRV system is proportionally calculated for each indoor unit. The calculated data can be used for tenant billing.

Features

- » PPD data can be downloaded using the Daikin *HERO* Cloud Service
- » Automated Tenant reporting with smart notification to the facility manager
- » Configure output of the Tenant Reports
 - Allows for company logo and info to be added.
 - Selectable start and end period
 - Provide cost per kWh, admin fees and determine if heating usages should be excluded from billing.
 - Separated cooling and heating energy calculation.
 - Select the type of file output.
- » Send the tenant report by email.



* Pulse power meter that provides an output of 1 pulse per 1 kw and has a width of 40-400 milliseconds.

Set Up Monthly Site and Tenant Reports

Site logo: 

Choose the monthly period for your Site and Tenant Reports:

Parameters to include:

- % ODU Consumption
- % kWh
- Add Tax
- Add Admin Fee

% ODU Consumption: % kWh:

It is possible to include up to six time slots with corresponding hourly energy consumption costs.

Export formats:


Site Report: PDF CSV

Tenant Report: PDF CSV

Send report to:

Report Reviewer:

Report Receivers:






BACnet™ Client Option

The Daikin *HERO* Pro Edge offers an advanced and cost-effective solution for Building Management Systems (BMS) applications. The *BACnet* Client Option provides more flexibility to enhance the Daikin *HERO* Pro Edge's function as a mini BMS. With this option, the Daikin *HERO* Pro Edge is able to manage third party DOAS and other third party equipment through the *BACnet*/IP protocol. By registering equipment connected to a *BACnet* server as management points in the Daikin *HERO* Pro Edge, you can now monitor and control the equipment from the Daikin *HERO* Cloud Service.

Features and Benefits:

- » Cost-effective BMS solution
- » Direct connection on Daikin *HERO* Pro Edge using the *BACnet*/IP Protocol
- » Integrated control on Daikin VRV system and Daikin Applied System
- » Monitors and controls third party equipment
- » Daikin Light Commercial rooftop units (RTU) with *iLINQ* controller. Monitor and control Daikin Light Commercial rooftop units (RTU) with *iLINQ* controller.

***BACnet* Client DGE009A71 can manage up to 10 *BACnet* devices; while the *BACnet* Client DGE009A72 can manage up to 50 *BACnet* devices.**



Object Types

- » Analog Input, Analog Output, Analog Value
- » Binary Input, Binary Output, Binary Value
- » Multi-State Input, Multi-State Output, Multi-State Value

Applications

- » Sensors, Pumps, Lights, Fans
- » AHU, Alarms, DOAS, Elevator

Advanced Multi-Zone Controllers – Intelligent Touch Manager (iTM)

DCM601B71 - *intelligent Touch Manager (iTM)*

The *intelligent Touch Manager (iTM)* is an advanced multi-zone controller that provides the most cost-effective way to control and monitor the Daikin VRV system.

Centralized and Advanced VRV Control

Up to 64 Indoor Unit Groups (128 actual Indoor Units) can be monitored and controlled with individual Cool and Heat Set-points, Set-point Range Limitation, Setback Set-points, and Auto changeover to meet your expectations and project requirements. Up to 512 Indoor Unit Groups (1024 actual Indoor Units) can be monitored and controlled with the addition of up to 7 optional *iTM* Plus Adaptors (DCM601A72).

Built-in Service Tool with Remote Access

- » Operation data are stored in the *iTM* for the last 5 days:
 - Indoor unit and outdoor unit operation data
 - BACnet™ Client objects
 - WAGO® I/O system data
- » Operation data can be exported through a USB drive or through the *iTM* web browser remotely
- » BMS can monitor the *BACnet* objects of indoor unit and outdoor unit operation data with the *BACnet* Server Gateway Option activated

Ancillary Equipment Control

Integrates and/or interlocks sensors, switches, dampers, fans, pumps, and lighting with Daikin indoor units.

Web Access and Alert E-mail

Allows daily remote monitoring and control with the Web/E-mail function that can be accessed via the facility's Local Area Network or your Internet connection. Sends Error E-mail to mobile devices with the Web/E-mail function.

Tenant Billing

Determines energy consumption of shared condensing units based upon tenant (Indoor Unit) demand using the PPD Software option (DCM002A71).

Features

- » 10.4" LCD touch screen, USB drive
- » Advanced, scalable and cost-effective management system
 - Up to 650 points (max 512 indoor unit groups (1024 indoor units)
 - Floor plan layout view

Functions

- » Dual set-points or Single set-point in occupied or Setback in unoccupied
- » Set-point Range Limitation
- » Scheduling (7 day, Weekday-Weekend, Weekday-Saturday-Sunday, Everyday)




 **intelligent Manager**

- » Scheduling (7 day, Weekday-Weekend, Weekday-Saturday-Sunday, Everyday)
- » Optimum Start and Timed Override
- » Advanced Auto changeover
 - Applicable to both VRV Heat Pump and Heat Recovery systems
 - Fixed, Individual, Average and Vote methods
- » Demand Response
 - Interlock the digital input signals to provide automatic demand control functions
 - Multiple demand control functions: Indoor unit set-point shift control, Indoor unit forced thermo-off, Indoor unit on/off control and outdoor unit's capacity demand limit control
- » WAGO I/O
 - Monitor and control 3rd party equipment with DI, DO, AI and AO signals
 - Up to 512 management points
 - Interlock function with indoor units and ancillary equipment
- » Power Proportional Distribution Option (DCM002A71)
 - Calculates apportionment of outdoor unit's total power consumption to individual units on the system
- » *iTM BACnet* Client Option (DCM009A51)
 - Enabling the *BACnet* Client option allows the *iTM* to use the *BACnet*/IP protocol
 - Allows for full monitoring and control of 3rd party *BACnet* capable equipment
 - Up to 512 *BACnet* management points
- » *iTM BACnet* Server Gateway Option (DCM014A51)
 - Enable BMS to control indoor units and/or monitor outdoor unit operation via *BACnet*/IP (up to a total of 128 *BACnet* device IDs and 4000 *BACnet* objects)
 - Virtual router function embedded that enables individual and configurable *BACnet* device ID for each indoor unit group address and each outdoor unit.
- » Web (HTTP) Interface Option (DCM007A51)
 - The *iTM* Web IF (HTTP) software provides a building automation system or a home automation system the ability to monitor and control the VRV indoor units over the HTTP protocol

Advanced Multi-Zone Controllers – Intelligent Touch Manager (iTM) (cont.)



iTM System Overview






DCM009A51 - *iTM BACnet™* Client Option

The *Intelligent Touch Manager (iTM)* offers an advanced and cost-effective solution for Building Management Systems (BMS) applications. The *iTM BACnet Client Option* (DCM009A51) provides more flexibility to enhance the *iTM*'s function as a mini BMS. With this option, the *iTM* is able to manage DOAS systems and other third party equipment through the *BACnet/IP* protocol. By registering equipment connected to a *BACnet* server as management points in the *iTM*, you can now monitor and control the equipment via the *iTM*.

Features

- » Cost-effective BMS solution
- » Direct connection on *iTM* using the *BACnet/IP* Protocol
- » Integrated control on Daikin *VRV* system and Daikin Applied System
- » Monitors and controls third party equipment
- » Easy commissioning with pre-engineering Preset Tool
- » Easy monitoring with preconfigured GUI

Intelligent Manager with BACnet™ Client Option



Object Types

- » Analog Input, Analog Output, Analog Value
- » Binary Input, Binary Output, Binary Value
- » Multi-State Input, Multi-State Output, Multi-State Value

Applications

- » Simple I/O: Sensor, Pump, Light, Fan
- » Multi-State Objects: AHU, Alarm, Elevator



DKN Plus Interface

The DKN Plus Interface (AZAI6WSPDKC) enables the energy-efficient control of Daikin air conditioners by a third-party thermostat or an automation system. With this interface, third-party devices or systems can control the VRV, SkyAir, and Daikin Single/Multi-Zone indoor units through Cloud API, Modbus®, BACnet™ MS/TP, or thermostat relay contacts. This interface can be commissioned with ease through the DKN Cloud North America (NA) app via Bluetooth® Low Energy (BLE).



Features

» Versatile interface adaptor that can integrate with a third-party thermostat/BMS through multiple approaches:

- Cloud API
- Modbus
- BACnet MS/TP
- Backup thermostat G/Y/W (Fan/Cool/Heat) relay control through thermostat wire:
 - Automatically disables thermostat relay logic when cloud API connection detected
 - Advanced control logic to maximize indoor unit efficiency

» Easy commissioning with the BLE configuration app (DKN Cloud NA app)

» Indoor unit control and monitoring points*

- On/Off
- Set-point
- Room temperature
- Mode (Auto, Cool, Heat, Fan, Dry)
- Fan speed
- Louver position
- Error code
- Interlock control with indoor unit On/Off


» Auxiliary Heater Control

- Auxiliary heater controlled as a secondary heat source

*Availability depends on indoor unit model

Integration with Building Management System (BMS) or Home Automation System (HAS)

» Integration through Modbus or BACnet MS/TP






System Diagram

Integration with 3rd party thermostat

» The adaptor provides 4 different approaches for a 3rd party thermostat to control the Daikin indoor units



» Integration through Cloud API



Modbus is a registered trademark of Schneider Electric USA, Inc.

BACnet is a trademark of ASHRAE.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc., and any use of such marks are under license.




DCM014A51 - *iTM BACnet™ Server Gateway Option*

The *intelligent Touch Manager (iTM)* is capable of serving as a *BACnet* interface for Building Management System (BMS) integration. With the *iTM BACnet Server Gateway Option* (DCM014A51), the *iTM* provides BMS integrators with the ability to monitor and/or control the *VRV* indoor and outdoor units, eliminating the need for an additional hardware interface. Moreover, with the latest software update to the *iTM 2+* (v2.06), the *iTM* is able to serve as a service tool to access indoor and outdoor unit operation data. With the *iTM BACnet Server Gateway Option*, the operation data points for both the IDU (indoor unit) and ODU (outdoor unit) are also available to the BMS through *BACnet*.


Features

- » Additional service data points are now available*:
 - 6 new IDU service data points
 - 9 new common ODU service data points and
 - 22 new service data points for each ODU module
- » Direct connection on *iTM* using the *BACnet/IP* Protocol
- » Supports Change of Value (COV) notifications to the BMS
- » Configurable as a *BACnet* foreign device if a BBMD exist on a different subnet within a *BACnet* network
- » *BACnet virtual router* function implemented:
 - Individual *BACnet* device ID assigned to each indoor unit group address and each outdoor unit
 - Indoor unit group names created in the *iTM* are visible on the BMS
- » Easy commissioning using CSV file
 - Available objects can be configured for each indoor unit
- » Independent heating and cooling set-points for occupied and unoccupied periods
- » Individual min/max Set-point Range Limitation for heat and cool modes
- » The *iTM*'s auto changeover, set-point range limitation, setback, dual set-point logic and schedule can be accessed by the BMS
- » Up to 128 Device IDs (including both indoor units and outdoor units) and up to 4000 *BACnet* objects can be monitored and controlled by BMS.
 - When the IDU/ODU operation data is enabled a total of 128 devices and 4000 *BACnet* points are available
- » Up to 7 *iTM* Plus Adaptors can be connected to an *iTM* for a total of 8 DIII-Net ports





Powerful Service Tool with Indoor and Outdoor Unit Operation Data Points



- » When a problem occurs, the BMS integrators and Service Technicians can start troubleshooting remotely immediately before going to the site.
- » Indoor and outdoor operation data trending* by Third party BMS can benefit the VRV service process.

*BMS programming needed

Enhanced BMS Integration Solution for Indoor Unit Operation




Individual Device instance number for each indoor unit (Configurable)

Device ID (1:1-00) = 531100 Device ID (1:1-01) = 531101

Object instance number repeated for every indoor unit point

Occupancy Mode = MO 1 (All indoor units)
Unit On Off Status = BI 2 (All indoor units)

Advanced iTM BACnet™ Server Gateway Points






DCM007A51 - ITM Web (HTTP) Interface Option

- » Building or Home Automation Interface based on HTTP protocol
- » Interface between the DIII-Net and the HTTP automation work station.
- » Monitor and Control up to 512 Indoor units groups

DMS502B71 - Interface for use in BACnet™

- » *BACnet*: Building Automation and Control Networks
 - Standard open protocol based on ANSI/ASHREA Standard 135
- » Monitor/Control indoor unit's points
- » Monitor/Control up to 256 indoor units groups (512 indoor units)
- » Manage up to 4 DIII-Net systems
 - Option Board (DAM411B51) required

BACnet, LonWorks and Modbus® Interface overview



DMS504C71 Interface for use in LonWorks®

- » BMS interface based on LonTalk
- » Interface between Daikin DIII-Net and BMS LonTalk work station
 - Manages up to 64 indoor unit groups (128 indoor units) with network variables for each group
 - Manages 1 DIII-Net system
- » Lon Interface communicates over twisted pair wire
- » External Interface File (XIF) documents device information available at www.daikincomfort.com

Daikin's *BACnet*, *LonWorks* and *Modbus* interface units provides control for all VRV systems.

DTA116A51 - DIII-Net Modbus Adaptor

- » BMS interface based on Modbus (RS485)
- » Gateway between Daikin DIII-Net and BMS Modbus workstation
 - Manages up to 16 VRV indoor units connected to up to 2 outdoor units
- » Modbus interface communicates via Modbus RTU

DTA118A72 -DIII-NET/ BACnet MSTP Communication Adaptor

- » The DIII-Net/BACnet MS/TP Communication Adaptor enables the connection of VRV systems to a compatible Building Management System (BMS).
- » The adaptor operates as a BACnet router/gateway for the VRV system.
- » With this adaptor, a third-party BMS can monitor the VRV indoor units and outdoor units, as well as control the VRV indoor units through the *BACnet* MS/TP protocol.
- » The adaptor can be mounted to the VRV outdoor or indoor unit.



The Daikin *HERO* Simple Edge provides a connection of a Daikin VRV* system to the *HERO* Cloud Services network for remote monitoring. The *HERO* Simple Edge is mounted onto the outdoor unit, and the built-in SIM card provides wireless connectivity.

Daikin *HERO* Cloud Services is a remote monitoring service for Daikin VRV* systems. When integrated, data visualization of connected indoor and outdoor unit data and animated piping diagrams displaying operation status is provided. Daikin *HERO* Cloud Services also includes failure prediction for the compressors and sensors and refrigerant leak detection in the VRV system. In addition, *HERO* Cloud Services can help optimize the equipment operation based on outdoor ambient temperatures.

Elevate control through remote monitoring:

- » **Time and cost-saving opportunities** – Helps reduce unnecessary truck rolls and expand awareness of potential system issues.
- » **An owner-oriented design with a customizable dashboard** – Provides a quick overview of all connected sites and VRV systems.

HERO Cloud Services is based upon a recurring licensing fee to access site information. Licenses can be purchased in 1-year, 3-year, or 5-year increments, with no additional cost for the first-year access after the device is activated.

*Compatible with select Daikin VRV models.
Please visit daikinac.com to learn more.





Features and Benefits:

- » Mounts to the outdoor unit using powerful Neodymium magnets.
- » Powered by the outdoor unit and does not require separate power or panel build.
- » The built-in cellular connectivity¹ provides a simple connection to the cloud without burdening the building network and without the addition of expensive network gateways.
- » Connects directly to the Daikin VRV* outdoor unit system without needing additional adaptors or centralized controllers.
- » Simple device commissioning using a QR code.

System Capacity:

- » A maximum of one (1) Daikin VRV* outdoor unit system and its connected indoor units (up to 64) can be connected to the Simple Edge device.
- » Multiple Simple Edge devices can be connected on a site.
- » A single user account can monitor multiple sites.



¹ HERO Simple Edge uses cellphone communication. HERO Simple Edge cannot establish communication outside the service area, and it is possible, communication cannot be established even if installed within the service area but where cellphone signals are hard to reach, such as underground or on a high-rise building, etc.

*Compatible with select Daikin VRV models. Please visit daikinac.com to learn more.





Daikin *HERO* Pro Edge is a cloud-based VRV Centralized Controller that offers real-time remote control and monitoring, advanced analytics, and a customized dashboard. Daikin *HERO* Pro Edge can also control and monitor Daikin Mini-split/Multi-split, Daikin ERV (VAM), Daikin Rooftop Units, Daikin Applied *Rebel*, and third-party systems.


Daikin *HERO* Cloud Services is a remote monitoring and control service for Daikin VRV systems and other equipment connected to Daikin *HERO* Pro Edge. The *HERO* Cloud Services is based upon a recurring licensing fee to access site information. The *HERO* Pro Edge includes the first year *HERO* Cloud Services access for monitoring and control with the purchase of the hardware; licenses can be renewed in 1-year, 3-year, or 5-year increments.

System Capacity

- » 14 Outdoor units (Expand up to 56 Outdoor units with the use of option adaptor)
- » 128 Indoor units (Expand up to 512 Indoor Units with the use of option adaptor)
- » 3 Digital Outputs and 8 Digital Inputs (Expand up to 32 Digital Inputs with the use of option adaptors)
- » 512 WAGO® Inputs and Outputs
- » 1000 Total management points
- » 50 BACnet™ Devices for monitoring and control

Software Options




- » Power Proportional Distribution (one-time license activation) (DGE002A71)
 - Calculates apportionment of outdoor unit's total power consumption to individual indoor units on the system
- » BACnet Client (One time license activation)
 - Can be purchased in 10 device (DGE009A71) or 50 device (DGE009A72) license
 - Enabling the BACnet Client option allows the Pro Edge to use the BACnet/IP protocol
 - Allows for full monitoring and control of 3rd party BACnet capable equipment
 - Up to 512 BACnet management points
- » Tenant App (one-time license activation) (HGPFETEN-01)
 - Provides remote access for tenants to their indoor units in multi-family applications





Features of *HERO* Cloud Services with *HERO* Pro Edge

- » Remote monitoring for Daikin VRV outdoor and indoor unit operation data.
- » Intuitive, customizable dashboard provides quick status of connected units and sites.
- » Animated piping diagram based on system mode of operation.
- » Download or view historical data (up to 5 years) with built-in trending capabilities.
- » Alarm dashboard with automatic email notifications when an alarm occurs.
- » The Alarm details page provides in-depth information regarding an alarm with a detailed description, possible causes, tech tips, and a comment section.
- » The Energy Management dashboard is used to view energy consumption for the outdoor units (only for Daikin VRV *EMERION* units).
- » User management with customizable access for the user.
- » Monitor multiple outdoor and indoor units across multiple sites with a single login.
- » Advanced scheduling with Holidays and energy-saving settings.
- » Powerful indoor unit control features such as setpoint range limits, button lockouts, Setback, Auto changeover with deadband, and guard timer using Vote, Average, Individual, and Fixed methods.
- » Automatic registration of indoor units and outdoor units.
- » Tenant billing option (PPD) allows proportional billing of tenant's outdoor unit usage.
- » Control and monitor third-party equipment using WAGO® I/O
- » Control and monitor BACnet™ devices such (third-party unit *BACnet DDC*) using the *BACnet Client* optional license
- » Interlock programming for automated equipment control.
- » Tenant App allows tenants in multi-family building to have individual access to their assigned indoor units via an app on their smart device.



PART NUMBER	DESCRIPTION
DGE601A71	Daikin <i>HERO</i> Pro Edge
DGE601A72	Plus ADP for Daikin <i>HERO</i> Pro Edge and <i>iTM</i>
DGE601A53	Plus ADP Slot (For use with DGE601A72)
DGE002A71	Power Proportional Distribution (PPD) – Tenant billing
DGE009A71	Monitor up to 10 <i>BACnet</i> Devices
DGE009A72	Monitor up to 50 <i>BACnet</i> Devices
HGPFETEN-01	Allow tenant to monitor and controls assigned indoor units (no access to system data)
WAGOI/O	Monitor and control third-party units using I/O contacts.

¹ The power proportional distribution (PPD) feature supplies the user with a reasonably calculated apportionment of the total power consumption by the Daikin VRV system. Because input to the PPD includes measured pulses in the refrigerant system and because the VRV system includes a number of variables, including the operating temperatures and pressures, piping lengths, heat exchange rates, and so forth, no meter-type apportionment of individual user consumption can be made. However, the PPD feature provides an apportionment methodology that uses highly advanced technology and is applied to the many variables in the VRV system.



Daikin HERO Cloud Services is a remote monitoring and system control service for Daikin HVAC systems and ancillary equipment. When integrated, data visualization of connected HVAC equipment and animated piping diagrams displays operation status. Daikin HERO Cloud Services also includes failure predication for the compressors and refrigerant leak detection in the Daikin VRV System.

Elevate control through remote monitoring:

» **Time and cost-saving opportunities** – Helps reduce unnecessary truck rolls and expand awareness of potential system issues.

» **An owner-oriented design with a customizable dashboard** – Provides a quick overview of all connected sites and Daikin VRV systems.

Daikin HERO Cloud Services is based upon a recurring licensing fee to access site information. Licenses can be purchased in 1-year, 3-year, or 5-year increments, with no additional cost for the first-year access after the device is activated.

* Compatible with select Daikin VRV models.
Please visit daikinac.com to learn more.





- » Remote monitoring to help manage and diagnose system performance.
- » Uses predictive logic to notify of impending failures.
- » Visualize system performance through the integrated dashboard from a web browser or the Daikin *HERO* Cloud Services App.
- » Streamline service and maintenance for each site.
- » The Daikin *HERO* Simple Edge offers a secure cellular communication to the Daikin *HERO* Cloud Services use a built-in SIM card.
- » The Daikin *HERO* Pro Edge allows connecting to Daikin *HERO* Cloud Services by using the building internet (Ethernet) connection or use an optional LTE router for network free communication.

Daikin *HERO* Cloud Services license options: 1-year, 3-year, and 5-year licenses. Learn more at www.daikinhero.com



Daikin *HERO*
Simple Edge



Daikin *HERO*
Pro Edge

The Daikin *HERO* Cloud Services benefits include advantages for building owners, contractors, and Daikin representatives:

Building Owners

- » Peace of mind
- » Remote monitoring and control
- » Multisite access
- » Intuitive user interface

Daikin Representatives


- » Remote access to all buildings in your territory
- » Continuous commissioning
- » Provide a service solution to the end-user
- » Commissioning reports, maintenance check and system health check

Contractors

- » Remotely diagnose technical issues
- » Easy troubleshooting using multiple tools, live data, graphs, history trends, alarm console, etc
- » Error prediction and notifications




Remote monitoring and control
anytime, from anywhere




Multisite access and map view

- **Monitor and control** your building no matter where you are
- **Manage multiple sites**
- **Visualize energy** consumption and benchmark between different sites to help reduce energy costs
- **Remote diagnostic** support to help increase your systems lifetime
- **Predictive maintenance** to help prevent breakdowns
- **Remote troubleshooting** in case of malfunctions



Trending and report generation



Remote alarms for pre-diagnostics
with unique predictive logic



Energy Savings



Optimization recommendation
by Daikin experts




The Daikin *HERO* Cloud Services dashboard offers an overview of the accessible sites and provides the status of the total number of units displaying alarms, errors, warnings, or offline. The dashboard can be customized using the “Customize” button on the top right side of the page to fit the user’s role. The Customize button allows users to add or remove the widgets (Map, Subscription, and Energy management). For example:

- » The License widget will display the currently subscribed sites and the expiration date.

» The “Energy Management” widget offers customized bar chart views for the energy consumption of the selected unit. This widget will also give users a quick view of their site’s outdoor unit and indoor unit error status and mode of operation.

On the top right of the dashboard, users can switch to dark mode, check the current errors through the notification icon, request site access control through the “key icon,” and edit the user profile.





Individual Controllers

ITEM	MODEL NO.	FUNCTION
Navigation Remote Controller	BRCE173 (R-410A), BRCE1NRV71 <small>RS2</small>	Programmable zone controller
DKN Cloud Wi-Fi Adaptor	AZAI6WSCDKA	Remote control by smartphone app
Wireless Remote Controller	BRCE4C82 BRCE7E18 BRCE7E83 BRCE082A41W BRCE082A42S BRCE082A42W	Hand-held zone controller with infrared receiver kit
Daikin One+ Smart Thermostat	DTST-ONE-ADA-A	Smart thermostat with App control
Madoka Remote Controller	BRCE1H71W	Compact controller with Bluetooth setup App
Daikin One Touch	DTST-TOU-A	Smart thermostat with App control

Multi-Zone Controllers and Options

ITEM	MODEL NO.	FUNCTION
Intelligent Touch Manager (iTM)	intelligent Touch Manager (iTM)	Air-conditioning management system that can be controlled by touch screen or web browser to monitor and control up to 64 groups (10 outdoor units)
	HERO Pro Edge DIII Plus Adaptor / HERO Pro Edge DIII Plus ADP Slot	Up to 7 Plus adaptors can be connected to the iTM, Up to 6 Plus adaptors can be connected to the HERO Pro Edge. Each Plus Adaptor can add up to 64 additional groups (10 outdoor units)
	iTM PPD Option	Power consumption of indoor units are calculated based on operation status of the indoor unit and outdoor unit power consumption measured by kWh meter
	iTM Web (HTTP) Interface Option	The iTM Web IF (HTTP) software provides a building automation system or a home automation system the ability to monitor and control the VRV indoor units over the HTTP protocol.
	iTM BACnet™ Client Option	The BACnet Client Option enables the iTM to control and monitor equipment through the BACnet/IP protocol
	iTM BACnet Server Gateway Option*	The BACnet Server Gateway Option provide BMS integrators with the ability to monitor and control the VRV indoor units via the BACnet/IP protocol.
Daikin HERO Pro Edge	HERO Pro Edge	Air-conditioning management system that can be controlled by the HERO Cloud to monitor and control up to 64 groups (7 outdoor units)
	HERO Pro Edge DIII Plus Adaptors	Up to 6 Plus adaptors can be connected to the Hero Pro Edge. Up to 5 DGE601A53 can be used with the DGE601A72 when combined with the HERO Pro Edge
	HERO Pro Edge (PPD)	Power consumption of indoor units are calculated based on operation status of the indoor unit and outdoor unit. The power consumption measured by kWh meter
	HERO Pro Edge BACnet IP Client	The BACnet Client Option enables the HERO Pro Edge to control and monitor equipment through the BACnet/IP protocol (Up to 10 BACnet Devices)
		The BACnet Client Option enables the HERO Pro Edge to control and monitor equipment through the BACnet/IP protocol (Up to 50 BACnet Devices)
	HERO Tenant App	Allow tenant to monitor and controls assigned indoor units

*iTM BACnet Server Gateway Option is not compatible with iTM BACnet Client option.

Hardware Interface Solutions

ITEM	MODEL NO.	FUNCTION
DKN Plus Interface	AZAI6WSPDKC	Third-party thermostat/HAS integration through cloud, Modbus®, BACnet MS/TP, or G/Y/W connection
Interface for use in BACnet	DMS502B71	Interface unit to allow communications between VRV and BMS. Operation and monitoring of air-conditioning systems through BACnet/IP communication.
Optional DIII board	DAM411B51	Expansion kit, installed on DMS502B71, to provide 2 more DIII-NET communication ports. Not usable independently.
Interface for use in LonWorks®	DMS504C71	Interface unit to allow communications between VRV and BMS. Operation and monitoring of air-conditioning systems through LonWorks communication
Interface for use in Modbus®	DTA116A51	Use of the Modbus protocol enables the connection of the VRV system with a variety of home automation and BMS systems from other manufacturers.
DIII-Net/BACnet MS/TP Communication Adaptor	DTA118A72	Interface unit to allow communications between VRV and BMS. Operation and monitoring of air-conditioning systems through BACnet/MSTP communication.



Adaptors

ITEM	MODEL NO.	FUNCTION
DIII-Net Expander Adaptor	DTA109A51	Apply to increase the number of outdoor units (up to another 10) connected in one DIII-Net system. Apply to overcome communication errors in electrically noisy environments.
External control Adaptor for Outdoor Unit	DTA104A53/61/62	Unified changeover of Cool/Heat mode. To change the mode of several outdoor units by one remote controller. Demand Control. Low Noise Control: -2 to 3 dB of outdoor unit
Group Control Adaptor	KRP4A71/72/73/74	Turn On/Off Remote Control Group. Change set-point (with resistance interface 0-135 ohm). Monitor On/Off and Error status
ABC Terminal Kit	BRP2A81	Remotely manage the operating mode of the heat pump system. Integration point for ambient thermostats to engage lock-out
Wiring Adaptor	KPR1C74/75/76/77	Thermo-on status. Fan status. AUX heater output. Humidifier output
RA Interface Adaptor for DIII-Net Use	KRP928BB2S	Mini-split can be controlled through DIII-NET
RA PCB Adaptor for Time Clock	KRP413A1S	Remotely Start / Stop for mini-split indoor units

WAGO® I/O System

MODULE	PART NUMBER	DESCRIPTION
Basic Kit	60359653	Bus Coupler, Connector, 24 VDC Power Supply, and End Module
Digital Input	2 Channel DI 750-400	2 Channel Digital Input Module, 24 VDC
	4 Channel DI 750-432	4 Channel Digital Input Module, 24 VDC
	8 Channel DI 750-430	8 Channel Digital Input Module, 24 VDC
Digital Output	2 Channel DO 750-513/000-001	2 Channel Digital Output Module, without power jumper
	4 Channel DO 750-504	4 Channel Digital Output Module, 24 VDC
Analog Input	750-454	2 Channel Analog Input Module, 4-20 mA, Differential Inputs
	2 Channel AI 750-479	2 Channel Analog Input Module, ± 10 VDC, Differential Measurement Input
	750-461/020-000	2 Channel Analog Input Module, NTC 20k Ohm
	4 Channel AI 750-455	4 Channel Analog Input Module, 4-20 mA, single-ended
	750-459	4 Channel Analog Input Module, 0-10 VDC, single-ended
Analog Output	750-554	2 Channel Analog Output Module, 4-20 mA
	750-550	2 Channel Analog Output Module, 0-10 VDC
	750-555	4 Channel Analog Output Module, 4-20 mA
	750-559	4 Channel Analog Output Module, 0-10 VDC
Internal System Power Supply	750-613	24 VDC Bus Power Supply Module, Required for use after every 32 contact points connected in a node
Passive Power Supply	750-602	24 VDC Power Supply Module, passive
24 VDC Jumper	750-603	24 VDC Power Jumper Module, for use with 8 channel DI module


Daikin WAGO BACnet™/IP Controller and Parts

PART NUMBER	NAME	DESCRIPTION
759-302/000-923	WAGO I/O Check USB kit	WAGO I/O Check CD ROM and service cable
787-712	24 VDC Power Supply	24 VDC Power Supply
750-600	End Module	WAGO End Module



Support and Tools





Daikin's array of software and support tools are designed to streamline all stages of project design, application, installation and service/maintenance.


Daikin provides multiple tools to aid the design, selection, analysis, submission, and general support for its line up of ductless, rooftop, light commercial split and specifically for the full line of Daikin VRV systems.

The tools have been designed to be simple to use, easily accessible and to address the various considerations and steps in the evolution of a residential or commercial project, aimed at helping the architect, consulting engineer, contractor, installation technician, and service company to enhance workflows and general project execution.


Daikin VRV support and tools overview

CATEGORIES	TOOLS
	WebXpress Ventilation Xpress Controls Configurator Online Energy Calculator IES-VE Daikin VRV plug-in Performance curves for third-party energy simulation Programs CAD drawings Revit models Reference Charge Calculator Ventilation Rate Calculator Daikin City (including Guide Specs, IOMS etc.) Daikin equip application Dr. Daikin VRV Configurator Service Checker Online Spare Parts Bank
 Selection	
 Energy screening and simulation	
 Design and verification	
 Online and tablet reference (spec, data, submittal)	
 Smartphone and mobile reference	
 After sales and service	

Support and Tools (cont.)



WebXpress



IES-VE plug-in for Daikin VRV

Selection software

A key tool for Reps, Consulting Engineers and Contractors to use is the suite of **Xpress** selection software. These tools are web based and windows based EXE file designed to provide quick, easy and above all accurate selections of VRV systems and ventilation devices. Inputs can be customized to meet a variety of project needs and has the following features and benefits:

- » Fully array of software configuration settings
- » Select and customize indoor unit types with options/accessories
- » Optimize condensing unit selections based on block load characteristics
- » Define pipe sizes and lengths and both local and centralized wiring schemes
- » Define and generate selection reports in Word (DOC), Excel (XLS), or CAD (DXF) formats

As controls for variable refrigerant flow system systems become much more sophisticated at both a zone and building level, ensuring the full array of features are captured, Daikin has developed a simple **controls configurator tool** allowing the consulting engineer or contractor to capture all of the features that are needed to be utilized with the suite of controls products from Daikin so to ensure that the commissioning engineer can then set-up and configure the system appropriately at start up.

Energy screening and simulation tools

With the continued trend in looking at building costs beyond just the 1st cost, accurately screening or simulating the performance of systems in buildings at the conceptual stage is more important than ever. Daikin recognizes this need and has developed a variety of support tools for this purpose.

Online VRV energy calculator


- » Easy access and registration via online.
- » Free of charge and easy to use.
- » Allows for a semi-dynamic energy screening to be completed for VRV only. Provides useful information such as part load curves, estimated annualized operating costs etc.

IES-VE plug-in for Daikin VRV

- » One of the leading Energy Simulation programs in Europe is now gaining awareness and a growing user-base in North America.
- » With the Daikin VRV plug in for IES-VE you can take advantage of the enhanced energy simulation capabilities with the IES platform and combine in a fully validated modeling methodology for Daikin VRV systems including the innovative and energy saving "VRT" function. The results of the IES-VE simulations can be utilized for LEED®, California Title 24 and other regulatory energy simulation requirements.

» **Performance curve/plug-ins for 3rd party modeling software**

- » Daikin have developed curves, instructions and sample building files for a variety of other 3rd party energy simulation software programs such as:
 - eQuest
 - Trace 700
 - HAP
 - Energy Pro
 - Energy Plus (VRV HP only)



Revit



www.DaikinCity.com



Design and verification

Equipment Selection and Energy Simulation only reflect the early stages of a project evolution. At Daikin we recognize the importance of additionally providing resources to the Engineer and Architect community as well as contractors as follows:

- » **CAD files** for all products in multiple formats (DWG and DXF), etc.
- » **Revit files** for BIM architecture for all products
- » **Refrigerant Charge Calculator**
 - Quick check of the total refrigerant charge in a VRV System based on applied pipe-lengths and combination ratio's etc
 - Quick check of the minimum room volume (occupied space) that system charge can be utilized in per ASHRAE Standard 15-2010 and ASHRAE Standard 34-2010.
- » **Ventilation Rate Calculator**
 - Easy to use calculator to determine ventilation rates required for different room sizes and applications in accordance with ASHRAE Standard 62.1-2013.



Online and tablet reference material

Daikin City serves as the multi-functional portal for all disciplines interested in or already using Daikin products and technologies for a project. More than just a typical website, Daikin City provides:

- » Energy-saving characteristics of VRV systems in various vertical market buildings
- » Product videos and feature summaries via the communications center
- » A fully stocked library of information simply arranged for ease of finding any piece of Daikin information you may need such as IOM's, brochures, engineering data, and application guides etc (registration required).
- » Easy access to the suite of sales tools that Daikin offer (registration required).
- » An easy to use product specification library to quickly verify any spec item required, or to generate a submittal data sheet, guide spec or confirmation of the available accessories and options for a specific product (registration required).

Support and Tools (cont.)



Daikin eQuip application



www.DrDaikin.com



Smartphone and mobile reference

» With the **Daikin eQuip application**, available for both iOS devices and Android devices, you can have the power of all Daikin product information and support material readily accessible on your mobile device or tablet.

» For rapid resolution to a system with an error code, or general troubleshooting needs, the **Dr. Daikin tool** is a helpful and quick reference tool that works via a standard desktop, tablet or smartphone and even SMS. When you need to understand or isolate the scope of one of Daikin's diagnostic codes, enter the code into the Dr. Daikin resource and automatically the tool will provide feedback of what the diagnostic code refers to and straightforward guidance on how to address the code.

Visit www.drdaikin.com for further information.



Daikin's tools and support enables consulting engineers, building owners and installers to optimize the life cycle cost of the VRV systems.



Daikin VRV Configurator



Daikin's online spare parts databank



After sales and service

With a strong commitment to sales tools to help design and apply the product is equally supported with a strong commitment on after-sales and service tools aimed at the service contractor or maintenance technician.

- » **Daikin VRV Configurator** is a PC based software tool that allows an installing contractor to “set-up” the operating parameters and field settings of the VRV IV outdoor units off-site and then use a handy USB connection to upload those settings during the commissioning process. This helps save time and ensure that projects with multiple systems can be set up correctly and error free. The Configurator tool also allows for up to 48hrs of operation data from an installed system to be downloaded to a laptop computer for analysis if needed.
- » **Daikin VRV Service Checker** is a PC based software tool that facilitates a connection to the system and monitors all components of the system including temperatures, pressures, compressor and fan speeds, and may other items and can be utilized to understand operational trends with the system and what is happening in the system at a specific

time. This tool is very helpful when troubleshooting a system in the event of error or diagnostic notification.

- » **Daikin's online spare parts databank** (registration required) is an easy to use graphically driven means of identifying what spare or replacement part might be needed during the life cycle of the VRV equipment. Using this resource will help you identify the part number, applicable model, any alternative part options, and the availability of the part both locally and globally.
- » **Daikin University** offers Daikin's customers a variety of quality training programs designed to provide the tools and resources needed for our customers to be successful.
 - Our courses are designed by training professionals around specific objectives based on industry needs and job task analysis. We offer a choice of instructional settings based on the program goals and our students' needs including: online/on-demand web-based training, instructor led webinars, on-site training, and instructor-led classroom training at one of our many Daikin Authorized training facilities.


Notes





About Daikin:

Daikin Industries, Ltd. (DIL) is a global Fortune 1000 company and is recognized as one of the largest HVAC (Heating, Ventilation, Air Conditioning) manufacturers in the world. Founded in 1924, celebrated its 100 years of HVAC worldwide leadership in 2024. DIL is primarily engaged in developing indoor comfort systems and refrigeration products for residential, commercial, and industrial applications. Its consistent success is derived, in part, from a focus on innovative, energy-efficient, and premium quality indoor climate and comfort management solutions.



ADDITIONAL INFORMATION

Before purchasing this appliance, read important information about its estimated annual energy consumption, yearly operating cost, or energy efficiency rating that is available from your retailer.

Our continuing commitment to quality products may mean a change in specifications without notice.

© 2025 DAIKIN COMFORT TECHNOLOGIES NORTH AMERICA, INC.

Houston, Texas · USA · www.daikincomfort.com

R32

CT-VRV_04-25