

## Description

The Daikin *ONE* Wireless Relative Humidity and Temperature (RHT) Sensor is a compact, wireless sensor designed to measure the average temperature and humidity between the sensor and the thermostat. It delivers thermostat-like functionality by sensing temperature and humidity conditions with control and monitoring through the *SkyportCare* app.

Up to 8 Daikin *ONE* Wireless RHT Sensors can be connected to a single Daikin *ONE+* smart thermostat. Each sensor is battery-powered, requiring no wires, and can be easily mounted in any room, within the same controlled zone, to enhance comfort and efficiency compared to having only the Daikin *ONE+* smart thermostat by itself.

## Standard Features

- Cost-Effective, Thermostat-Like Control: Provides sensing only, but enables full control via the *SkyportHome* app-offering a smart, lower-cost alternative to installing additional thermostats without a physical display
- Wireless & Battery-Powered: Easy to mount anywhere — no wiring needed
- Zonal Comfort & Efficiency: Measures and averages temperature and humidity across rooms
- Compatible only with Daikin *ONE+* Smart Thermostat
- Sub-GHz Communication: No Wi-Fi required
- Battery Life: Up to 1 year
- Pairing wizard for signal strength, sensor naming, and calibration
- Multi-Sensor Support: Up to 8 sensors per thermostat
- App Integration: Connect and monitor via *SkyportCare*
- Location Range: Optimized for a 40ft\* distance from the Daikin *ONE+* Smart Thermostat in typical homes, with the flexibility for greater distances. Use the built-in pairing wizard to verify signal strength at your desired location before final mounting



SkyportCare



SkyportHome

<b>Model</b>	<b>DSEN-TH-BWS-A</b>
<b>Description</b>	Daikin <i>ONE</i> Wireless RHT Sensor
<b>Maximum Connections</b>	8 sensors per Daikin <i>ONE+</i>
<b>Power Requirements</b>	CR2450 Lithium Cell Battery
<b>Dimensions</b>	1.64"L x 1.64"W x .69"H
<b>Weight</b>	3.3oz
<b>Storage Temperature</b>	-22°F to 122°F
<b>Operating Temperature</b>	35°F to 104°F
<b>Humidity</b>	5-95% RH
<b>Compliance</b>	FCC (sub-gig ISM radio)
<b>Distance from Thermostat</b>	40 ft (12m)*

Note: \*Range may vary based on home construction materials, wireless interference, and other environmental factors. Always refer to the Quick Start Guide and use the pairing wizard to confirm signal strength before final mounting.



\* Complete warranty available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). To receive the 12-Year Parts Limited<sup>1</sup> Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California, Florida, or Québec. The duration of warranty coverages in Texas and Florida differs in some cases. Other limitations and exclusions apply, refer to complete warranty details for full list of limitations and exclusions.

<sup>1</sup> 12-Year Limited Warranty is available for owner-occupied residences only. For multi-family and/or commercial applications, the warranty period is 5-years.

