



Submittal Data Sheet

0.75 Ton One Way Blow Cassette

FXEQ09PVJU

FEATURES

- Compact design with 7-7/8" body height and 3-3/16" panel height
- Outside air integration ready (requires field supplied accessories)
- Energy efficient fan with 5 speed settings
- Mold resistant resin decoration panel that matches standard ceiling color
- Integral condensate pump with up to 25" lift

BENEFITS

- Increased overall heating effect due to the innovative discharge air louver design
- Compact heat exchanged and fan design to increase space saving



VRV





Submittal Data Sheet
0.75 Ton One Way Blow Cassette
FXEQ09PVJU

PERFORMANCE

Indoor Unit Model No.	FXEQ09PVJU	Indoor Unit Name:	0.75 Ton One Way Blow Cassette
Type:	Cassette	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Rated Cooling Capacity (Btu/hr):	9,500	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Sensible Capacity (Btu/hr):	7,100	Rated Piping Length(ft):	
Cooling Input Power (kW):		Rated Height Separation (ft):	
Rated Heating Capacity (Btu/hr):	10,500		

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (HH/H/M/L/SL) (CFM):	244/226/205/187/170
Power Supply Connections:		Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):	0.4	Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):	15	Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	7-7/8 x 33-1/16 x 18-1/2	Condensate Connection (inch):	1-1/32
Net Weight (lb):	37.5	Sound Pressure (H/M/L/SL) (dBA):	31/30/29/28
Ext. Static Pressure (Rated/Max) (inWg):	/	Sound Power Level (dBA):	

Submittal Data Sheet
0.75 Ton One Way Blow Cassette
FXEQ09PVJU

DIMENSIONAL DRAWING

