



Submittal Data Sheet

1.5 Ton One Way Blow Cassette

FXEQ18PVJU

FEATURES

- Compact design with 7-7/8" body height and 3-3/16" panel height
- Outside air integration ready (requires field supplied accessories)
- Energy efficient fan with 5 speed settings
- Mold resistant resin decoration panel that matches standard ceiling color
- Integral condensate pump with up to 25" lift

BENEFITS

- Increased overall heating effect due to the innovative discharge air louver design
- Compact heat exchanged and fan design to increase space saving





Submittal Data Sheet

1.5 Ton One Way Blow Cassette

FXEQ18PVJU

PERFORMANCE

| | | | |
|----------------------------------|------------|-------------------------------|---|
| Indoor Unit Model No. | FXEQ18PVJU | Indoor Unit Name: | 1.5 Ton One Way Blow Cassette |
| Type: | Cassette | Rated Cooling Conditions: | Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75 |
| Rated Cooling Capacity (Btu/hr): | 18,000 | Rated Heating Conditions: | Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43 |
| Sensible Capacity (Btu/hr): | 12,900 | Rated Piping Length(ft): | |
| Cooling Input Power (kW): | | Rated Height Separation (ft): | |
| Rated Heating Capacity (Btu/hr): | 20,000 | | |

INDOOR UNIT DETAILS

| | | | |
|--|---------------------------|-----------------------------------|---------------------|
| Power Supply (V/Hz/Ph): | 208-230 / 60 / 1 | Airflow Rate (HH/H/M/L/SL) (CFM): | 441/403/367/336/307 |
| Power Supply Connections: | | Moisture Removal (Gal/hr): | |
| Min. Circuit Amps MCA (A): | 0.5 | Gas Pipe Connection (inch): | 1/2 |
| Max Overcurrent Protection (MOP) (A): | 15 | Liquid Pipe Connection (inch): | 1/4 |
| Dimensions (HxWxD) (in): | 7-7/8 x 48-13/16 x 18-1/2 | Condensate Connection (inch): | 1-1/32 |
| Net Weight (lb): | 50.7 | Sound Pressure (H/M/L/SL) (dBA): | 37/35/33/31 |
| Ext. Static Pressure (Rated/Max) (inWg): | / | Sound Power Level (dBA): | |

Submittal Data Sheet
1.5 Ton One Way Blow Cassette
FXEQ18PVJU

DIMENSIONAL DRAWING

