



## Submittal Data Sheet

3.0 T Residential VRV

RXSQ36TBVJUA

## FEATURES

- Choice of Heat Pump or Gas Furnace or Dual-Fuel heating capability
- Field customizable and programmable temperatures to switch from Heat pump to gas furnace
- 1 to 1 and 1 to multi connection capable
- Dependable heat pump operation from -4 °F in heating to 122 °F in cooling
- Engineered with Daikin Swing compressor
- Diverse selection of Indoor units with 15 types and 79 models to choose from

## BENEFITS

- Superior zoning capability with connection to up to 9 indoor units
- Quiet operation with sound levels of under 58 dBA make install close to lot lines easy
- Reduced install cost with re-use of existing refrigerant lines and uninsulated liquid line
- Light weight design for easy install and transportation
- Compact design to reduce mechanical space required by up to 75%



VRV





## Submittal Data Sheet

3.0 T Residential VRV

RXSQ36TBVJUA

### PERFORMANCE

Outdoor Unit Model No.	RXSQ36TBVJUA	Outdoor Unit Name:	3.0 T Residential VRV
Type:	Heat Pump		
Rated Cooling Conditions:	Indoor (°F DB/DB): 80 / 67 Ambient (°F DBWB):95 / 75	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Piping Length(ft):			
Rated Height Difference (ft):			
Rated Cooling Capacity (Btu/hr):	34,200 / 34,200	Rated Heating Capacity @ 47F Non-Ducted/Ducted(Btu/hr):	37,000 / 37,000
Cooling Input Power (kW):	Heating Input Power (kW):		
EER2 (Non-Ducted/Ducted):	12.00 / 9.20	Heating COP@ 47F (Non-Ducted/Ducted):	4.1 / 3.3
SEER2 (Non-Ducted/Ducted):	18.20 / 15.30	HSPF2 (Non-Ducted/Ducted):	9.0 / 8.5
Max/Min Cooling Capacity (Btu/hr):	/	Max/Min Heating Capacity (Btu/hr):	

### OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Compressor Stage:	
Power Supply Connections:	L1, L2, G	Capacity Control Range (%):	14 - 100
Min. Circuit Amps MCA (A):	16.5	Airflow Rate (H) (CFM):	
Max Overcurrent Protection (MOP) (A):	20	Gas Pipe Connection (inch):	5/8
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	3/8
Rated Load Amps RLA(A):		Sound Pressure (H) (dBA):	58
Dimensions (HxWxD) (in):	39 x 37 x 12-5/8	Sound Power Level (dBA):	75
Net Weight (lb):	172		

# Submittal Data Sheet

3.0 T Residential VRV  
RXSQ36TBVJUA

## SYSTEM DETAILS

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	122 - 23
Holding Refrigerant Charge (lbs):	6.4	Heating Operation Range (°F WB):	-4 - 60
Additional Charge (lb/ft):		Max. Pipe Length (Vertical) (ft):	98
Pre-charge Piping (Length) (ft):		Cooling Range w/Baffle (°F DB):	-
Max. Pipe Length (Total) (ft):	328	Heating Range w/Baffle (°F WB):	-
Max Height Separation (Ind to Ind ft):	33		

## DIMENSIONAL DRAWING

